Product datasheet

Specifications





Time delay auxiliary contact block, TeSys Deca, 1NO+1NC, on delay 1-30s, front, lugs-ring terminals

LADT26

Main

Range	TeSys
	TeSys Deca
Product name	TeSys Deca
product or component type	Time delay auxiliary contact block
Range compatibility	TeSys D CAD
	TeSys D LC1D
	TeSys F LC1F
	TeSys F CR1F
	TeSys Deca CAD
	TeSys Deca LC1D
mounting location	Front
Pole contact composition	1 NO + 1 NC
Contacts operation	Time delay
Timer type	On delay
time delay range	130 s
[Ue] rated operational voltage	690 V AC 25400 Hz
[le] rated operational current	6 A at 120 V AC-15
	1.04 A at 690 V AC-15
	0.55 A at 125 V DC-13
	0.1 A at 600 V DC-13
	0.17/4/000 / 2010
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1
	600 V conforming to UL
	600 V conforming to CSA
[Ith] conventional free air thermal current	10 A (at 60 °C)
Standards	EN/IEC 60947-5-1
	UL 60947-5-1
	CSA C22.2 No 60947-5-1
	GB/T 14048.5
	EN 50012
	IEC 60335-1:Clause 30.2
	IEC 60335-2-40:Annex JJ
	UL 60335-2-40:Annex JJ
Product certifications	CB
	UL
	CSA
	CCC
	EAC
	UKCA

Complementary

Irms rated making capacity

140 A AC 250 A DC

Permissible short-time rating	100 A 60 °C 1 s
	120 A 60 °C 500 ms
	140 A 60 °C 100 ms
Protection type	GG fuse 10 A
Mechanical durability	5 Mcycles
Minimum switching current	5 mA
	3114
Minimum switching voltage	17 V
Non-overlap time	1.5 ms on de-energisation no overlap between NC and NO contact
	1.5 ms on energisation no overlap between NC and NO contact
	- ·
Insulation resistance	> 10 MOhm
Connections - terminals	Lugs-ring terminals (external diameter: 8 mm)
Tightening torque	1.7 N.m - with screwdriver flat Ø 6 mm
lightening torque	
	1.7 N.m - with screwdriver Philips No 2
	1.7 N.m - with screwdriver pozidriv No 2
Height	48 mm
Width	44 mm
Depth	61 mm
Colour Dark grey	

Environment

Environmental characteristic	Normal environment	
IP degree of protection	IP2X conforming to IEC 60529	
Protective treatment	TH conforming to IEC 60068	
ambient air temperature for storage	-6080 °C	
ambient air temperature for operation	-4070 °C	
Operating altitude	3000 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	5.3 cm
Package 1 Length	6.6 cm
Package 1 Weight	73 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.3 cm
Package 2 Width	24.3 cm
Package 2 Length	5.2 cm
Package 2 Weight	755 g
Unit Type of Package 3	S03
Number of Units in Package 3	140
Package 3 Height	30 cm

Package 3 Width	30 cm	
Package 3 Length	40 cm	
Package 3 Weight	10.712 kg	

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Sustainable Packaging Transparency RoHS/REACh

Resource performance

Sustainable Packaging

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations