Product datasheet

Specifications





TeSys D contactor - 3P(3 NO) -AC-3 - <= 440 V 12 A - 115 V AC coil

LC1D12FE7

(!) Discontinued

Main

Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Motor control Resistive load
Utilisation Category	AC-4 AC-1 AC-3 AC-3e
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC
[le] Rated Operational Current	25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 12 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 12 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Uc] Control Circuit Voltage	115 V AC 50/60 Hz

Complementary

Motor Power Kw	3 kW at 220230 V AC 50/60 Hz (AC-3)		
	5.5 kW at 380400 V AC 50/60 Hz (AC-3)		
	5.5 kW at 415440 V AC 50/60 Hz (AC-3)		
	7.5 kW at 500 V AC 50/60 Hz (AC-3)		
	7.5 kW at 660690 V AC 50/60 Hz (AC-3)		
	3.7 kW at 400 V AC 50/60 Hz (AC-4)		
	3 kW at 220230 V AC 50/60 Hz (AC-3e)		
	5.5 kW at 380400 V AC 50/60 Hz (AC-3e)		
	5.5 kW at 415440 V AC 50/60 Hz (AC-3e)		
	7.5 kW at 500 V AC 50/60 Hz (AC-3e)		
	7.5 kW at 660690 V AC 50/60 Hz (AC-3e)		
Motor Power Hp	0.5 hp at 115 V AC 50/60 Hz for 1 phase motors		
	2 hp at 230/240 V AC 50/60 Hz for 1 phase motors		
	3 hp at 200/208 V AC 50/60 Hz for 3 phases motors		
	3 hp at 230/240 V AC 50/60 Hz for 3 phases motors		
	7.5 hp at 460/480 V AC 50/60 Hz for 3 phases motors		
	10 hp at 575/600 V AC 50/60 Hz for 3 phases motors		
Compatibility Code	LC1D		
Pole Contact Composition	3 NO		
Protective Cover	With		
[Ith] Conventional Free Air	25 A (at 60 °C) for power circuit		
Thermal Current	10 A (at 60 °C) for signalling circuit		

Irms Rated Making Capacity	250 A at 440 V for power circuit conforming to IEC 60947
	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	250 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand	105 A 40 °C - 10 s for power circuit
Current	210 A 40 °C - 1 s for power circuit
	30 A 40 °C - 10 min for power circuit
	61 A 40 °C - 1 min for power circuit
	100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	40 A gG at <= 690 V coordination type 1 for power circuit
	25 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power Dissipation Per Pole	0.36 W AC-3
· · · · · · · · · · · · · · · · · · ·	1.56 W AC-1
	0.36 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit: 600 V conforming to IEC 60047.4.1
Long Mateu moulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified
	Power circuit: 600 V UL certified
	Signalling circuit: 690 V conforming to IEC 60947-1
	Signalling circuit: 600 V CSA certified
	Signalling circuit: 600 V UL certified
Overvoltage Category	III
Pollution Degree	3
This and the second second second	
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
	13849-1
Mechanical Durability	15 Mcycles
Electrical Durability	2 Mcycles 12 A AC-3 at Ue <= 440 V
	0.8 Mcycles 25 A AC-1 at Ue <= 440 V
	2 Mcycles 12 A AC-3e at Ue <= 440 V
Control Circuit Type	AC at 50/60 Hz standard
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz
	0.81.1 Uc (-4060 °C):operational AC 50 Hz
	0.851.1 Uc (-4060 °C):operational AC 60 Hz 11.1 Uc (6070 °C):operational AC 50/60 Hz
Inmuch Rower In V-	
Inrush Power In Va	70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C)
	10 VA 30 112 COS pill 0.73 (at 20 C)
Hold-In Power Consumption In Va	7.5 VA 60 Hz cos phi 0.3 (at 20 °C)
	7 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	23 W at 50/60 Hz
Operating Time	1222 ms closing
	419 ms opening
Maximum Operating Bata	0000 mm/h 00 %0
Maximum Operating Rate	3600 cyc/h 60 °C

Connections - Terminals	Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible without cable end		
	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end		
	Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable end		
	Power circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end		
	Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without cable end		
	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without cable end		
	Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible without cable end		
	Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end		
	Control circuit: screw clamp terminals 1 14 \mbox{mm}^2 - cable stiffness: flexible with cable end		
	Control circuit: screw clamp terminals 2 12.5 $\mbox{ mm}^2$ - cable stiffness: flexible with cable end		
	Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without cable end		
	Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without cable end		
Tightening Torque	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat \emptyset 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat \emptyset 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2		
Auxiliary Contact Composition	1 NO + 1 NC		
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1		
Signalling Circuit Frequency	25400 Hz		
Minimum Switching Voltage	17 V for signalling circuit		
	5 mA for signalling circuit		
Minimum Switching Current			
_	> 10 MOhm for signalling circuit		
Minimum Switching Current Insulation Resistance Non-Overlap Time	 > 10 MOhm for signalling circuit 1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact 		

Environment

Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 IEC 60335-1
Product Certifications	GL BV DNV LROS (Lloyds register of shipping) RINA UL CCC CSA GOST UKCA CB
Ip Degree Of Protection	IP20 front face conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068-2-30

Climatic Withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat		
Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating		
Operating Altitude	03000 m		
Fire Resistance	850 °C conforming to IEC 60695-2-1		
Flame Retardance	V1 conforming to UL 94		
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor open (10 Gn for 11 ms) Shocks contactor closed (15 Gn for 11 ms)		
Height	77 mm		
Width	45 mm		
Depth	86 mm		
Net Weight	0.325 kg		

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	8.000 cm
Package 1 Length	9.500 cm
Package 1 Weight	355.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	20
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.434 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	320
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	129.380 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance


Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes
 Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Dimensions Drawings

Dimensions



- (1) Including LAD 4BB
- (2) Minimum electrical clearance

LC1		D09D18	D093D123	D099D129
b	without add-on blocks	77	99	80
	with LAD 4BB	94	107	95.5
	with LA4 D•2	110 ⁽¹⁾	₁₂₃ (1)	111.5 (1)
b1	with LA4 DF, DT	119 (1)	132 ⁽¹⁾	120.5 ⁽¹⁾
	with LA4 DW, DL	126 (1)	₁₃₉ (1)	_{127.5} (1)
	without cover or add-on blocks	84	84	84
c with cove	with cover, without add-on blocks	86	86	86
c1	with LAD N or C (2 or 4 contacts)	117	117	117
c2	with LA6 DK10, LAD 6K10	129	129	129
- 2	with LAD T, R, S	137	137	137
c3	with LAD T, R, S and sealing cover	141	141	141
(1)	Including LAD 4BB.			

Product datasheet

Connections and Schema

Wiring

