# Product data sheet

Specifications





IEC contactor, TeSys Deca Green, nonreversing, 25A, 15HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 100/250VAC/VDC coil

LC1D25KUE

Product availability: Stock - Normally stocked in distribution facility

Price\*: 59.00 USD

#### Main

Range	TeSys TeSys Deca	
Range Of Product	TeSys Deca	
Product Or Component Type	Contactor	
Device Short Name	LC1D	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-3 AC-1 AC-3e	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz	
[le] Rated Operational Current	25 A (at <140 °F (60 °C)) at <= 440 V AC-3 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC-1 for power circuit 25 A (at <140 °F (60 °C)) at <= 440 V AC-3e for power circuit	
[Uc] Control Circuit Voltage	100250 V AC 50/60 Hz 100250 V DC	

### Complementary

Motor Power Kw	5.5 kW at 220230 V AC 50 Hz (AC-3)
	11 kW at 380400 V AC 50 Hz (AC-3)
	11 kW at 415 V AC 50 Hz (AC-3)
	11 kW at 440 V AC 50 Hz (AC-3)
	15 kW at 500 V AC 50 Hz (AC-3)
	15 kW at 660690 V AC 50 Hz (AC-3)
	5.5 kW at 220230 V AC 50 Hz (AC-3e)
	11 kW at 380400 V AC 50 Hz (AC-3e)
	11 kW at 415 V AC 50 Hz (AC-3e)
	11 kW at 440 V AC 50 Hz (AC-3e)
	15 kW at 500 V AC 50 Hz (AC-3e)
	15 kW at 660690 V AC 50 Hz (AC-3e)
Maximum Horse Power Rating	2 hp at 115 V AC 60 Hz for 1 phase motors
	3 hp at 230/240 V AC 60 Hz for 1 phase motors
	7.5 hp at 200/208 V AC 60 Hz for 3 phase motors
	7.5 hp at 230/240 V AC 60 Hz for 3 phase motors
	15 hp at 460/480 V AC 60 Hz for 3 phase motors
	20 hp at 575/600 V AC 60 Hz for 3 phase motors
Compatibility Code	LC1D
Pole Contact Composition	3 NO
	0.110

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Protective Cover	With
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C)) for signalling circuit 40 A (at 140 °F (60 °C)) for power circuit
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 450 A at 440 V for power circuit conforming to IEC 60947
Rated Breaking Capacity	450 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit 50 A 104 °F (40 °C) - 10 min for power circuit 120 A 104 °F (40 °C) - 1 min for power circuit 240 A 104 °F (40 °C) - 10 s for power circuit 380 A 104 °F (40 °C) - 1 s for power circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit 40 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2 mOhm - Ith 40 A 50 Hz for power circuit
Power Dissipation Per Pole	3.2 W AC-1 1.25 W AC-3 1.25 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	15 Mcycles
Electrical Durability	2 Mcycles 21 A AC-3 <= 440 V 0.9 Mcycles 40 A AC-1 <= 440 V 2 Mcycles 21 A AC-3e <= 440 V
Control Circuit Type	AC/DC 50/60 Hz AC/DC electronic
Coil Technology	Built-in bidirectional peak limiting
Control Circuit Voltage Limits	<= 0.1 Uc -40158 °F (-4070 °C) drop-out AC/DC 0.851.1 Uc -40140 °F (-4060 °C) operational AC/DC 11.1 Uc 140158 °F (6070 °C) operational AC/DC
Inrush Power In Va	25 VA 50/60 Hz (at 68 °F (20 °C))
Inrush Power In W	18 W 68 °F (20 °C))
Hold-In Power Consumption In Va	1.6 VA 50/60 Hz (at 68 °F (20 °C))
Hold-In Power Consumption In W	1.1 W 68 °F (20 °C)
Heat Dissipation	1.1 W at 50/60 Hz
Operating Time	4555 ms closing 2090 ms opening
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

Connections - Terminals	Control circuit: screw clamp terminals 1 0.000.01 in² (14 mm²) - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 0.000.01 in² (14 mm²) - cable stiffness:
	flexible without cable end  Control circuit: screw clamp terminals 1 0.000.01 in² (14 mm²) - cable stiffness:
	flexible with cable end  Control circuit: screw clamp terminals 2 0.000.00 in² (12.5 mm²) - cable stiffness:
	flexible with cable end
	Control circuit: screw clamp terminals 1 0.000.01 in² (14 mm²) - cable stiffness: solid
	Control circuit: screw clamp terminals 2 0.000.01 in² (14 mm²) - cable stiffness: solid
	Power circuit: screw clamp terminals 1 0.000.02 in² (2.510 mm²) - cable stiffness: flexible without cable end
	Power circuit: screw clamp terminals 2 0.000.02 in² (2.510 mm²) - cable
	stiffness: flexible without cable end Power circuit: screw clamp terminals 1 0.000.02 in² (110 mm²) - cable stiffness:
	flexible with cable end Power circuit: screw clamp terminals 2 0.000.01 in² (1.56 mm²) - cable stiffness:
	flexible with cable end
	Power circuit: screw clamp terminals 1 0.000.02 in² (1.510 mm²) - cable stiffness: solid
	Power circuit: screw clamp terminals 2 0.000.02 in² (2.510 mm²) - cable stiffness: solid
Tightening Torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm
	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm
	Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat \$6 \text{ film}  Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals Philips No 2
	Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals pozidriv No 2 M4
	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2 M3.5
Auxiliary Contact Composition 1 NO + 1 NC	
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	<ul><li>1.5 ms on de-energisation between NC and NO contact</li><li>1.5 ms on energisation between NC and NO contact</li></ul>
Mounting Support	Plate Rail
Environment	
Standards	EN/IEC 60947-4-1
	EN/IEC 60947-5-1 UL 60947-4-1
	CSA C22.2 No 60947-4-1
	IEC 60335-1
Product Certifications	CCC
	CSA
	EAC UL
	KC
	DNV-GL
	LROS (Lloyds register of shipping) UKCA
Ip Degree Of Protection	IP20 front face IEC 60529
Climatic Withstand	IACS E10 exposure to damp heat IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating
Operating Altitude	09842.52 ft (03000 m)

Fire Resistance	1562 °F (850 °C) IEC 60695-2-1	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor closed 15 Gn for 11 ms) Shocks contactor open 8 Gn for 11 ms)	
Height	3.35 in (85 mm)	
Width	1.77 in (45 mm)	
Depth	3.62 in (92 mm)	
Net Weight	0.95 lb(US) (0.433 kg)	

# Ordering and shipping details

Category	US10I1222356	
Discount Schedule	scount Schedule 0l12	
Gtin	3606480987748	
Returnability	Yes	
Country Of Origin	FR	

## **Packing Units**

_		
Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	2.17 in (5.500 cm)	
Package 1 Width	3.74 in (9.500 cm)	
Package 1 Length	4.65 in (11.800 cm)	
Package 1 Weight	16.01 oz (454.000 g)	
Unit Type Of Package 2	S02	
Number Of Units In Package 2	15	
Package 2 Height	5.91 in (15.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	<b>Length</b> 15.75 in (40.000 cm)	
Package 2 Weight	age 2 Weight 15.67 lb(US) (7.110 kg)	

## **Contractual warranty**

Warranty 18 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
	Halogen Free Plastic Parts & Cables Product	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information