Product data sheet

Specification





IEC contactor, TeSys Deca Green, nonreversing, 40A, 30HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 100/250VAC/VDC coil

LC1D40AKUE

Product availability: Stock - Normally stocked in distribution facility

Price*: 99.00 USD

Main

Range	TeSys TeSys Deca
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load Motor control
Utilisation Category	AC-1 AC-3 AC-3e
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25400 Hz
[le] Rated Operational Current	60 A (at <140 °F (60 °C)) at <= 440 V AC-1 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC-3 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC-3e for power circuit
[Uc] Control Circuit Voltage	100250 V AC 50/60 Hz 100250 V DC

Complementary

Motor Power Kw	11 kW at 220230 V AC 50 Hz (AC-3)
	18.5 kW at 380400 V AC 50 Hz (AC-3)
	22 kW at 415 V AC 50 Hz (AC-3)
	22 kW at 440 V AC 50 Hz (AC-3)
	22 kW at 500 V AC 50 Hz (AC-3)
	30 kW at 660690 V AC 50 Hz (AC-3)
	11 kW at 220230 V AC 50 Hz (AC-3e)
	18.5 kW at 380400 V AC 50 Hz (AC-3e)
	22 kW at 415 V AC 50 Hz (AC-3e)
	22 kW at 440 V AC 50 Hz (AC-3e)
	22 kW at 500 V AC 50 Hz (AC-3e)
	30 kW at 660690 V AC 50 Hz (AC-3e)
Maximum Horse Power Rating	3 hp at 115 V AC 60 Hz for 1 phase motors
	5 hp at 230/240 V AC 60 Hz for 1 phase motors
	10 hp at 200/208 V AC 60 Hz for 3 phase motors
	10 hp at 230/240 V AC 60 Hz for 3 phase motors
	10 hp at 230/240 V AC 60 Hz for 3 phase motors 30 hp at 460/480 V AC 60 Hz for 3 phase motors
	,
Compatibility Code	30 hp at 460/480 V AC 60 Hz for 3 phase motors

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Protective Cover	With
[Ith] Conventional Free Air Thermal Current	60 A (at 140 °F (60 °C)) for power circuit 10 A (at 140 °F (60 °C)) for signalling circuit
Irms Rated Making Capacity	800 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	800 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	72 A 104 °F (40 °C) - 10 min for power circuit 165 A 104 °F (40 °C) - 1 min for power circuit 320 A 104 °F (40 °C) - 10 s for power circuit 720 A 104 °F (40 °C) - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated Fuse Rating	80 A gG at <= 690 V coordination type 1 for power circuit 80 A gG at <= 690 V coordination type 2 for power circuit 10 A gG for signalling circuit conforming to IEC 60947-5-1
Average Impedance	1.5 mOhm - Ith 60 A 50 Hz for power circuit
Power Dissipation Per Pole	5.4 W AC-1 2.4 W AC-3 2.4 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	6 Mcycles
Electrical Durability	2 Mcycles 35 A AC-3 <= 440 V 0.7 Mcycles 60 A AC-1 <= 440 V 2 Mcycles 35 A AC-3e <= 440 V
Control Circuit Type	AC/DC 50/60 Hz AC/DC electronic
Coil Technology	Built-in bidirectional peak limiting
Control Circuit Voltage Limits	<= 0.1 Uc -40158 °F (-4070 °C) drop-out AC/DC 0.851.1 Uc -40140 °F (-4060 °C) operational AC/DC 11.1 Uc 140158 °F (6070 °C) operational AC/DC
Inrush Power In Va	18 VA 50/60 Hz (at 68 °F (20 °C))
Inrush Power In W	14 W 68 °F (20 °C))
Hold-In Power Consumption In Va	1.8 VA 50/60 Hz (at 68 °F (20 °C))
Hold-In Power Consumption In W	1.2 W 68 °F (20 °C)
Heat Dissipation	1.2 W at 50/60 Hz
Operating Time	5565 ms closing 20120 ms opening >= 17221) 2080 ms opening >= 18011)
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

iess:
iess:
ffness:
iess:
iess:
cable
Lable
cable
n²
n² (1

Operating Altitude	09842.52 ft (03000 m)	
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)	
Height	4.80 in (122 mm)	
Width	2.17 in (55 mm)	
Depth	4.72 in (120 mm)	
Net Weight	2.19 lb(US) (0.992 kg)	

Ordering and shipping details

Category	US10I1222356
Discount Schedule	0112
Gtin	3606480988226
Returnability	Yes
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.44 in (6.2 cm)
Package 1 Width	5.39 in (13.7 cm)
Package 1 Length	5.98 in (15.2 cm)
Package 1 Weight	2.32 lb(US) (1.052 kg)
Unit Type Of Package 2	S02
Number Of Units In Package 2	9
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	21.55 lb(US) (9.774 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information