# **Product data sheet**

Specifications





IEC contactor, TeSys D, nonreversing, 65A, 40HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 200VAC 60Hz coil, open style

LC1D65L6

Product availability: Stock - Normally stocked in distribution facility

Price\*: 532.80 USD

#### Main

Range	TeSys
Range of Product	TeSys Deca
Product or Component Type	Contactor
Device short name	LC1D
contactor application	Motor control Resistive load
	Nesistive load
Utilisation category	AC-3
	AC-4
	AC-1
	AC-2
	AC-3e
poles description	3P
[Ue] rated operational voltage	Power circuit <= 690 V AC 25400 Hz
[le] rated operational current	80 A (at <140.0000000000 °F (60 °C)) at <= 440 V AC AC-1 for power circuit
	65 A (at <140.0000000000 °F (60 °C)) at <= 440 V AC AC-3 for power circuit
	65 A (at <140.0000000000 °F (60 °C)) at <= 440 V AC AC-3e for power circuit
[Uc] control circuit voltage	200 V AC 60 Hz

### Complementary

Motor power kW	30 kW at 440 V AC 50/60 Hz 30 kW at 380400 V AC 50/60 Hz 37 kW at 500 V AC 50/60 Hz 37 kW at 660690 V AC 50/60 Hz 18.5 kW at 220230 V AC 50/60 Hz 30 kW at 415 V AC 50/60 Hz 37 kW at 1000 V AC 50/60 Hz
Maximum Horse Power Rating	10 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to CSA 10 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to UL 20 hp at 200/208 V AC 60 Hz for 3 phase motors conforming to USA 20 hp at 200/208 V AC 60 Hz for 3 phase motors conforming to UL 20 hp at 230/240 V AC 60 Hz for 3 phase motors conforming to CSA 20 hp at 230/240 V AC 60 Hz for 3 phase motors conforming to UL 5 hp at 115 V AC 60 Hz for 1 phase motors conforming to USA 5 hp at 115 V AC 60 Hz for 1 phase motors conforming to UL 50 hp at 460/480 V AC 60 Hz for 3 phase motors conforming to CSA 50 hp at 460/480 V AC 60 Hz for 3 phase motors conforming to UL 50 hp at 575/600 V AC 60 Hz for 3 phase motors conforming to UL 50 hp at 575/600 V AC 60 Hz for 3 phase motors conforming to USA
Compatibility code	LC1D
Pole contact composition	3 NO

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Protective cover	With
[Ith] conventional free air thermal current	10 A (at 140.0000000000 °F (60 °C)) for control circuit 80 A (at 140.0000000000 °F (60 °C)) for power circuit
Irms rated making capacity	140 A AC for control circuit conforming to IEC 60947-5-1 1000 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	1000 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 125 A gG at <= 690 V coordination type 1 for power circuit 125 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	1 mOhm - Ith 80 A 50 Hz for power circuit
Power dissipation per pole	6.4 W AC-1
[Ui] rated insulation voltage	Control circuit 600 V CSA Control circuit 600 V UL Power circuit 600 V CSA Power circuit 600 V UL Control circuit 690 V IEC 60947-1 Power circuit 690 V IEC 60947-1
Overvoltage category	III
[Uimp] rated impulse withstand voltage	8 kV IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	6000000 cycles
Control circuit type	AC 60 Hz
Coil technology	Without built-in bidirectional peak limiting diode suppressor
Control circuit voltage limits	0.30.6 Uc 140.0000000000 °F (60 °C) drop-out AC 50/60 Hz 0.851.1 Uc 140.0000000000 °F (60 °C) operational AC 60 Hz
Inrush power in VA	140 VA cos phi 0.75 (at 68.0000000000 °F (20 °C)) 160 VA cos phi 0.75 (at 68.0000000000 °F (20 °C))
Hold-in power consumption in VA	13 VA 50 Hz cos phi 0.3 (at 68.0000000000 °F (20 °C)) 15 VA 60 Hz cos phi 0.3 (at 68.0000000000 °F (20 °C))
Heat dissipation	45 W at 50/60 Hz for control circuit
Operating time	1226 ms closing 419 ms opening
Maximum operating rate	3600 cyc/h 140.0000000000 °F (60 °C)
Connections - terminals	Control circuit: screw clamp terminal 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminal 1 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 1 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminal 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminal 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Power circuit: connector 1 0.0040.05 in² (2.535 mm²) - cable stiffness: solid with cable end Power circuit: connector 2 0.0040.05 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 2 0.0040.04 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 1 0.0040.05 in² (2.535 mm²) - cable stiffness: flexible without cable end Power circuit: connector 2 0.0040.05 in² (2.535 mm²) - cable stiffness: flexible with cable end Power circuit: connector 1 0.0040.05 in² (2.535 mm²) - cable stiffness: flexible with cable end

Tightening torque	Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminal flat Ø 6 mm
	Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminal Philips No 2
	Power circuit 44.3 lbf.in (5 N.m) screw clamp terminal flat Ø 6 mm
	Power circuit 44.3 lbf.in (5 N.m) screw clamp terminal flat Ø 8 mm
	Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminal pozidriv No 2
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	Mirror contact 1 NC IEC 60947-4-1
	Mechanically linked 1 NO + 1 NC IEC 60947-5-1
Terminals description ISO n°1	(21-22)NC
	(13-14)NO
	(A1-A2)CO
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contacts
	1.5 ms on energisation between NC and NO contacts
Mounting Support	Plate
	Rail

### **Environment**

Standards	CSA C22.2 No 14
	IEC 60947-5-1
	EN 60947-4-1
	UL 508
	IEC 60947-4-1
	EN 60947-5-1
Product Certifications	LROS (pending)
	UL UL
	BV
	CCC
	GL
	CSA
	RINA
	GOST
	DNV
	UKCA
IP degree of protection	IP2X IEC 60529
	IP2X VDE 0106
Climatic withstand	IACS E10 exposure to damp heat
Permissible ambient air	23.000000000140.0000000000 °F (-560 °C)
temperature around the device	-40.000000000158.0000000000 °F (-4070 °C) at Uc
	-40.0000000000136.0000000000 F (-4070 C) at 0C
Operating altitude	9842.52 ft (3000 m) without derating
Fire resistance	1562.0000000000 °F (850 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Shocks contactor opened 10 Gn for 11 ms)
	Shocks contactor closed 15 Gn for 11 ms)
	,
	Vibrations contactor opened 2 Gn, 5300 Hz)
	Vibrations contactor closed 4 Gn, 5300 Hz)
Height	5.0000000000 in (127 mm)
Width	3.0 in (75 mm)
Depth	4.7 in (119 mm)
Net Weight	3.09 lb(US) (1.4 kg)

## Ordering and shipping details

Category US10I1222357

Discount Schedule	0112
GTIN	3389110437140
Returnability	Yes
Country of origin	US

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 in (13.0 cm)
Package 1 Width	5.1 in (13.0 cm)
Package 1 Length	3.5 in (9.0 cm)
Package 1 Weight	3.09 lb(US) (1.4 kg)

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>②</b>	Reach Free Of Svhc
<b>Ø</b>	Toxic Heavy Metal Free
<b>Ø</b>	Mercury Free
<b>Ø</b>	Rohs Exemption Information Yes
<b>②</b>	Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov