Product datasheet





Contactor, TeSys Deca, 3P(3NO),AC-3/AC-3e/<=440V 65A,230V AC 50/60Hz coil, screw clamp terminals

LC1D65P7

(!) Discontinued on: 10 Dec 2021

! Discontinued

Main		
Range	TeSys	
Range of product	TeSys Deca	
Product or component type	Contactor	
Device short name	LC1D	
contactor application	Motor control Resistive load	
Utilisation category	AC-2 AC-4 AC-1 AC-3e AC-1	
poles description	3P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz	
[le] rated operational current	65 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 65 A (at <60 °C) at <= 440 V AC AC-3e for power circuit 65 A (at <60 °C) at 230 V AC AC-3 for power circuit 80 A (at <60 °C) at 230 V AC AC-1 for power circuit	
[Uc] control circuit voltage	230 V AC 50/60 Hz	

Complementary

Motor power kW	11 kW at 400 V AC 50 Hz (AC-4)
•	30 kW at 380400 V AC 50 Hz (AC-3)
	37 kW at 500 V AC 50 Hz (AC-3)
	37 kW at 660690 V AC 50 Hz (AC-3)
	18.5 kW at 220230 V AC 50 Hz (AC-3)
	30 kW at 415 V AC 50 Hz (AC-3)
	37 kW at 1000 V AC 50 Hz (AC-3)
	30 kW at 440 V AC 50 Hz (AC-3e)
	37 kW at 500 V AC 50 Hz (AC-3e)
	37 kW at 660690 V AC 50 Hz (AC-3e)
	18.5 kW at 220230 V AC 50 Hz (AC-3e)
	30 kW at 415 V AC 50 Hz (AC-3e)
	37 kW at 1000 V AC 50 Hz (AC-3e)
	37 kW at 500 V AC 50 Hz
	30 kW at 380400 V AC 50 Hz
Motor power hp	10 hp at 230/240 V AC 60 Hz for 1 phase motors
	20 hp at 200/208 V AC 60 Hz for 3 phases motors
	20 hp at 230/240 V AC 60 Hz for 3 phases motors
	40 hp at 460/480 V AC 60 Hz for 3 phases motors
	50 hp at 575/600 V AC 60 Hz for 3 phases motors
	5 hp at 115 V AC 60 Hz for 1 phase motors
Compatibility code	LC1D
Pole contact composition	3 NO

Life Is On Schneider 26 Jul 2024

Protective cover	With
[lth] conventional free air thermal current	80 A (at 60 °C) for power circuit 10 A (at 60 °C) for control circuit
Irms rated making capacity	140 A at 440 V AC for control circuit conforming to IEC 60947-5-1 140 A AC for control circuit conforming to IEC 60947-5-1 1000 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	1000 kA at 440 V for power circuit conforming to IEC 60947
[lcw] rated short-time withstand current	520 A 40 °C - 10 s for power circuit 900 A 40 °C - 1 s for power circuit
Associated fuse rating	125 A gG at <= 690 V coordination type 2 for power circuit 160 A gG at <= 690 V coordination type 1 for power circuit conforming to IEC 60947-5-1 125 A gG at <= 690 V coordination type 1 for power circuit 10 A gG for control circuit conforming to IEC 60947-5-1
Average impedance	1.5 Ohm - Ith 80 A 50 Hz for power circuit
Power dissipation per pole	6.4 W AC-1 4.2 W AC-3e 6.3 W AC-3 9.6 W AC-1
[Ui] rated insulation voltage	Control circuit: 600 V UL certified Power circuit: 600 V CSA certified Power circuit: 600 V UL certified conforming to IEC 60947-1 Control circuit: 690 V conforming to IEC 60947-1 Power circuit: 690 V CSA certified conforming to IEC 60947-1 Control circuit: 600 V CSA certified
Overvoltage category	III
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Safety reliability level	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical durability	6000000 cycles
Control circuit type	AC at 50/60 Hz
Coil technology	Without built-in
Control circuit voltage limits	0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz 11.1 Uc (6070 °C):operational AC 50/60 Hz 0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz
Inrush power in VA	160 VA cos phi 0.75 (at 20 °C) 140 VA cos phi 0.75 (at 20 °C)
Hold-in power consumption in VA	15 VA 50 Hz cos phi 0.3 (at 20 °C) 13 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	45 W at 50/60 Hz for control circuit
Operating time	1226 ms closing 419 ms opening
Maximum operating rate	3600 cyc/mn 60 °C

Connections - terminals	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: rigid without cable end
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without
	cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without
	cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with
	cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with
	cable end Power circuit: screw terminals 1 2.525 mm² - cable stiffness: rigid
	Power circuit: screw terminals 2 2.516 mm ² - cable stiffness: rigid without cable end
	Power circuit: screw terminals 1 2.525 mm² - cable stiffness: flexible without cable end
	Power circuit: screw terminals 2 2.516 mm ² - cable stiffness: flexible without cable end
	Power circuit: screw terminals 1 2.525 mm² - cable stiffness: flexible with cable end
	Power circuit: screw terminals 2 2.510 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: rigid
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: rigid
Tightening torque	Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver Philips No 2
	Power circuit: 5 N.m - on screw terminal - with screwdriver flat Ø 6 to Ø 8 mm Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver pozidriv No 2
	Control circuit: 1.7 N.m - on screw clamp terminal - with screwdriver flat Ø 6 mm
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	type mirror contact 1 NC conforming to IEC 60947-4-1 type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on energisation between NC and NO contacts 1.5 ms on de-energisation between NC and NO contacts
Mounting support	Rail
	Rail
Environment	
Standards	IEC 60947-5-1
	EN 60947-5-1
	IEC 60947-4-1 EN 60947-4-1
	CSA C22.2 No 14
Product certifications	DNV
	GL BV
	CSA
	GOST
	UL
	RINA
	CCC UKCA
	RINA
IP degree of protection	IP2X conforming to VDE 0106 IP2X conforming to IEC 60529
Protective treatment	<u> </u>
TOLOGUYO WOUNIENE	TH (pollution degree 3) conforming to IEC 60068-2-30

conforming to IACS E10 exposure to damp heat

850 °C conforming to IEC 60695-2-1

V1 conforming to UL 94

0...3000 m

Climatic withstand

Operating altitude

Fire resistance

Flame retardance

Mechanical robustness	Shocks contactor closed (15 Gn for 11 ms) Vibrations contactor opened (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor opened (10 Gn for 11 ms)	
Height	122 mm	
Width	70 mm	
Depth	118 mm	
Net weight	2.185 kg	
Quantity per set	Set of 10	

Packing Units

- - -

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
⊘	Rohs Exemption Information Yes
②	Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations