



IEC contactor, TeSys Deca, nonreversing, 80A, 60HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 24VAC 50Hz coil, open style

LC1D80B5

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 363.00 USD

Main

Range	TeSys
Range of Product	TeSys Deca
Product or Component Type	Contactor
Device short name	LC1D
contactor application	Motor control Resistive load
Utilisation category	AC-3 AC-3e AC-4 AC-1
poles description	3P
[Ue] rated operational voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[le] rated operational current	80 A (at <140 °F (60 °C)) at <= 440 V AC-3 for power circuit 125 A (at <140 °F (60 °C)) at <= 440 V AC-1 for power circuit 80 A (at <140 °F (60 °C)) at <= 440 V AC-3e for power circuit
[Uc] control circuit voltage	24 V AC 50 Hz

Complementary

Motor power kW	22 kW at 220230 V AC 50 Hz (AC-3)
	37 kW at 380400 V AC 50 Hz (AC-3)
	45 kW at 415440 V AC 50 Hz (AC-3)
	55 kW at 500 V AC 50 Hz (AC-3)
	45 kW at 660690 V AC 50 Hz (AC-3)
	15 kW at 400 V AC 50 Hz (AC-4)
	22 kW at 220230 V AC 50 Hz (AC-3e)
	37 kW at 380400 V AC 50 Hz (AC-3e)
	45 kW at 415440 V AC 50 Hz (AC-3e)
	55 kW at 500 V AC 50 Hz (AC-3e)
	45 kW at 660690 V AC 50 Hz (AC-3e)
Maximum Horse Power Rating	7.5 hp at 120 V AC 50/60 Hz for 1 phase motors
	15 hp at 230/240 V AC 50/60 Hz for 1 phase motors
	30 hp at 200/208 V AC 50/60 Hz for 3 phase motors
	30 hp at 230/240 V AC 50/60 Hz for 3 phase motors
	60 hp at 460/480 V AC 50/60 Hz for 3 phase motors
	60 hp at 575/600 V AC 50/60 Hz for 3 phase motors
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for signalling circuit 125 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1100 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[lcw] rated short-time withstand current	135 A 104 °F (40 °C) - 10 min for power circuit 320 A 104 °F (40 °C) - 1 min for power circuit 640 A 104 °F (40 °C) - 10 s for power circuit 990 A 104 °F (40 °C) - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	0.8 mOhm - Ith 125 A 50 Hz for power circuit
Power dissipation per pole	5.1 W AC-3 12.5 W AC-1 5.1 W AC-3e
[Ui] rated insulation voltage	Power circuit 1000 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	8 kV IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	10 Mcycles
Electrical durability	1.5 Mcycles 80 A AC-3 <= 440 V 0.8 Mcycles 125 A AC-1 <= 440 V 1.5 Mcycles 80 A AC-3e <= 440 V
Control circuit type	AC 50 Hz
Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 50 Hz 0.851.1 Uc -40131 °F (-4055 °C) operational AC 50 Hz 11.1 Uc 131158 °F (5570 °C) operational AC 50 Hz
Inrush power in VA	200 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	20 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	610 W at 50 Hz
Operating time	2035 ms closing 620 ms opening
Maximum operating rate	3600 cyc/h 140 °F (60 °C)
Maximum operating rate	3600 cyc/h at 60 °C

Connections - terminals	Control circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 1 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness; flexible without cable end
	Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end
	Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end
	Power circuit: connector 1 0.0060.08 in² (450 mm²) - cable stiffness: flexible without cable end
	Power circuit: connector 2 0.0060.04 in² (425 mm²) - cable stiffness: flexible without cable end
	Power circuit: connector 1 0.0060.08 in ² (450 mm ²) - cable stiffness: flexible with cable end
	Power circuit: connector 2 0.006002 in 2 $(416$ mm $^2)$ - cable stiffness: flexible with cable end
	Power circuit: connector 1 0.0060.08 in ² (450 mm ²) - cable stiffness: solid without cable end
	Power circuit: connector 2 0.0060.04 in ² (425 mm ²) - cable stiffness: solid without cable end
Tightening torque	Power circuit 106.2 lbf.in (12 N.m) connector flat Ø 6 to Ø 8 mm
	Power circuit 106.2 lbf.in (12 N.m) connector hexagonal 0.2 in (4 mm) Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm
	Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminals Philips No 2 Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminals pozidriv No 2
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling circuit frequency	25400 Hz
Minimum switching voltage	17 V for signalling circuit
Minimum switching current	5 mA for signalling circuit
Insulation resistance	> 10 MOhm for signalling circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Rail
	Plate
Environment	
Standards	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1 IEC 60947-5-1
	CSA C22.2 No 14
	UL 60947-4-1
	IEC 60335-2-40:Annex JJ
	UL 60335-2-40:Annex JJ IEC 60335-1:Clause 30.2
Product Certifications	ccc
	UL
	CB Scheme
	CSA
	CE LIKCA
	UKCA Marine
	EAC
	- -

IP20 front face IEC 60529

IACS E10 exposure to damp heat

THIEC 60068-2-30

IP degree of protection

Protective treatment

Climatic withstand

Permissible ambient air temperature around the device	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating
Operating altitude	09842.52 ft (03000 m)
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Vibrations contactor open 2 Gn, 5300 Hz) Shocks contactor open 8 Gn for 11 ms) Vibrations contactor closed 3 Gn, 5300 Hz) Shocks contactor closed 10 Gn for 11 ms)
Height	5.0000000000 in (127 mm)
Width	3.3 in (85 mm)
Depth	5.1 in (130 mm)
Net Weight	3.51 lb(US) (1.59 kg)

Ordering and shipping details

Category	US10l1222359
Discount Schedule	0112
GTIN	3389110439991
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 in (9.6 cm)
Package 1 Width	5.5 in (14.0 cm)
Package 1 Length	5.5 in (14.0 cm)
Package 1 Weight	3.44 lb(US) (1.56 kg)
Unit Type of Package 2	S02
Number of Units in Package 2	6
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	21.477 lb(US) (9.742 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Sustainable Packaging Transparency RoHS/REACh

Resource performance



Sustainable Packaging

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Pvc Free

Certifications & Standards

Reach Regulation

Eu Rohs Directive

Compliant
EU RoHS Declaration

China Rohs Regulation

China Rohs declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

Product Environmental Profile

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile

No need of specific recycling operations

California Proposition 65 WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Pvc Free Yes

Offer Marketing Illustration

Product benefits / Features



LC1D80B5

Offer Marketing Illustration

Product benefits / Features

