# **Product datasheet**





Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 80A, 24V DC wide voltage range coil, screw clamp terminals

LC1D80BW

### Main

Range	TeSys	
Range Of Product	TeSys Deca	
Product Or Component Type	Contactor	
Device Short Name	LC1D	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-3 AC-3e AC-4 AC-1	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit: <= 300 V DC 25400 Hz Power circuit: <= 690 V AC	
[le] Rated Operational Current	125 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
[Uc] Control Circuit Voltage	24 V DC	

### Complementary

Motor Power Kw	22 kW at 220230 V AC 50/60 Hz (AC-3)	
	37 kW at 380400 V AC 50/60 Hz (AC-3)	
	45 kW at 415440 V AC 50/60 Hz (AC-3)	
	55 kW at 500 V AC 50/60 Hz (AC-3)	
	45 kW at 660690 V AC 50/60 Hz (AC-3)	
	15 kW at 400 V AC 50/60 Hz (AC-4)	
	22 kW at 220230 V AC 50/60 Hz (AC-3e)	
	37 kW at 380400 V AC 50/60 Hz (AC-3e)	
	45 kW at 415440 V AC 50/60 Hz (AC-3e)	
	55 kW at 500 V AC 50/60 Hz (AC-3e)	
	45 kW at 660690 V AC 50/60 Hz (AC-3e)	
Motor Power Hp	7.5 hp at 120 V AC 50/60 Hz for 1 phase motors	
	15 hp at 230/240 V AC 50/60 Hz for 1 phase motors	
	30 hp at 200/208 V AC 50/60 Hz for 3 phases motors	
	30 hp at 230/240 V AC 50/60 Hz for 3 phases motors	
	60 hp at 460/480 V AC 50/60 Hz for 3 phases motors	
	60 hp at 575/600 V AC 50/60 Hz for 3 phases motors	
Compatibility Code	LC1D	
Pole Contact Composition	3 NO	
Protective Cover	With	
[Ith] Conventional Free Air	10 A (at 60 °C) for signalling circuit	
Thermal Current	125 A (at 60 °C) for power circuit	
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	
	1100 A at 440 V for power circuit conforming to IEC 60947	

Life Is On Schneider 26 Jun 2024



Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand	640 A 40 °C - 10 s for power circuit
Current	990 A 40 °C - 1 s for power circuit
	135 A 40 °C - 10 min for power circuit
	320 A 40 °C - 1 min for power circuit
	100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	200 A gG at <= 690 V coordination type 1 for power circuit
	160 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.8 mOhm - Ith 125 A 50 Hz for power circuit
Power Dissipation Per Pole	5.1 W AC-3 12.5 W AC-1
	5.1 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified
. ,	Power circuit: 600 V UL certified
	Power circuit: 1000 V conforming to IEC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-1
	Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand	8 kV conforming to IEC 60947
Voltage	o kt comoning to 120 coch
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	10 Mcycles
Electrical Durability	0.8 Mcycles 125 A AC-1 at Ue <= 440 V
	1.5 Mcycles 80 A AC-3 at Ue <= 440 V
	1.5 Mcycles 80 A AC-3e at Ue <= 440 V
Control Circuit Type	DC wide range
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.751.2 Uc (-4055 °C):operational DC
	0.10.3 Uc (-4070 °C):drop-out DC
	11.2 Uc (5570 °C):operational DC
Inrush Power In W	22 W (at 20 °C)
Hold-In Power Consumption In W	22 W at 20 °C
Operating Time	95130 ms closing
	2035 ms opening
Time Constant	75 ms
Maximum Operating Rate	3600 cyc/h 60 °C
Connections - Terminals	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with
	cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with
	cable end
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without
	cable end
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without
	cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without
	cable end
	cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end
	cable end  Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end  Power circuit: connector 2 425 mm² - cable stiffness: flexible without cable end
	cable end  Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end  Power circuit: connector 2 425 mm² - cable stiffness: flexible without cable end  Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end
	cable end  Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end  Power circuit: connector 2 425 mm² - cable stiffness: flexible without cable end

Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
nsulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact     1.5 ms on energisation between NC and NO contact
Mounting Support	Rail Plate
Environment	
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product Certifications	LROS (Lloyds register of shipping) CSA RINA CCC GL GOST BV UL DNV
p Degree Of Protection	IP20 front face conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068-2-30
Climatic Withstand	conforming to IACS E10 exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating
Operating Altitude	03000 m
Fire Resistance	850 °C conforming to IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Shocks contactor open (8 Gn for 11 ms) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor closed (10 Gn for 11 ms)
Height	127 mm
Width	85 mm
Depth	186 mm
Net Weight	2.59 kg
Packing Units	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	

Number Of Units In Package 1 1

Package 1 Height	11.2 cm
Package 1 Width	16.0 cm
Package 1 Length	22.6 cm
Package 1 Weight	2.659 kg
Unit Type Of Package 2	S02
Number Of Units In Package 2	2
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.62 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Reach Free Of Svhc
	Toxic Heavy Metal Free
<b>Ø</b>	Mercury Free
<b>Ø</b>	Rohs Exemption Information Yes
<b>⊘</b>	Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations