

Product data sheet

Specifications



TeSys F contactor - 3P (3 NO) - AC-3 - <= 440 V 250 A - coil 110 V AC

LC1F150F6

Discontinued

Discontinued on: Jul 12, 2021

End-of-service on: Aug 2, 2021

Main

Range	TeSys
Range of product	TeSys F
Product or component type	Contactor
Device short name	LC1F
contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-3
poles description	3P
[Ue] rated operational voltage	<= 690 V AC 50/60 Hz <= 460 V DC
[Uc] control circuit voltage	110 V AC 60 Hz
[Ie] rated operational current	250 A (at <104.0000000000 °F (40 °C)) at <= 440 V AC-1 150 A (at <131.0000000000 °F (55 °C)) at <= 440 V AC-3

Complementary

[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	250 A (at 104.0000000000 °F (40 °C))
Rated breaking capacity	1200 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	1200 A 104.0000000000 °F (40 °C) - 10 s 700 A 104.0000000000 °F (40 °C) - 30 s 600 A 104.0000000000 °F (40 °C) - 1 min 450 A 104.0000000000 °F (40 °C) - 3 min 350 A 104.0000000000 °F (40 °C) - 10 min
Associated fuse rating	160 A aM at <= 440 V 250 A gG at <= 440 V
Average impedance	0.35 mOhm - Ith 250 A 50 Hz
[Ui] rated insulation voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power dissipation per pole	22 W AC-1 8 W AC-3
Overvoltage category	III
power pole contact composition	3 NO

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Motor power kW	75 kW at 380...400 V AC 50/60 Hz (AC-3) 80 kW at 415 V AC 50/60 Hz (AC-3) 80 kW at 440 V AC 50/60 Hz (AC-3) 90 kW at 500 V AC 50/60 Hz (AC-3) 100 kW at 660...690 V AC 50/60 Hz (AC-3) 40 kW at 220...230 V AC 50/60 Hz (AC-3) 22 kW at 400 V AC 50/60 Hz (AC-4)
Control circuit voltage limits	Operational 0.85...1.1 Uc 50/60 Hz 131.0000000000 °F (55 °C)) Drop-out 0.35...0.55 Uc 50/60 Hz 131.0000000000 °F (55 °C))
Mechanical durability	10 Mcycles
Inrush power in VA	660 VA, 60 Hz 0.3 68.0000000000 °F (20 °C))
Hold-in power consumption in VA	55 VA, 60 Hz 0.3 68.0000000000 °F (20 °C))
Maximum operating rate	2400 cyc/h 131.0000000000 °F (55 °C)
Operating time	23...35 ms closing 5...15 ms opening
Connections - terminals	Control circuit screw clamp terminals 1 0.002...0.006 in ² (1...4 mm ²)flexible without cable end Control circuit screw clamp terminals 2 0.002...0.006 in ² (1...4 mm ²)flexible without cable end Control circuit screw clamp terminals 1 0.002...0.006 in ² (1...4 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²)flexible with cable end Control circuit screw clamp terminals 1 0.002...0.006 in ² (1...4 mm ²)solid without cable end Control circuit screw clamp terminals 2 0.002...0.006 in ² (1...4 mm ²)solid without cable end Power circuit bar 2 25 x 3 mm Power circuit lugs-ring terminals 1 0.2 in ² (120 mm ²) Power circuit connector 1 0.2 in ² (120 mm ²)
Tightening torque	Control circuit 10.6 lbf.in (1.2 N.m) Power circuit 159.3 lbf.in (18 N.m)
Mounting support	Plate
Heat dissipation	12...16 W
Standards	JIS C8201-4-1 IEC 60947-4-1 EN 60947-1 IEC 60947-1 EN 60947-4-1
Product certifications	CB ABS LROS (Lloyds register of shipping) BV CCC DNV UL RINA RMRoS
Compatibility code	LC1F
Control circuit type	AC 60 Hz

Environment

IP degree of protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-40.0000000000...140.0000000000 °F (-40...60 °C)
Ambient air temperature for storage	-76.0000000000...176.0000000000 °F (-60...80 °C)
Permissible ambient air temperature around the device	140.0000000000...158.0000000000 °F (60...70 °C) at Uc

Height	6.7 in (170 mm)
Width	6.4 in (163.5 mm)
Depth	6.7 in (171 mm)
Operating altitude	3000 m without derating
Net weight	7.56 lb(US) (3.43 kg)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.3 in (21 cm)
Package 1 Width	7.9 in (20 cm)
Package 1 Length	9.4 in (24 cm)
Package 1 Weight	9.24 lb(US) (4.19 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information