# Product data sheet

Specifications





() Discontinued

# TeSys F contactor - 3P (3 NO) -AC-3 - <= 440 V 250 A - coil 240 V AC

LC1F150U6

Discontinued on: Nov 1, 2020

Main

mann		
Range	TeSys	
Range Of Product	TeSys F	
Product Or Component Type	Contactor	
Device Short Name	LC1F	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-1 AC-4 AC-3	
Poles Description	3P	
[Ue] Rated Operational Voltage	<= 690 V AC 50/60 Hz <= 460 V DC	
[Uc] Control Circuit Voltage	240 V AC 60 Hz	
[le] Rated Operational Current	250 A (at <40 °C) at <= 440 V AC-1 150 A (at <55 °C) at <= 440 V AC-3	

#### Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	250 A (at 40 °C)
Rated Breaking Capacity	1200 A conforming to IEC 60947-4-1
[Icw] Rated Short-Time Withstand Current	1200 A 40 °C - 10 s 700 A 40 °C - 30 s 600 A 40 °C - 1 min 450 A 40 °C - 3 min 350 A 40 °C - 10 min
Associated Fuse Rating	160 A aM at <= 440 V 250 A gG at <= 440 V
Average Impedance	0.35 mOhm - Ith 250 A 50 Hz
[Ui] Rated Insulation Voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power Dissipation Per Pole	22 W AC-1 8 W AC-3
Overvoltage Category	III
Power Pole Contact Composition	3 NO

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Life Is On Schneider

Motor Power Kw	75 kW at 380400 V AC 50/60 Hz (AC-3) 80 kW at 415 V AC 50/60 Hz (AC-3)
	80 kW at 440 V AC 50/60 Hz (AC-3)
	90 kW at 500 V AC 50/60 Hz (AC-3) 100 kW at 660690 V AC 50/60 Hz (AC-3)
	40 kW at 220230 V AC 50/60 Hz (AC-3)
	22 kW at 400 V AC 50/60 Hz (AC-4)
Control Circuit Voltage Limits	Operational: 0.851.1 Uc 50/60 Hz (at 55 °C) Drop-out: 0.350.55 Uc 50/60 Hz (at 55 °C)
Mechanical Durability	10 Mcycles
Inrush Power In Va	660 VA, 60 Hz cos phi 0.3 (at 20 °C)
Hold-In Power Consumption In Va	
	55 VA, 60 Hz cos phi 0.3 (at 20 °C)
Maximum Operating Rate	2400 cyc/h 55 °C
Operating Time	2335 ms closing 515 ms opening
Connections - Terminals	Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm <sup>2</sup> solid without cable end Power circuit: bar 2 cable(s) - busbar cross section: 25 x 3 mm Power circuit: lugs-ring terminals 1 cable(s) 120 mm <sup>2</sup> Power circuit: connector 1 cable(s) 120 mm <sup>2</sup> Power circuit: bolted connection
Tightening Torque	Control circuit: 1.2 N.m
	Power circuit: 18 N.m
Mounting Support	Plate
Heat Dissipation	1216 W
Standards	IEC 60947-1
	IEC 60947-4-1 EN 60947-1
	JIS C8201-4-1
	EN 60947-4-1
Product Certifications	ABS
	BV RINA
	LROS (Lloyds register of shipping)
	DNV
	ccc
	UL CB
	RMRoS
Compatibility Code	LC1F
Control Circuit Type	AC at 60 Hz
Environment	
Ip Degree Of Protection	IP2X front face with shrouds conforming to IEC 60529
	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Protective Treatment	тн
Ambient Air Temperature For Operation	-4060 °C
Ambient Air Temperature For Storage	-6080 °C
Permissible Ambient Air Temperature Around The Device	6070 °C at Uc
Height	170 mm

Width

Depth

163.5 mm

171 mm

Operating Altitude	3000 m without derating	
Net Weight	3.43 kg	
Packing Units		
Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Contractual warranty		
Warranty	18 months	

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance



Rohs Exemption Information

### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information