# **Product datasheet**





(!) Discontinued

## Contactor body, TeSys F, 4P(4NO), AC-1, <=440V 400A without coil

LC1F3304

! Discontinued on: 28 Jan 2023

! End-of-service on: 31 Dec 2023

### Main

Range	TeSys
Product name	TeSys F
Product or component type	Contactor
Device short name	LC1F
contactor application	Resistive load
Utilisation category	AC-1
poles description	4P
power pole contact composition	4 NO
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[le] rated operational current	400 A (at <40 °C) at <= 440 V AC AC-1

### Complementary

[Uc] control circuit voltage	241000 V AC 40400 Hz with LX1/LX9 coil
	24460 V DC with LX4 coil
	100250 V AC 50/60 Hz with LXE coil
	100380 V DC with LXE coil
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	400 A (at 40 °C)
Irms rated making capacity	3300 A AC conforming to IEC 60947-4-1
Rated breaking capacity	2640 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand	2650 A 40 °C - 10 s
current	1800 A 40 °C - 30 s
	1300 A 40 °C - 1 min
	900 A 40 °C - 3 min
	750 A 40 °C - 10 min
Associated fuse rating	400 A aM at <= 440 V
	500 A gG at <= 440 V
Average impedance	0.28 mOhm - Ith 400 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1
	1500 V conforming to VDE 0110 group C
Power dissipation per pole	44 W AC-1

Life Is On Schneider 29 Jul 2024

Control circuit voltage limits	Operational: 0.851.1 Uc AC 40400 Hz with LX1/LX9 coil Drop-out: 0.350.55 Uc AC 40400 Hz with LX1/LX9 coil Operational: 0.851.1 Uc DC with LX4 coil Drop-out: 0.150.2 Uc DC with LX4 coil Operational: 85275 V AC 50/60 Hz with LXE coil Drop-out: 060 V AC 50/60 Hz with LXE coil Operational: 85418 V DC with LXE coil Drop-out: 045 V DC with LXE coil
Heat dissipation	8 W 2.25.5 W
Operating time	4065 ms closing for with LX1/LX9 coil 100170 ms opening for with LX1/LX9 coil 4050 ms closing for with LX4 coil 4065 ms opening for with LX4 coil 4080 ms closing for with LXE coil 654 ms opening for with LXE coil
Mounting support	Plate
Standards	IEC 60947-4-1 JIS C8201-4-1 EN 60947-1 IEC 60947-1 EN 60947-4-1
Product certifications	ABS CSA UL RMRoS DNV CB BV LROS (Lloyds register of shipping) RINA UKCA
Connections - terminals	Power circuit: lugs-ring terminals 1 cable(s) 240 mm² Power circuit: bar 2 cable(s) - busbar cross section: 30 x 5 mm Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 12.5 mm²solid without cable end Control circuit: screw clamp terminals 1 cable(s) 14 mm² Control circuit: screw clamp terminals 2 cable(s) 14 mm² Control circuit: screw clamp terminals 1.0 cable(s) 0.22.5 mm²flexible without cable end Control circuit: screw clamp terminals 1.0 cable(s) 0.22.5 mm²flexible with cable end Control circuit: screw clamp terminals 1.0 cable(s) 0.252.5 mm²flexible with cable end Control circuit: screw clamp terminals 1.0 cable(s) 0.22.5 mm²solid without cable end
Tightening torque	Power circuit: 35 N.m Control circuit: 1.2 N.m Control circuit: 0.6 N.m
Mechanical durability	10 Mcycles
Inrush power in VA	600700 VA, 40400 Hz cos phi 0.9 (at 20 °C)with LX1/LX9 coil 655803 VA (at 20 °C)with LX4 coil 300350 VA, 50/60 Hz cos phi 0.5 (at 20 °C)with LXE coil 300310 VA (at 20 °C)with LXE coil
Hold-in power consumption in VA	810 VA, 40400 Hz cos phi 0.9 (at 20 °C)with LX1/LX9 coil 3.684.53 VA (at 20 °C)with LX4 coil 4.57.0 VA, 50/60 Hz cos phi 0.5 (at 20 °C)with LXE coil 2.54.0 VA (at 20 °C)with LXE coil
Maximum operating rate	2400 cyc/h 55 °C
Compatibility code	LC1F
Environment	

IP degree of protection

IP20 front face with shrouds conforming to IEC 60529

IP20 front face with shrouds conforming to VDE 0106

Protective treatment	тн
Ambient air temperature for operation	-555 °C
Ambient air temperature for storage	-6080 °C
Permissible ambient air temperature around the device	-4070 °C
Operating altitude	3000 m without derating
Mechanical robustness	Vibrations contactor open: 2 Gn, 5300 Hz Vibrations contactor closed: 5 Gn, 5300 Hz Shocks contactor open: 6 Gn for 1/2 sine wave (11 ms) Shocks contactor closed: 15 Gn for 1/2 sine wave (11 ms)
Height	206 mm
Width	261 mm
Depth	219 mm
Net weight	9.5 kg

# **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.000 cm
Package 1 Width	24.000 cm
Package 1 Length	31.500 cm
Package 1 Weight	10.059 kg
Unit Type of Package 2	P06
Number of Units in Package 2	10
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	110.000 kg

# **Contractual warranty**

Warranty 18 months

### Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information