



TeSys F contactor - 3P (3 NO) - AC-3 - <= 440 V 400 A - coil 48 V AC

LC1F400E7

- ! To be discontinued on: Dec 31, 2025
- ! To be end-of-service on: Jan 30, 2026

① To be discontinued

Main

Range	TeSys
Range of product	TeSys F
product or component type	Contactor
Device short name	LC1F
contactor application	Resistive load Motor control
Utilisation category	AC-4 AC-3 AC-1
poles description	3P
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Uc] control circuit voltage	48 V AC 40400 Hz
[le] rated operational current	500 A (at <104 °F (40 °C)) at <= 440 V AC AC-1 400 A (at <131 °F (55 °C)) at <= 440 V AC AC-3

Complementary

[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	500 A (at 104 °F (40 °C))
Rated breaking capacity	3200 A conforming to IEC 60947-4-1
[lcw] rated short-time withstand current	3600 A 104 °F (40 °C) - 10 s 2400 A 104 °F (40 °C) - 30 s 1700 A 104 °F (40 °C) - 1 min 1200 A 104 °F (40 °C) - 3 min 1000 A 104 °F (40 °C) - 10 min
Associated fuse rating	400 A aM at <= 440 V 500 A gG at <= 440 V
Average impedance	0.26 mOhm - Ith 500 A 50 Hz
[Ui] rated insulation voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power dissipation per pole	65 W AC-1 42 W AC-3
Overvoltage category	III
power pole contact composition	3 NO

Motor power kW	75 kW at 400 V AC 50/60 Hz (AC-4)
	200 kW at 380400 V AC 50/60 Hz (AC-3)
	220 kW at 415 V AC 50/60 Hz (AC-3)
	250 kW at 440 V AC 50/60 Hz (AC-3)
	257 kW at 500 V AC 50/60 Hz (AC-3)
	280 kW at 660690 V AC 50/60 Hz (AC-3)
	185 kW at 1000 V AC 50/60 Hz (AC-3)
	110 kW at 220230 V AC 50/60 Hz (AC-3)
Control circuit voltage limits	Operational 0.851.1 Uc 40400 Hz 131 °F (55 °C)) Drop-out 0.30.5 Uc 40400 Hz 131 °F (55 °C))
Mechanical durability	10 Mcycles
Inrush power in VA	1075 VA, 40400 Hz 0.9 68 °F (20 °C))
Hold-in power consumption in VA	15 VA, 40400 Hz 0.9 68 °F (20 °C))
Maximum operating rate	2400 cyc/h 131 °F (55 °C)
Operating time	4065 ms closing
	100170 ms opening
Connections - terminals	Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 2 0.0020.006 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)flexible with cable end
	Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²)flexible with cable end
	Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)solid without cable end
	Control circuit screw clamp terminals 2 0.0020.006 in² (14 mm²)solid without cable end
	Power circuit bar 2 30 x 5 mm
	Power circuit lugs-ring terminals 2 0.2 in ² (150 mm ²)
	Power circuit bolted connection
Tightening torque	Control circuit 10.6 lbf.in (1.2 N.m) Power circuit 309.8 lbf.in (35 N.m)
mounting support	Plate
Heat dissipation	14 W
motor power range	110220 kW 480500 V 3 phases
	110220 kW 380440 V 3 phases
	110220 kW 200240 V 3 phases
	250500 kW 480500 V 3 phases
Motor starter type	Direct on-line contactor
Contactor coil voltage	48 V AC standard
Standards	IEC 60947-1
	IEC 60947-4-1
	EN 60947-4-1
	EN 60947-1
	JIS C8201-4-1
Product certifications	RINA
	BV
	RMRoS
	LROS (Lloyds register of shipping)
	UL
	ABS
	CSA
	CB
	DNV
	UKCA
Compatibility code	LC1F
Control circuit type	AC 40400 Hz

Environment

IP degree of protection	IP20 front face with shrouds IEC 60529 IP20 front face with shrouds VDE 0106			
Protective treatment	тн			
Ambient air temperature for operation	23131 °F (-555 °C)			
ambient air temperature for storage	-76176 °F (-6080 °C)			
Permissible ambient air temperature around the device	-40158 °F (-4070 °C)			
Height	8.1 in (206 mm)			
Width	8.4 in (213 mm)			
Depth	8.6 in (219 mm)			
Operating altitude	3000 m without derating			
net weight	20.06 lb(US) (9.1 kg)			

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.8 in (25.0 cm)
Package 1 Width	9.4 in (24.0 cm)
Package 1 Length	12.2 in (31.0 cm)
Package 1 Weight	20.5 lb(US) (9.3 kg)

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Dimensions Drawings

Dimensions and Drawings

LC1 F400 and F500



(1) Power terminal protection shroud

NOTE: X1 (mm) = Minimum electrical clearance according to operating voltage and breaking capacity.

LC1	200500 V	6001000 V
F400	15	20
F500	15	20


LC1		а	b	b2	С	f	G supplied	G min.	G max.	G1 supplied	G1 min.	G1 max.	J	L	М	Р	Q	Q1
	2P	213	206	375	219	146	80	66	102	170	156	192	19.5	145	181	48	69	96
F400	3P	213	206	375	219	146	80	66	102	170	156	192	19.5	145	181	48	43	74
	4P	261	206	375	219	146	80	66	150	170	156	240	67.5	145	181	48	43	74
	2P	233	238	400	232	150	80	66	120	170	156	210	39.5	146	208	55	76	102
F500	3P	233	238	400	232	150	80	66	120	170	156	210	39.5	146	208	55	46	77
	4P	288	238	400	232	150	140	66	175	230	156	265	34.5	146	208	55	46	77

TeSys F reversing contactors and changeover contactor pairs Vertically mounted

NOTE: For customer assembly, with mechanical interlock (MI) LA9 F, fixing recommended on AM1 EC uprights (please consult your Regional Sales Office). 2 x LC1 identical or different ratings (LC1 F115 to F630 and F800).

Assembly A

LC1F400E7




- (1) Mechanical interlock shaft.
- (2) For assembly of contactors of different ratings only.
- (3) 4 x Ø6.5 for LC1 F115 to F225.

Assembly A⁽⁷⁾ - Mechanical interlock reference

/ Godinbiy / t	IVICOITA	mour mic	TIOOK TOIC	101100				
	G3 3P	G3 4P	H min.	H max.	H1 min.	H1 max.	J1 3P	J1 4P
LA9 FF4F	0	0	200	310	80	190	137	155.5
LA9 FG4F	3	4	210	300	90	180	139.5	159.5
LA9 FG4G	0	0	220	310	100	190	139.5	159.5

	J2 3P	J2 4P	J3 3P	J3 4P	J4 3P	J4 4P
LA9 FF4F	137	155.5	48.5	67	48.5	67
LA9 FG4F	137	155.5	53	73	54	69
LA9 FG4G	139.5	159.5	53	73	53	73

Assembly B



- (4) 4 x Ø6.5 for LC1 F265.
- (5) Mechanical interlock guide bracket.

Assembly B⁽⁷⁾ - Mechanical interlock reference

Assembly By 7 - Mechanical Interlock reference										
	G1 3P	G1 4P	G3 3P	G3 4P	G5 3P	G5 4P	H min.	H max.		
LA9 FH4F	96	96	21	27	60	83	240	380		
LA9 FJ4F	80	80	45	26	83	83	250	380		
LA9 FK4F	80	140	45	26	83	83	270	380		
LA9 FL4F	180	240	35	17	74	74	310	380		
LA9 FH4G	96	96	19	23	60	83	250	380		
LA9 FJ4G	80	80	42	22	83	83	250	380		
LA9 FK4G	80	140	42	22	83	83	270	380		
LA9 FL4G	180	240	33	13	74	74	310	380		


	H1 min.	H1 max.	J1 3P	J1 4P	J2 3P	J2 4P	J4 3P	J4 4P
LA9 FH4F	110	250	157.5	181.5	137	155.5	48.5	67
LA9 FJ4F	80	210	144.5	192.5	137	155.5	48.5	67
LA9 FK4F	100	210	164.5	219.5	137	155.5	48.5	67
LA9 FL4F	140	210	248.5	328.5	137	155.5	48.5	67
LA9 FH4G	120	250	157.5	181.5	139.5	159.5	53	73
LA9 FJ4G	90	220	144.5	192.5	139.5	159.5	53	73
LA9 FK4G	110	220	164.5	219.5	139.5	159.5	53	73

Product data sheet


LC1F400E7

	H1 min.	H1 max.	J1 3P	J1 4P	J2 3P	J2 4P	J4 3P	J4 4P
LA9 FL4G	150	220	248.5	328.5	139.5	159.5	53	73

Assembly C



(6) 4 x Ø8.5 for LC1 F400, F500 or 4 x Ø10.5 for LC1 F630 and F800.



- (7) Only 3P for F800.
- (8) In this case, G4 is greater than G5.

Assembly C⁽⁷⁾

Assembly C										
	G1 3P	G1 4P	G2 3P	G2 4P	G3 3P	G3 4P	G4 3P	G4 4P	G5 3P	G5 4P
LA9 FH4H	96	96	96	96	0	0	60	83	60	83
LA9 FJ4H	80	80	96	96	23	0	60	83	83	83
LA9 FK4H	80	140	96	96	23	0	60	83	83	83

Product data sheet

LC1F400E7

	G1 3P	G1 4P	G2 3P	G2 4P	G3 3P	G3 4P	G4 3P	G4 4P	G5 3P	G5 4P
LA9 FL4H	180	240	96	96	14	9 ⁽⁸⁾	60	83	74	74
LA9 FJ4J	80	80	80	80	0	0	83	83	83	83
LA9 FK4J	80	140	80	80	0	0	83	83	83	83
LA9 FL4J	180	240	80	80	9 ⁽⁸⁾	9 ⁽⁸⁾	83	83	74	74
LA9 FK4K	80	140	80	140	0	0	83	83	83	83
LA9 FL4K	180	240	80	140	9 ⁽⁸⁾	9 ⁽⁸⁾	83	83	74	74
LA9 FL4L	180	240	180	240	0	0	74	74	74	74


	H min.	H max.	H1 min.	H1 max.	J1 3P	J1 4P	J2 3P	J2 4P
LA9 FH4H	250	380	130	260	157.5	181.5	157.5	181.5
LA9 FJ4H	260	380	110	230	144.5	192.5	157.5	181.5
LA9 FK4H	280	380	130	230	164.5	219.5	157.5	181.5
LA9 FL4H	330	380	170	220	248.5	328.5	157.5	181.5
LA9 FJ4J	260	380	60	200	144.5	192.5	144.5	192.5
LA9 FK4J	280	380	100	200	164.5	219.5	144.5	192.5
LA9 FL4J	325	380	140	195	248.5	329.5	144.5	192.5
LA9 FK4K	300	380	120	200	164.5	329.5	164.5	219.5
LA9 FL4K	345	380	160	195	248.5	328.5	164.5	219.5
LA9 FL4L	380	380	200	200	248.5	328.5	248.5	328.5

LC1F400E7

Connections and Schema

Connections and Schema

2, 3, and 4-pole Contactors



LC1 F115 to F630, F1250(coil LX1 F **)



LC1 F115 to F630 , F1250 (coil LX4 F ==)
LC1 F115 to F265 (coil LX9 F =>)
LC1 F800 (coil LX8 F => / ==)

Product data sheet

LC1F400E7

Motor Starter BOM Motor Starter BOM