Product data sheet

Specification





TeSys Deca reversing contactor - 3P - <= 440 V - 9 A AC-3 - 24...60 V AC/DC coil

LC2D09BNE

Product availability: Stock - Normally stocked in distribution facility

Price*: 127.00 USD

Main

Range	TeSys TeSys Deca
Product Name	Tesys Deca green TeSys Deca
Product Or Component Type	Reversing contactor
Device Short Name	LC2D
Contactor Application	Motor control Resistive load
Utilisation Category	AC-3 AC-1 AC-3e
Device Presentation	Preassembled with reversing power busbar
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage Power circuit <= 690 V AC 25400 Hz	
[le] Rated Operational Current	9 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 25 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 9 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit
Motor Power Kw	2.2 kW at 220230 V AC 50 Hz 4 kW at 380400 V AC 50 Hz 4 kW at 415 V AC 50 Hz 4 kW at 440 V AC 50 Hz 5.5 kW at 500 V AC 50 Hz 5.5 kW at 660690 V AC 50 Hz
Motor Power Hp (UI / Csa)	0.33 hp at 115 V AC 60 Hz for 1 phase motors 1 hp at 230/240 V AC 60 Hz for 1 phase motors 2 hp at 200/208 V AC 60 Hz for 3 phase motors 2 hp at 230/240 V AC 60 Hz for 3 phase motors 5 hp at 460/480 V AC 60 Hz for 3 phase motors 7.5 hp at 575/600 V AC 60 Hz for 3 phase motors
Control Circuit Type	AC 50/60 Hz AC/DC electronic DC AC/DC electronic
[Uc] Control Circuit Voltage	2460 V AC 50/60 Hz 2460 V DC
Auxiliary Contact Composition	1 NO + 1 NC
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C)) for signalling circuit 25 A (at 140 °F (60 °C)) for power circuit

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Irms Rated Making Capacity	250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	250 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	105 A 104 °F (40 °C) - 10 s for power circuit
Current	210 A 104 °F (40 °C) - 1 s for power circuit 30 A 104 °F (40 °C) - 10 min for power circuit
	61 A 104 °F (40 °C) - 1 min for power circuit
	100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	25 A gG at <= 690 V coordination type 1 for power circuit 20 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1
Electrical Durability	2.4 Mcycles 8 A AC-3 <= 440 V
	0.6 Mcycles 25 A AC-1 <= 440 V 2.4 Mcycles 8 A AC-3e <= 440 V
	2.4 INCYCLES 6 A AC-3E \= 440 V
Power Dissipation Per Pole	1.56 W AC-1
	0.2 W AC-3 0.2 W AC-3e
Front Cover	With
Interlocking Type	Mechanical
Mounting Support	Rail Plate
Standards	EN/IEC 60947-4-1
	EN/IEC 60947-5-1
	UL 60947-4-1 CSA C22.2 No 60947-4-1
	IEC 60335-1
Product Certifications	ccc
	CSA EAC
	UL
	KC
	DNV-GL LROS (Lloyds register of shipping)
	UKCA
Connections - Terminals	Power circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without
	cable end Power circuit screw clamp terminals 2 0.000.01 in² (14 mm²)flexible without
	cable end
	Power circuit screw clamp terminals 1 0.000.01 in ² (14 mm ²)flexible with cable end
	Power circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end
	Power circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid
	Power circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible without cable end
	Control circuit screw clamp terminals 2 0.000.01 in ² (14 mm ²)flexible without cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)flexible with cable end
	Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²)flexible with cable end
	Control circuit screw clamp terminals 1 0.000.01 in² (14 mm²)solid Control circuit screw clamp terminals 2 0.000.01 in² (14 mm²)solid
Tightening Torque	Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm
	Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2
	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2
	Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2
	, , , , , , , , , , , , , , , , , , , ,

Operating Time	4555 ms closing 2090 ms opening
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	15 Mcycles
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

Complementary

Coil Technology	Built-in bidirectional peak limiting	
Control Circuit Voltage Limits	<= 0.1 Uc -40158 °F (-4070 °C) drop-out AC/DC 0.851.1 Uc -40140 °F (-4060 °C) operational AC 0.81.1 Uc -40140 °F (-4060 °C) operational DC 11.1 Uc 140158 °F (6070 °C) operational AC/DC	
Inrush Power In Va	15 VA 50/60 Hz 68 °F (20 °C))	
Inrush Power In W	14 W 68 °F (20 °C)	
Hold-In Power Consumption In Va 0.9 VA 68 °F (20 °C)) 50/60 Hz		
Hold-In Power Consumption In W	0.6 W 68 °F (20 °C)	
Heat Dissipation	0.6 W 50/60 Hz	
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1	
Signalling Circuit Frequency	25400 Hz	
Minimum Switching Current	5 mA for signalling circuit	
Minimum Switching Voltage	17 V for signalling circuit	
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Insulation Resistance	> 10 MOhm for signalling circuit	

Environment

Liviloillient		
Ip Degree Of Protection	IP20 front face IEC 60529	
Climatic Withstand	IACS E10 IEC 60947-1 Annex Q category D	
Protective Treatment	TH IEC 60068-2-30	
Pollution Degree	3	
Ambient Air Temperature For Operation	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating	
Ambient Air Temperature For Storage	-76176 °F (-6080 °C)	
Operating Altitude	09842.52 ft (03000 m)	
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor open10 Gn for 11 ms Shocks contactor closed15 Gn for 11 ms	
Height	3.03 in (77 mm)	
Width	3.54 in (90 mm)	
Depth	3.39 in (86 mm)	
Net Weight	1.73 lb(US) (0.783 kg)	

Color Gray SE GREY 6)
Green SE GREEN 2)

Ordering and shipping details

Category	US10I1222356	
Discount Schedule	0112	
Gtin	3606480987847	
Returnability	No	
Country Of Origin	FR	

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.74 in (9.500 cm)
Package 1 Width	4.53 in (11.500 cm)
Package 1 Length	5.51 in (14.000 cm)
Package 1 Weight	30.86 oz (875.000 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	6
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	12.34 lb(US) (5.597 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes
	Halogen Free Plastic Parts & Cables Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information