# Product data sheet

Specification





TeSys Deca reversing contactor - 3P - <= 440 V - 32 A AC-3 - 100...250 V AC/DC coil

LC2D32KUE

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 191.00 USD

#### Main

Range	TeSys TeSys Deca
Product name	Tesys Deca green TeSys Deca
Product or Component Type	Reversing contactor
Device short name	LC2D
contactor application	Resistive load Motor control
Utilisation category	AC-1 AC-3
device presentation	Preassembled with reversing power busbar
poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit <= 690 V AC 25400 Hz
[le] rated operational current	32 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 50 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 32 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit
Motor power kW	7.5 kW at 220230 V AC 50 Hz 15 kW at 380400 V AC 50 Hz 15 kW at 415 V AC 50 Hz 15 kW at 440 V AC 50 Hz 18.5 kW at 500 V AC 50 Hz 18.5 kW at 660690 V AC 50 Hz
motor power HP (UL / CSA)	2 hp at 115 V AC 60 Hz for 1 phase motors 5 hp at 230/240 V AC 60 Hz for 1 phase motors 10 hp at 200/208 V AC 60 Hz for 3 phase motors 10 hp at 230/240 V AC 60 Hz for 3 phase motors 20 hp at 460/480 V AC 60 Hz for 3 phase motors 25 hp at 575/600 V AC 60 Hz for 3 phase motors
Control circuit type	AC 50/60 Hz AC/DC electronic DC AC/DC electronic
[Uc] control circuit voltage	100250 V AC 50/60 Hz 100250 V DC
Auxiliary contact composition	1 NO + 1 NC
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Overvoltage category	III
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for signalling circuit 50 A (at 140 °F (60 °C)) for power circuit

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 550 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	550 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit 260 A 104 °F (40 °C) - 10 s for power circuit 430 A 104 °F (40 °C) - 1 s for power circuit 60 A 104 °F (40 °C) - 10 min for power circuit 138 A 104 °F (40 °C) - 1 min for power circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit 63 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	2 mOhm - Ith 50 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1
Electrical durability	2.1 Mcycles 29 A AC-3 <= 440 V 0.9 Mcycles 50 A AC-1 <= 440 V
Power dissipation per pole	2 W AC-3 5 W AC-1
Front cover	With
Interlocking type	Mechanical
Mounting Support	Rail Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 IEC 60335-1
Product certifications	CCC CSA EAC UL KC DNV-GL LROS (Lloyds register of shipping) UKCA
Connections - terminals	Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)flexible without cable end Control circuit screw clamp terminals 2 0.0020.006 in² (14 mm²)flexible without cable end Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)flexible with cable end Control circuit screw clamp terminals 2 0.0020.004 in² (12.5 mm²)flexible with cable end Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)solid Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)solid Power circuit screw clamp terminals 2 0.0020.006 in² (14 mm²)solid Power circuit screw clamp terminals 1 0.0040.02 in² (2.510 mm²)flexible without cable end Power circuit screw clamp terminals 2 0.0040.02 in² (110 mm²)flexible with cable end Power circuit screw clamp terminals 2 0.0020.009 in² (1.56 mm²)flexible with cable end Power circuit screw clamp terminals 1 0.0020.009 in² (1.56 mm²)flexible with cable end Power circuit screw clamp terminals 1 0.0020.001 in² (1.510 mm²)solid Power circuit screw clamp terminals 2 0.0040.02 in² (1.510 mm²)solid
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Power circuit 22.1 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm Power circuit 22.1 lbf.in (2.5 N.m) screw clamp terminals Philips No 2 Power circuit 22.1 lbf.in (2.5 N.m) screw clamp terminals pozidriv No 2 Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2

Operating time	4555 ms closing 2090 ms opening	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1	
Mechanical durability	15 Mcycles	
Maximum operating rate	3600 cyc/h 140 °F (60 °C)	

# Complementary

•		
Coil technology	Built-in bidirectional peak limiting	
Control circuit voltage limits	<= 0.1 Uc -40158 °F (-4070 °C) drop-out AC/DC 0.851.1 Uc -40140 °F (-4060 °C) operational AC/DC 11.1 Uc 140158 °F (6070 °C) operational AC/DC	
Inrush power in VA	25 VA 50/60 Hz 68 °F (20 °C))	
Inrush power in W	18 W 68 °F (20 °C)	
Hold-in power consumption in VA	1.6 VA 68 °F (20 °C)) 50/60 Hz	
Hold-in power consumption in W	1.1 W 68 °F (20 °C)	
Heat dissipation	1.1 W 50/60 Hz	
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1	
Signalling circuit frequency	25400 Hz	
Minimum switching current	5 mA for signalling circuit	
Minimum switching voltage	17 V for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact     1.5 ms on energisation between NC and NO contact	
Insulation resistance	> 10 MOhm for signalling circuit	

### **Environment**

IP20 front face IEC 60529	
IACS E10 IEC 60947-1 Annex Q category D	
TH IEC 60068-2-30	
3	
-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating	
-76176 °F (-6080 °C)	
09842.52 ft (03000 m)	
1562 °F (850 °C) IEC 60695-2-1	
V1 conforming to UL 94	
Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed15 Gn for 11 ms Shocks contactor open8 Gn for 11 ms	
3.3 in (85 mm)	
3.5 in (90 mm)	
3.6 in (92 mm)	
2.03 lb(US) (0.923 kg)	

color Gray SE GREY 6)
Green SE GREEN 2)

# Ordering and shipping details

Category	US10I1222356	
Discount Schedule	0112	
GTIN	3606480988042	
Returnability	No	
Country of origin	FR	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.5 in (11.5 cm)	
Package 1 Width	4.5 in (11.5 cm)	
Package 1 Length	5.5 in (14.0 cm)	
Package 1 Weight	2.244 lb(US) (1.018 kg)	
Unit Type of Package 2	S02	
Number of Units in Package 2	5	
Package 2 Height	5.9 in (15.0 cm)	
Package 2 Width	11.8 in (30.0 cm)	
Package 2 Length	15.7 in (40.0 cm)	
Package 2 Weight	12.22 lb(US) (5.545 kg)	

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information