Product data sheet

Specifications





reversing contactor TeSys Deca -3 poles - AC-3 - 440V 40A - coil 120V AC 60 Hz - TQPKG

LC2D40AG7TQ

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 667.08 USD

Main

Range	TeSys TeSys Deca
Product name	TeSys Deca
Product or Component Type	Reversing contactor
Device short name	LC2D
contactor application	Resistive load Motor control
Utilisation category	AC-1 AC-3
device presentation	Preassembled with reversing power busbar
poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[le] rated operational current	60 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit
Motor power kW	18.5 kW at 380400 V AC 50 Hz 11 kW at 220230 V AC 50 Hz 22 kW at 415440 V AC 50 Hz 22 kW at 500 V AC 50 Hz 30 kW at 660690 V AC 50 Hz
motor power HP (UL / CSA)	10 hp at 200/208 V AC 60 Hz for 3 phase motors 3 hp at 115 V AC 60 Hz for 1 phase motors 30 hp at 575600 V AC 60 Hz for 3 phase motors 30 hp at 460480 V AC 60 Hz for 3 phase motors 5 hp at 230240 V AC 60 Hz for 1 phase motors 10 hp at 230240 V AC 60 Hz for 3 phase motors
Control circuit type	AC 60 Hz
[Uc] control circuit voltage	120 V AC 60 Hz
Auxiliary contact composition	1 NO + 1 NC
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Overvoltage category	III
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for signalling circuit 60 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 800 A at 440 V for power circuit conforming to IEC 60947-4
Rated breaking capacity	800 A at 220/415/440 V for power circuit conforming to IEC 60947

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Icw] rated short-time withstand current	100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit 320 A 104 °F (40 °C) - 10 s for power circuit 720 A 104 °F (40 °C) - 1 s for power circuit
	72 A 104 °F (40 °C) - 10 min for power circuit 165 A 104 °F (40 °C) - 1 min for power circuit
	165 A 104 F (40 C) - T min for power circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
Average impedance	1.5 mOhm - Ith 60 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL
Electrical durability	1.5 Mcycles 40 A AC-3 <= 440 V 1.4 Mcycles 60 A AC-1 <= 440 V
Power dissipation per pole	5.4 W AC-1 3.4 W AC-3
Front cover	With
Interlocking type	Mechanical
Mounting Support	Plate Rail
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-5-1 IEC 60947-5-1 UL 508 IEC 60335-1
Product certifications	CCC CSA DNV EAC UKCA
Connections - terminals	Control circuit screw clamp terminals 1 0.0020.006 in ² (14 mm ²)flexible without cable end Control circuit screw clamp terminals 2 0.0020.006 in ² (14 mm ²)flexible without cable end Control circuit screw clamp terminals 1 0.0020.006 in ² (14 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.0020.004 in ² (14 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.0020.004 in ² (14 mm ²)flexible with cable end Control circuit screw clamp terminals 1 0.0020.006 in ² (14 mm ²)solid without cable end Control circuit screw clamp terminals 2 0.0020.006 in ² (14 mm ²)solid without cable end Control circuit screw clamp terminals 2 0.0020.006 in ² (14 mm ²)solid without cable end Power circuit screw clamp terminals 1 0.0020.05 in ² (135 mm ²)flexible without cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)flexible without cable end Power circuit screw clamp terminals 1 0.0020.05 in ² (135 mm ²)flexible without cable end Power circuit screw clamp terminals 1 0.0020.05 in ² (135 mm ²)flexible with cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)flexible with cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)flexible with cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)flexible with cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)flexible with cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)flexible with out cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)solid without cable end Power circuit screw clamp terminals 2 0.0020.04 in ² (125 mm ²)solid without cable end
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Power circuit 70.8 lbf.in (8 N.m) EverLink BTR screw connectors 0.040.05 in ² (25 35 mm ²) hexagonal 0.2 in (4 mm) Power circuit 44.3 lbf.in (5 N.m) EverLink BTR screw connectors 0.0020.04 in ² (1 25 mm ²) hexagonal 0.2 in (4 mm)
Operating time	419 ms opening 1226 ms closing

Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	6000000 cycles
Maximum operating rate	3600 cyc/h 140 °F (60 °C)

Complementary

Coil technology	Built-in bidirectional peak limiting diode suppressor
Control circuit voltage limits	0.30.6 Uc -40158 °F (-4070 °C) drop-out AC 60 Hz 0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz 11.1 Uc 140158 °F (6070 °C) operational AC 60 Hz
Inrush power in VA	160 VA 60 Hz 0.75 68 °F (20 °C))
Hold-in power consumption in VA	13 VA 68 °F (20 °C)) 0.3 60 Hz
Heat dissipation	45 W 60 Hz
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling circuit frequency	25400 Hz
Minimum switching current	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Insulation resistance	> 10 MOhm for signalling circuit

Environment

IP degree of protection	IP20 front face IEC 60529
Climatic withstand	IACS E10 IEC 60947-1 Annex Q category D
Protective treatment	TH IEC 60068-2-30
Pollution degree	3
Ambient air temperature for operation	-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating
Ambient Air Temperature for Storage	-76176 °F (-6080 °C)
Operating altitude	09842.52 ft (03000 m)
Fire resistance	1760 °F (960 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor closed10 Gn for 11 ms Shocks contactor open15 Gn for 11 ms
Height	4.8 in (122 mm)
Width	4.7 in (119 mm)
Depth	4.7 in (120 mm)
Net Weight	4.12 lb(US) (1.87 kg)

Ordering and shipping details

Category	US10I1222357
Discount Schedule	0 12

GTIN	3606480787522
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.906 in (15.000 cm)
Package 1 Width	11.811 in (30.000 cm)
Package 1 Length	15.748 in (40.000 cm)
Package 1 Weight	4.070 lb(US) (1.846 kg)
Unit Type of Package 2	S02
Number of Units in Package 2	4
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	17.999 lb(US) (8.164 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	64
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	307.104 lb(US) (139.300 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov