Product data sheet

Specifications





TeSys Deca reversing contactor -3P - <= 440 V - 65 A AC-3 -100...250 V AC/DC coil

LC2D65AKUE

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 366.00 USD

Main

Range	TeSys
	TeSys Deca
Product name	Tesys Deca green
	TeSys Deca
Product or Component Type	Reversing contactor
Device short name	LC2D
contactor application	Motor control
	Resistive load
Utilisation category	AC-3
	AC-1
device presentation	Preassembled with reversing power busbar
poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit 690 V AC 25400 Hz
[le] rated operational current	80 A (at <140 °F (60 °C)) at <= 440 V AC-1 for power circuit
·	65 A (at <140 °F (60 °C)) at <= 440 V AC-3 for power circuit
Motor power kW	18.5 kW at 220230 V AC 50 Hz
	30 kW at 380400 V AC 50 Hz
	37 kW at 415 V AC 50 Hz
	37 kW at 440 V AC 50 Hz
	37 kW at 500 V AC 50 Hz
	37 kW at 660690 V AC 50 Hz
motor power HP (UL / CSA)	5 hp at 115 V AC 60 Hz for 1 phase motors
	10 hp at 230/240 V AC 60 Hz for 1 phase motors
	20 hp at 200/208 V AC 60 Hz for 3 phase motors
	20 hp at 230/240 V AC 60 Hz for 3 phase motors
	40 hp at 460/480 V AC 60 Hz for 3 phase motors
	50 hp at 575/600 V AC 60 Hz for 3 phase motors
Control circuit type	AC 50/60 Hz AC/DC electronic
	DC AC/DC electronic
[Uc] control circuit voltage	100250 V AC 50/60 Hz
	100250 V DC
Auxiliary contact composition	1 NO + 1 NC
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Overvoltage category	III
[Ith] conventional free air thermal	10 A (at 140 °F (60 °C)) for signalling circuit
current	80 A (at 140 °F (60 °C)) for power circuit

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1 1000 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	1000 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit 520 A 104 °F (40 °C) - 10 s for power circuit 900 A 104 °F (40 °C) - 1 s for power circuit 110 A 104 °F (40 °C) - 10 min for power circuit 260 A 104 °F (40 °C) - 1 min for power circuit
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 125 A gG at <= 690 V coordination type 1 for power circuit 125 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	1.5 mOhm - Ith 80 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1
Electrical durability	1.8 Mcycles 57 A AC-3 <= 440 V 0.5 Mcycles 80 A AC-1 <= 440 V
Power dissipation per pole	9.6 W AC-1 6.3 W AC-3
Front cover	With
Interlocking type	Mechanical
Mounting Support	Rail Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 IEC 60335-1
Product certifications	CCC CSA EAC UL KC DNV-GL LROS (Lloyds register of shipping) UKCA
Connections - terminals	Control circuit screw clamp terminals 1 0.0020.006 in ² (14 mm ²)flexible without cable end Control circuit screw clamp terminals 2 0.0020.006 in ² (14 mm ²)flexible without cable end Control circuit screw clamp terminals 1 0.0020.006 in ² (14 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.0020.004 in ² (14 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.0020.004 in ² (14 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.0020.006 in ² (14 mm ²)solid Control circuit screw clamp terminals 2 0.0020.006 in ² (14 mm ²)solid Control circuit screw clamp terminals 2 0.0020.006 in ² (14 mm ²)solid Power circuit EverLink BTR screw connectors 1 0.0020.05 in ² (135 mm ²)flexible without cable end Power circuit EverLink BTR screw connectors 1 0.0020.05 in ² (135 mm ²)flexible with cable end Power circuit EverLink BTR screw connectors 2 0.0020.04 in ² (125 mm ²)flexible with cable end Power circuit EverLink BTR screw connectors 2 0.0020.05 in ² (135 mm ²)flexible with cable end Power circuit EverLink BTR screw connectors 2 0.0020.04 in ² (125 mm ²)flexible with cable end Power circuit EverLink BTR screw connectors 2 0.0020.04 in ² (125 mm ²)flexible with cable end Power circuit EverLink BTR screw connectors 2 0.0020.04 in ² (125 mm ²)flexible with cable end
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Power circuit 70.8 lbf.in (8 N.m) EverLink BTR screw connectors 0.040.05 in ² (25 35 mm ²) hexagonal 0.2 in (4 mm) Power circuit 44.3 lbf.in (5 N.m) EverLink BTR screw connectors 0.0020.04 in ² (1 25 mm ²) hexagonal 0.2 in (4 mm)

Operating time	5565 ms closing 20120 ms opening >= 17221) 2080 ms opening >= 18011)	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1	
Mechanical durability	6 Mcycles	
Maximum operating rate	3600 cyc/h 140 °F (60 °C)	

Complementary

Coil technology	Built-in bidirectional peak limiting
Control circuit voltage limits	<= 0.1 Uc -40158 °F (-4070 °C) drop-out AC/DC 0.851.1 Uc -40140 °F (-4060 °C) operational AC/DC 11.1 Uc 140158 °F (6070 °C) operational AC/DC
Inrush power in VA	18 VA 50/60 Hz 68 °F (20 °C))
Inrush power in W	14 W 68 °F (20 °C)
Hold-in power consumption in VA	1.8 VA 68 °F (20 °C)) 50/60 Hz
Hold-in power consumption in W	1.2 W 68 °F (20 °C)
Heat dissipation	1.2 W 50/60 Hz
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling circuit frequency	25400 Hz
Minimum switching current	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Insulation resistance	> 10 MOhm for signalling circuit

Environment

IP20 front face IEC 60529
IACS E10 IEC 60947-1 Annex Q category D
TH IEC 60068-2-30
3
-40140 °F (-4060 °C) 140158 °F (6070 °C) with derating
-76176 °F (-6080 °C)
09842.52 ft (03000 m)
1562 °F (850 °C) IEC 60695-2-1
V1 conforming to UL 94
Vibrations contactor open2 Gn, 5300 Hz Vibrations contactor closed4 Gn, 5300 Hz Shocks contactor open10 Gn for 11 ms Shocks contactor closed15 Gn for 11 ms
4.8 in (122 mm)
4.7 in (119 mm)
4.7 in (120 mm)
4.793 lb(US) (2.174 kg)

Gray SE GREY 6) Green SE GREEN 2)

Ordering and shipping details

Category	US10I1222356
Discount Schedule	0 12
GTIN	3606480988165
Returnability	No
Country of origin	FR

Packing Units

U	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.7 in (14.5 cm)
Package 1 Width	6.4 in (16.2 cm)
Package 1 Length	7.7 in (19.5 cm)
Package 1 Weight	5.179 lb(US) (2.349 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	21.80 lb(US) (9.89 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts & Cables Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information