## Product data sheet

Specifications





# REVERSING CONTACTOR 575VAC 40A IEC

LC2DT40F7

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Price\*: 601.56 USD

#### Main

| Mann                                   |   |  |
|--|---|--|
| Range                                  | TeSys   |  |
|  | TeSys Deca  |  |
| Product name                           | TeSys Deca  |  |
| Product or Component Type              | Changeover contactor  |  |
| Device short name                      | LC2D  |  |
| contactor application                  | Resistive load  |  |
| Utilisation category                   | AC-1  |  |
|  | AC-3  |  |
|  | AC-3e   |  |
|  | AC-4  |  |
| Device presentation                    | Preassembled with reversing power busbar                        |  |
| poles description                      | 4P  |  |
| power pole contact composition         | 4 NO  |  |
| [Ue] rated operational voltage         | Power circuit <= 690 V AC 25400 Hz                              |  |
|  | Power circuit <= 300 V DC                                       |  |
|  |   |  |
| [le] rated operational current         | 40 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit |  |
| Control circuit type                   | AC 50/60 Hz   |  |
| [Uc] control circuit voltage           | 110 V AC 50/60 Hz   |  |
| Auxiliary contact composition          | 1 NO + 1 NC   |  |
| [Uimp] rated impulse withstand voltage | 6 KV IEC 60947  |  |
| Overvoltage category                   | III   |  |
| [Ith] conventional free air thermal    | 10 A (at 140 °F (60 °C)) for signalling circuit                 |  |
| current                                | 40 A (at 140 $\degree$ F (60 $\degree$ C)) for power circuit    |  |
| Irms rated making capacity             | 140 A AC for signalling circuit conforming to IEC 60947-5-1     |  |
| 3 1 3                                  | 250 A DC for signalling circuit conforming to IEC 60947-5-1     |  |
|  | 450 A at 440 V for power circuit conforming to IEC 60947        |  |
| Rated breaking capacity                | 450 A at 440 V for power circuit conforming to IEC 60947        |  |
| [Icw] rated short-time withstand       | 50 A 104 °F (40 °C) - 10 min for power circuit                  |  |
| current                                | 120 A 104 °F (40 °C) - 1 min for power circuit                  |  |
|  | 240 A 104 °F (40 °C) - 10 s for power circuit                   |  |
|  | 380 A 104 °F (40 °C) - 1 s for power circuit                    |  |
|  | 100 A - 1 s for signalling circuit                              |  |
|  | 120 A - 500 ms for signalling circuit                           |  |
|  | 140 A - 100 ms for signalling circuit                           |  |
| Associated fuse rating                 | 10 A gG for signalling circuit conforming to IEC 60947-5-1      |  |
|  | 63 A gG at <= 690 V coordination type 1 for power circuit       |  |
|  | 40 A gG at <= 690 V coordination type 2 for power circuit       |  |
| Augrana impadance                      |   |  |
| Average impedance                      | 2 mOhm - Ith 40 A 50 Hz for power circuit                       |  |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| [Ui] rated insulation voltage                                       | Power circuit 690 V IEC 60947-4-1  |
|---|--|
|   | Power circuit 600 V CSA  |
|   | Power circuit 600 V UL<br>Signalling circuit 690 V IEC 60947-1   |
|   | Signalling circuit 600 V CSA   |
|   | Signalling circuit 600 V UL  |
| Electrical durability   | 1.4 Mcycles 40 A AC-1 <= 440 V   |
| Power dissipation per pole  | 3.2 W AC-1   |
| Front cover   | With   |
| nterlocking type  | Mechanical   |
| Mounting Support  | Rail   |
|   | Plate  |
| Standards   | CSA C22.2 No 14  |
|   | EN 60947-4-1   |
|   | EN 60947-5-1   |
|   | IEC 60947-4-1  |
|   | IEC 60947-5-1  |
|   | UL 508<br>IEC 60335-1  |
| Product certifications  | UL   |
|   | CSA  |
|   | CCC  |
|   | EAC  |
|   | UKCA   |
|   | CB   |
|   | EU-RO-MR by DNV-GL   |
| Connections - terminals   | Control circuit screw clamp terminals 1 0.0020.006 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without   |
|   | cable end  |
|   | Control circuit screw clamp terminals 2 0.0020.006 in <sup>2</sup> (14 mm <sup>2</sup> )flexible without   |
|   | cable end<br>Control circuit screw clamp terminals 1 0.0020.006 in² (14 mm²)flexible with  |
|   | cable end  |
|   | Control circuit screw clamp terminals 2 0.0020.004 in <sup>2</sup> (12.5 mm <sup>2</sup> )flexible with  |
|   | cable end  |
|   | Control circuit screw clamp terminals 1 0.0020.006 in <sup>2</sup> (14 mm <sup>2</sup> )solid without  |
|   | cable end  |
|   | Control circuit screw clamp terminals 2 0.0020.006 in <sup>2</sup> (14 mm <sup>2</sup> )solid without  |
|   | cable end  |
|   | Power circuit connector 1 0.0040.02 in <sup>2</sup> (2.510 mm <sup>2</sup> )flexible without cable end   |
|   | Power circuit connector 2 0.0040.02 in² (2.510 mm²)flexible without cable end  |
|   | Power circuit connector 1 0.0040.02 in <sup>2</sup> (2.510 mm <sup>2</sup> )flexible with cable end  |
|   | Power circuit connector 2 0.0040.02 in <sup>2</sup> (2.510 mm <sup>2</sup> )flexible with cable end  |
|   | Power circuit connector 1 0.0040.02 in <sup>2</sup> (2.516 mm <sup>2</sup> )solid without cable end<br>Power circuit connector 2 0.0040.02 in <sup>2</sup> (2.516 mm <sup>2</sup> )solid without cable end   |
| lightening torque   | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm   |
| Tightening torque   | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals hat 0 6 mm  |
|   |  |
|   | Power circuit 15.05 lbf.in (1.7 N.m) connector flat Ø 6 mm   |
|   | Power circuit 15.05 lbf.in (1.7 N.m) connector flat Ø 6 mm<br>Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2  |
|   | Power circuit 15.05 lbf.in (1.7 N.m) connector flat Ø 6 mm<br>Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2<br>Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2  |
|   | Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2  |
| Operating time  | Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2<br>Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2  |
| Operating time  | Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2<br>Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2<br>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2  |
|   | Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2<br>Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2<br>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2<br>1222 ms closing   |
|   | Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2<br>Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2<br>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2<br>1222 ms closing<br>419 ms opening   |
| Operating time<br>Safety reliability level<br>Mechanical durability | Power circuit 15.05 lbf.in (1.7 N.m) connector Philips No 2<br>Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2<br>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals pozidriv No 2<br>1222 ms closing<br>419 ms opening<br>B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 |

## Complementary

| Coil technology                | Without built-in suppressor module   |
|--------------------------------|--|
| Control circuit voltage limits | 0.30.6 Uc -40140 °F (-4060 °C) drop-out AC 50/60 Hz<br>0.81.1 Uc -40140 °F (-4060 °C) operational AC 50 Hz<br>0.851.1 Uc -40140 °F (-4060 °C) operational AC 60 Hz |

| Inrush power in VA              | 70 VA 60 Hz 0.75 68 °F (20 °C))<br>70 VA 50 Hz 0.75 68 °F (20 °C))                                      |  |
|---------------------------------|---|--|
| Hold-in power consumption in VA | 7.5 VA 68 °F (20 °C)) 0.3 60 Hz<br>7 VA 68 °F (20 °C)) 0.3 50 Hz  |  |
| Heat dissipation                | 23 W 50/60 Hz   |  |
| Auxiliary contacts type         | Mechanically linked 1 NO + 1 NC IEC 60947-5-1<br>Mirror contact 1 NC IEC 60947-4-1                      |  |
| Signalling circuit frequency    | 25400 Hz  |  |
| Minimum switching current       | 5 mA for signalling circuit   |  |
| Minimum switching voltage       | 17 V for signalling circuit   |  |
| Non-overlap time                | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact |  |
| Insulation resistance           | > 10 MOhm for signalling circuit  |  |

#### Environment

| IP20 front face IEC 60529   |
|---|
| IACS E10<br>IEC 60947-1 Annex Q category D  |
| TH IEC 60068-2-30   |
| 3   |
| -40140 °F (-4060 °C)<br>140158 °F (6070 °C) with derating   |
| -76176 °F (-6080 °C)  |
| 09842.52 ft (03000 m)   |
| 1562 °F (850 °C) IEC 60695-2-1  |
| V1 conforming to UL 94  |
| Vibrations contactor open2 Gn, 5300 Hz<br>Vibrations contactor closed4 Gn, 5300 Hz<br>Shocks contactor closed15 Gn for 11 ms<br>Shocks contactor open8 Gn for 11 ms |
| 3.6 in (91 mm)  |
| 3.5 in (90 mm)  |
| 3.9 in (98 mm)  |
| 1.87 lb(US) (0.85 kg)   |
|   |

## Ordering and shipping details

| Category          | US10I1222354  |  |
|-------------------|---------------|--|
| Discount Schedule | 012           |  |
| GTIN              | 3389110516234 |  |
| Returnability     | No            |  |
| Country of origin | FR            |  |

## **Packing Units**

| Unit Type of Package 1       | PCE               |
|------------------------------|-------------------|
| Number of Units in Package 1 | 1                 |
| Package 1 Height             | 3.57 in (9.08 cm) |

| Package 1 Width  | 3.5 in (9.0 cm)   |  |
|------------------|-------------------|--|
| Package 1 Length | 3.92 in (9.95 cm) |  |
| Package 1 Weight | 30.7 oz (870.0 g) |  |

## **Contractual warranty**

Warranty

18 months

### Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant<br>EU RoHS Declaration  |
| China Rohs Regulation     | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste<br>collection and never end up in rubbish bins.   |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |