

Photomos / 1 FORM A

Solid State Relays


Model Number	PLA110L PLA110 LCA110(L) LCA120L PLA134 PLA140									
Parameters	Sym.	Test Conditions	Units		1 Form A	1 Form A	1 Form A	1 Form A	1 Form A	1 Form A
Input Characteristics										
LED Forward Current - Turn on	I_{Fon}	$I_L = 100mA, t = 10ms$	mADC	Max Typ	5.0 2.0	5.0 2.0	5.0 2.0	5.0 2.0	5.0 2.0	5.0 2.0
LED Forward Current - Turn off	I_{Foff}	$I_L = 0.2mA, V_L = (Note 1)$	mADC	Min Typ	0.1 1.8	0.1 1.8	0.1 1.8	0.1 1.8	0.1 1.8	0.1 1.8
Recommended Forward Current	I_F		mADC	Min Max	10 30	10 30	10 30	10 30	10 30	10 30
LED Forward Voltage	V_F	$I_F = 20mA$	VDC	Min Max	1.1 1.4	1.1 1.4	1.1 1.4	1.1 1.4	1.1 1.4	1.1 1.4
Maximum Input Ratings										
LED Forward Current	I_F		mADC	Max	50	50	50	50	50	50
LED Reverse Voltage Withstand	V_R	$I_R = 10mA$		Max	10	10	10	10	10	10
Output Characteristics										
Switching Voltage	V_L	$I_L = 50mA$	V PEAK	Max	400	400	400	250	150	400
Switching Current: AC Mode(Note2)	I_L	Pin 4 to Pin 6	mA	Max	150	150	120	150	450	225
Switching Current: DC Mode(Note2)	I_L	Pins 5(-) to Pins 4&6 (+)	mA	Max	250	250	200	250	900	425
Current Limit: AC Mode(Note2)	I_{Lmt}	$I_F = 5mA, t = 5ms$	mA	Typ	380	n/a	380	380	n/a	n/a
Current Limit: DC Mode(Note2)	I_{Lmt}	$I_F = 5mA, t = 5ms$	mA	Typ	540	n/a	540	760	n/a	n/a
On Resistance: AC Mode(Note2)	R_{on}	$I_F = 5mA, I_L = 50mA$	Ω	Max	24	18	35	18	5	9
On Resistance: DC Mode(Note2)	R_{on}	$I_F = 5mA, I_L = 50mA$	Ω	Max	6	4.5	8.75	4.5	1.25	2.25
Off State Resistance	R_{off}	$I_F = 0mA, V_L = 100V$	G Ω	Min Typ	0.5 5000	0.5 5000	0.5 5000	0.5 5000	0.5 5000	0.5 5000
Off State Leakage	I_{off}	$I_F = 0mA, V_L = 100V$	nA	Max Typ	200 0.5	200 0.5	200 0.5	200 0.5	200 0.5	200 0.5
Turn On Time	T_{on}	$I_F = 5mA, I_L = 50mA$	ms	Max	5.0	5.0	5.0	5.0	5.0*	5.0
Turn Off Time	T_{off}	$I_F = 5mA, I_L = 50mA$	ms	Max	1.0	1.0	1.0	1.0	1.0	1.0
Capacitance - Across Output		$I_F = 0mA, V_L = 1V$ $I_F = 0mA, V_L = 50V$	pF	Typ	95 10	95 10	60 7	110 15	170 30	225 10
Thermal Offset Voltage		$I_F = 5mA$	mV	Typ	0.2	0.2	0.2	0.2	0.2	0.2
General Characteristics										
Dielectric Strength - Input to Output		$t = 60sec$	VRMS	Min	3750	3750	3750	3750	3750	3750
Capacitance - Input to Output			pF	Typ	0.8	0.8	0.8	0.8	0.8	1.1
Power Dissipation	P_{Diss}		mW	Max	500	500	500	500	600	600

Notes:


- 1: V_L for LED Forward Current - Turn Off is 50 Volts less than "Switching Voltage : Max".
- 2: See "AC Mode and DC Mode Operation" on Page 67 for further description of AC and DC Mode.
- 3: Specifications subject to change without notice.

Schematic Top View:
Mold mark on top of relay indicates Pin #1


* $I_F = 10mA$




Photomos / 1 FORM A




A. Load Current vs. Ambient Temperature




B. Output MOSFET BV vs. Ambient Temperature




C. On-Resistance vs. Ambient Temperature




D. Output Capacitance vs. Applied Voltage




E. On Time vs. Ambient Temperature



F. Turn Off Time vs. Ambient Temperature



G. Turn On Time vs. LED Forward Current



H. Turn Off Time vs. LED Forward Current

For recommended applications and more information contact:
USA: Sales Support (877) 502-5500 Tech Support (877) 702-7700 FAX (619) 710-8540
 Crydom Corp, 2320 Paseo de las Americas, Ste. 201, San Diego, CA 92154
 Email: sales@crydom.com **WEB SITE:** <http://www.crydom.com>

UK: +44 (0)1202 365070 • **FAX** +44 (0)1202 365090 Crydom International Ltd., 7 Cobham Road, Ferndown Industrial Estate, Ferndown, Dorset BH21 7PE, **Email:** intsales@crydom.com.
GERMANY: +49 (0)180 3000 506