



Siemens Low Voltage Circuit Protection General Duty Safety Switches.  
Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 240V A. Rating:  
30 A No. Of Poles: 2P F. Rating: 60Hz Action: SINGLE THROW Material:  
304SS Enclosure: TYPE 3R. 2-3 point mounting holes. O. Cycles: 10000  
O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental  
Conditions: OUTDOOR

mechanical service life (switching cycles) typical	10000
fastening method	SURFACE
number of poles	2
suitability for operation	DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS
<b>Electricity</b>	
ampacity	30 A
<b>Environmental conditions</b>	
ambient temperature during operation maximum	85 °C
ambient temperature during operation minimum	-29 °C
<b>Model</b>	
product brand name	SIEMENS
product sub brand name	VBII
product type designation	GENERAL DUTY PLUG FUSE
type of electrical connection	MECHANICAL LUGS
<b>Mechanical Design</b>	
design of the housing	TYPE 3R
design of the actuating element	SINGLE THROW
material	STEEL
<b>General product approval</b>	
certificate of suitability	UL98

last modified:

9/15/2021 

