

## 30A Kit Black handle NEMA 4

LK4DUKB4

Discontinued on: Nov 20, 2023

#### Main

Range	TeSys
Product or component type	Disconnect Switch
Disconnector device type	Non-fusible disconnect switch
Suitability for isolation	Yes
Handle colour	Black
Handle front plate colour	Black

### Complementary

Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[le] rated operational current	30 A600 V AC UL
	30 A600 V AC CSA
	32 A400 V AC AC-22A IEC
	32 A400 V AC AC-23A IEC
	32 A690 V AC AC-22A IEC
	32 A690 V AC AC-23A IEC
[Ue] rated operational voltage	600 V AC 50/60 Hz
Rated power in W	15 kW 400 V
	18.5 kW 500 V
	25 kW 690 V
Rated power in hp	10 hp 240 V 30 A AC
	20 hp 480 V 28 A AC
	25 hp 600 V 28 A AC
[lcw] rated short-time withstand current	5.5 kA
Mechanical durability	10000 cycles
Electrical durability	6000 cycles
Connections - terminals	Lugs-ring terminals 1 0.006 in² (4 mm²)
Width	3.1 in (79.5 mm)

## **Environment**

NEMA degree of protection	NEMA 4
Standards	UL98 CSA C22.2 No 4 IEC 60947-3

Product certifications	UL CSA
Height	4.9 in (125 mm)
Depth	2.5 in (64 mm)

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.9 in (12.5 cm)
Package 1 Width	3.1 in (8.0 cm)
Package 1 Length	2.5 in (6.4 cm)
Package 1 Weight	16.000 oz (453.592 g)

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

### Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration