

Product data sheet

Specifications



TeSys LK - disconnect switch -3P - 60A - AC

LK4GU3CN

Discontinued on: Nov 22, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

Discontinued

Main

Range	TeSys
Product Name	TeSys LK
Product Or Component Type	Disconnect Switch
Disconnecter Device Type	Non-fusible disconnect switch
Suitability For Isolation	Yes

Complementary

Poles Description	3P
Network Type	AC
Network Frequency	50/60 Hz
[Ie] Rated Operational Current	63 A400 V AC AC-22A IEC 63 A400 V AC AC-23A IEC 63 A690 V AC AC-22A IEC 63 A690 V AC AC-23A IEC 60 A CSA 60 A UL
[Ue] Rated Operational Voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	750 V
Control Type	Rotary handle
Type Of Operating Handle	External right side External frontal
Mounting Support	Plate
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC
Rated Power In W	30 kW 400 V 40 kW 500 V 55 kW 690 V
Rated Power In Hp	20 hp 240 V 56 A AC 40 hp 480 V 53 A AC 50 hp 600 V 52 A AC
[Icw] Rated Short-Time Withstand Current	17.6 kA
Mechanical Durability	10000 cycles
Electrical Durability	6000 cycles
Connections - Terminals	Lugs-ring terminals 1 0.01 in ² (4 mm ²)
Height	4.92 in (125 mm)
Width	3.13 in (79.5 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	2.52 in (64 mm)
-------	-----------------

Environment

Standards	UL98 CSA C22.2 No 4 IEC 60947-3
Product Certifications	UL CSA CE

Ordering and shipping details

Category	US10I1122640
Discount Schedule	0I11
Gtin	3606480510427
Returnability	No
Country Of Origin	TN

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.27 in (8.3 cm)
Package 1 Width	3.54 in (9 cm)
Package 1 Length	6.30 in (16 cm)
Package 1 Weight	21.98 oz (623 g)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant	EU RoHS Declaration
China Rohs Regulation		China RoHS declaration
California Proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov	