

Product data sheet

Specifications



TeSys LK disconnect switch kit, 3 pole, 60 A disconnect switch, shaft, guide cone, black rotary handle, NEMA 1, 3R, 12

LK4GUKB1

! Discontinued

! Discontinued on: Aug 24, 2022

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| | |
|---------------------------|-------------------------------|
| Range | TeSys |
| Product Or Component Type | Disconnect Switch |
| Disconnecter Device Type | Non-fusible disconnect switch |
| Suitability For Isolation | Yes |
| Handle Colour | Black |
| Handle Front Plate Colour | Black |

Complementary

| | |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Poles Description | 3P |
| Network Type | AC |
| Network Frequency | 50/60 Hz |
| [Ie] Rated Operational Current | 60 A600 V AC UL 60 A600 V AC CSA 63 A400 V AC AC-22A IEC 63 A400 V AC AC-23A IEC 63 A690 V AC AC-22A IEC 63 A690 V AC AC-23A IEC |
| [Ue] Rated Operational Voltage | 600 V AC 50/60 Hz |
| Rated Power In W | 30 kW 400 V 40 kW 500 V 55 kW 690 V |
| Rated Power In Hp | 20 hp 240 V 56 A AC 40 hp 480 V 53 A AC 50 hp 600 V 52 A AC |
| [Icw] Rated Short-Time Withstand Current | 17.6 kA |
| Mechanical Durability | 10000 cycles |
| Electrical Durability | 6000 cycles |
| Connections - Terminals | Lugs-ring terminals 1 0.01 in ² (4 mm ²) |
| Width | 3.13 in (79.5 mm) |

Environment

| | |
|---------------------------|--------------|
| Nema Degree Of Protection | NEMA 1/12/3R |
|---------------------------|--------------|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------|---------------------------------------|
| Standards | UL98 CSA C22.2 No 4 IEC 60947-3 |
| Product Certifications | UL CSA |
| Height | 4.92 in (125 mm) |
| Depth | 2.52 in (64 mm) |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10I1122640 |
| Discount Schedule | 0I11 |
| Gtin | 785901482826 |
| Returnability | No |
| Country Of Origin | FR |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.92 in (12.5 cm) |
| Package 1 Width | 3.15 in (8.0 cm) |
| Package 1 Length | 2.52 in (6.4 cm) |
| Package 1 Weight | 16.00 oz (453.592 g) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

| | | |
|---------------------------|------------------------------------------|---------------------|
| ✓ | Reach Free Of Svhc | |
| ✓ | Toxic Heavy Metal Free | |
| ✓ | Mercury Free | |
| ✓ | Rohs Exemption Information | Yes |
| Reach Regulation | REACH Declaration | |
| Eu Rohs Directive | Compliant | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration | |
| California Proposition 65 | WARNING: Cancer - www.P65Warnings.ca.gov | |