

LK4GUKB4

TeSys LK disconnect switch kit, disconnect switch, 3 P, 60 A, shaft, guide cone, black handle, NEMA 4

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product or component type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes
Handle colour	Black
Handle front plate colour	Black

Complementary

Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	60 A600 V AC UL 60 A600 V AC CSA 63 A400 V AC AC-22A IEC 63 A400 V AC AC-23A IEC 63 A690 V AC AC-22A IEC 63 A690 V AC AC-23A IEC
[Ue] rated operational voltage	600 V AC 50/60 Hz
Rated power in W	30 KW 400 V 40 KW 500 V 55 kW 690 V
Rated power in hp	20 Hp 240 V 56 A AC 40 Hp 480 V 53 A AC 50 hp 600 V 52 A AC
[Icw] rated short-time withstand current	17.6 kA
Mechanical durability	10000 cycles
Electrical durability	6000 cycles
Connections - terminals	Lugs-ring terminals 1 0.01 in ² (4 mm ²)
Width	3.13 in (79.5 mm)

Environment

NEMA degree of protection	NEMA 4
Standards	UL98 CSA C22.2 No 4 IEC 60947-3
Product certifications	UL CSA
Height	4.92 in (125 mm)
Depth	2.52 in (64 mm)

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901758662
Package weight(Lbs)	0.45 kg (1 lb(US))
Returnability	Yes
Country of origin	CN

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------