

Product data sheet

Specifications



Disconnect Switch, TeSys LK, nonfusible, 200A, 600 V, HP rated, 3 pole, rotary handle, up to 200kA SCCR

LK4MU3N

Product availability: Stock - Normally stocked in distribution facility

Price*: 1,010.00 USD

Main

Range	TeSys
Product Name	TeSys LK
Product Or Component Type	Disconnect Switch
Disconnecter Device Type	Non-fusible disconnect switch
Suitability For Isolation	Yes

Complementary

Poles Description	3P
Network Type	AC DC
Network Frequency	50/60 Hz
[Ie] Rated Operational Current	200 A400 V AC AC-22A IEC 200 A400 V AC AC-23A IEC 200 A690 V AC AC-22A IEC 200 A690 V AC AC-23A IEC 200 A CSA 200 A UL
[Ue] Rated Operational Voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	750 V
Control Type	Rotary handle
Type Of Operating Handle	External frontal External right side
Mounting Support	Plate
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC
Rated Power In W	100 kW 400 V 140 kW 500 V 185 kW 690 V
Rated Power In Hp	75 hp 240 V 92 A AC 150 hp 480 V 187 A AC 200 hp 600 V 192 A AC 15 hp 125 V 112 A DC 15 hp 250 V 56 A DC
[Icw] Rated Short-Time Withstand Current	32 kA
Mechanical Durability	8000 cycles
Electrical Durability	6000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - Terminals	Lugs-ring terminals 1 0.02 in² (16 mm²)
Height	6.30 in (160 mm)
Width	7.09 in (180 mm)
Depth	3.74 in (95 mm)
Net Weight	5.03 lb(US) (2.28 kg)

Environment

Standards	IEC 60947-3 CSA C22.2 No 4 UL98
Product Certifications	UL CSA CE

Ordering and shipping details

Category	US10I1122640
Discount Schedule	0I11
Gtin	3606480510458
Returnability	Yes
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.69 in (17.000 cm)
Package 1 Width	11.02 in (28.000 cm)
Package 1 Length	11.02 in (28.000 cm)
Package 1 Weight	4.99 lb(US) (2.264 kg)
Unit Type Of Package 2	S04
Number Of Units In Package 2	4
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	22.15 lb(US) (10.046 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Reach Regulation		REACH Declaration
Eu Rohs Directive		Compliant EU RoHS Declaration
China Rohs Regulation		China RoHS declaration
California Proposition 65		WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov