



# Reversing contactor, TeSys K, 3P, AC-3, It or eq to 440V 9A, 1 NO, 24VDC coil

LP2K09103BD

! Discontinued on: Jul 12, 2021



Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range	TeSys	
Product name	TeSys K	
Product or Component Type	Reversing contactor	
Device short name	LP2K	
Device Application	Control	
contactor application	Resistive load Motor control	
Utilisation category	AC-4 AC-1 AC-3	
Device presentation	Preassembled with reversing power busbar	
poles description	3P	
power pole contact composition	3 NO	
[Ue] rated operational voltage	Power circuit 690 V AC 50/60 Hz Signalling circuit <= 690 V AC 50/60 Hz	
[le] rated operational current	16 A (at <122 °F (50 °C)) at <= 440 V AC AC-1 for power circuit 9 A at <= 440 V AC AC-3 for power circuit	
Motor power kW	2.2 kW 220230 V AC 50/60 Hz 4 kW 380415 V AC 50/60 Hz 4 kW 440 V AC 50/60 Hz 4 kW 480 V AC 50/60 Hz 4 kW 500600 V AC 50/60 Hz 4 kW 660690 V AC 50/60 Hz	
Control circuit type	DC standard	
[Uc] control circuit voltage	24 V DC	
Auxiliary contact composition	1 NO	
[Uimp] rated impulse withstand 8 kV voltage		
Overvoltage category	III	
[Ith] conventional free air thermal current	16 A (at 122 °F (50 °C)) for power circuit 10 A (at 122 °F (50 °C)) for signalling circuit	
Irms rated making capacity	110 A AC for power circuit conforming to NF C 63-110 110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Rated breaking capacity	110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947
	80 A at 500 V conforming to IEC 60947
	110 A at 220230 V conforming to IEC 60947
	110 A at 380400 V conforming to IEC 60947
	70 A at 660690 V conforming to IEC 60947
[lcw] rated short-time withstand current	90 A 122 °F (50 °C) - 1 s for power circuit 85 A 122 °F (50 °C) - 5 s for power circuit
	80 A 122 °F (50 °C) - 10 s for power circuit
	60 A 122 °F (50 °C) - 30 s for power circuit
	45 A 122 °F (50 °C) - 1 min for power circuit
	40 A 122 °F (50 °C) - 3 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit
	110 A - 100 ms for signalling circuit
	20 A 122 °F (50 °C) - >= 15 min for power circuit
Associated fuse rating	25 A gG at <= 440 V for power circuit
	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947
	10 A gG for signalling circuit conforming to VDE 0660
Average impedance	3 mOhm - Ith 16 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit 600 V UL 508
	Power circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-4-1
	Signalling circuit 690 V IEC 60947-5-1 Signalling circuit 600 V UL 508
	Power circuit 600 V CSA C22.2 No 14
	Signalling circuit 600 V CSA C22.2 No 14
Electrical durability	0.18 Mcycles 20 A AC-1 <= 440 V
	1.3 Mcycles 9 A AC-3 <= 440 V
Interlocking type	Mechanical
Mounting Support	Plate Rail
Standards	EN/IEC 60947-4-1
	GB/T 14048.4
	UL 60947-4-1 CSA C33 3 No 60047 4.1
	CSA C22.2 No 60947-4-1 JIS C8201-4-1
Product Certifications	CB Scheme
Troduct Cordinations	CCC
	UL
	CSA
	EAC
	CE
	UKCA
Connections - terminals	spring terminals 1 0.0010.002 in² (0.751.5 mm²)solid spring terminals 1 0.0010.002 in² (0.751.5 mm²)flexible without cable end
On a section of the	
Operating time	3040 ms coil energisation and NO closing 10 ms coil de-energisation and NO opening
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	5 Mcycles
Maximum operating rate	3600 cyc/h
Complementary	
Control circuit voltage limits	Operational: 0.81.15 Uc (at <122 °F (50 °C)) Drop-out: 0.10.75 Uc (at <122 °F (50 °C))
Inrush power in W	3 W 68 °F (20 °C))
Hold-in power consumption in W	3 W 68 °F (20 °C)
Heat dissipation	3 W

Auxiliary contacts type	Instantaneous 1 NO	
Minimum switching current 5 mA for signalling circuit		
Minimum switching voltage 17 V for signalling circuit		
Non overlap distance 0.02 in (0.5 mm)		
Insulation resistance	> 10 MOhm for signalling circuit	

#### **Environment**

IP degree of protection	IP20 VDE 0106	
Protective treatment	TC IEC 60068 TC DIN 50016	
Ambient Air Temperature for Operation	-13122 °F (-2550 °C)	
Ambient Air Temperature for -58176 °F (-5080 °C) Storage		
Operating altitude	6561.68 ft (2000 m) without derating	
Flame retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102	
Mechanical robustness	Shocks contactor closed, on Z axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Z axis10 Gn for 11 ms IEC 60068-2-27 Vibrations contactor closed4 Gn, 5300 Hz IEC 60068-2-6 Vibrations contactor opened2 Gn, 5300 Hz IEC 60068-2-6 Shocks contactor opened, on X axis10 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Y axis6 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on X axis15 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Y axis10 Gn for 11 ms IEC 60068-2-27	
Height	2.3 in (58 mm)	
Width	3.5 in (90 mm)	
Depth	2.2 in (57 mm)	
Net Weight	1.06 lb(US) (0.48 kg)	

## Ordering and shipping details

Category	US10I1222322
Discount Schedule	0112
GTIN	3389110242928
Returnability	Yes
Country of origin	US

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.9 in (4.8 cm)	
Package 1 Width	2.6 in (6.5 cm)	
Package 1 Length	2.4 in (6.2 cm)	
Package 1 Weight	8.0 oz (226 g)	

## **Contractual warranty**

Warranty 18 months	
--------------------	--

## Sustainability Green Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>②</b>	Reach Free Of Svhc	
<b>9</b>	Toxic Heavy Metal Free	
<b>②</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Compliant
EU RoHS Declaration
China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
End of Life Information
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Oct 14, 2024