## Product data sheet

Specifications





() Discontinued

# TeSys LRF - electronic thermal overload relay - 200...330 A - class 10/20

LR9F75

(Discontinued on: Jun 15, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range	TeSys	
Product name	TeSys LRF	
Device short name	LR9F	
Product or Component Type	Electronic thermal overload relay	
relay application	Motor protection	
Product Compatibility	LC1F225LC1F500	
Network type	AC	
Thermal overload class	Class 10/20 IEC 60947-4	
Thermal protection adjustment range	200330 A	
Signalling function	Pre-alarm indicator	

### Complementary

Network Frequency	50/60 Hz	
[Us] rated supply voltage	24 V DC alarm circuit	
Supply voltage limits	1732 V alarm circuit)	
Mounting support	Direct on contactor Plate	
Tripping threshold	1.05 +/- 0.06 In alarm IEC 60947-4-1 1.12 +/- 0.06 In tripping IEC 60947-4-1	
Surge withstand	4 kV IEC 61000-4-5	
Contacts type and composition	1 NO + 1 NC	
[Ith] conventional free air thermal current	5 A control circuit	
[Ue] rated operational voltage	1000 V AC 50/60 Hz power circuit VDE 0110 group C	
[Ui] rated insulation voltage	Power circuit 1000 V AC IEC 60947-4	
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-1	
Phase failure sensitivity	Tripping in 4 s +/- 20 % IEC 60947-4-1	
Reset	Manual reset	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Control type	Dial White full-load current adjustment	
	Test button Red	
	Push-button reset	
	Push-button Red stop	
	Selector switch load balancing	
	Selector switch class 10/20	
local signalling	Trip indicator	
	Alarm	
Temperature compensation	-4158 °F (-2070 °C)	
Current consumption	<= 5 mA no-load	
switching capacity for alarm	0150 mA	
Maximum voltage drop	<2.5 V closed state	
Connections - terminals	Control circuit screw clamp terminals 1 0.0010.004 in <sup>2</sup> (0.752.5 mm <sup>2</sup> ) flexible -	
	with cable end	
	Control circuit screw clamp terminals 1 0.0010.004 in <sup>2</sup> (0.752.5 mm <sup>2</sup> ) solid	
	Control circuit screw clamp terminals 1 0.0010.006 in <sup>2</sup> (0.754 mm <sup>2</sup> ) flexible -	
	without cable end	
	Control circuit screw clamp terminals 2 0.0020.002 in <sup>2</sup> (11.5 mm <sup>2</sup> ) flexible - with cable end	
	Control circuit screw clamp terminals 2 0.0020.004 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible -	
	without cable end	
	Control circuit screw clamp terminals 2 0.002 in <sup>2</sup> (1 mm <sup>2</sup> ) solid	
	Alarm circuit screw clamp terminals 1 0.00080.002 in <sup>2</sup> (0.51.5 mm <sup>2</sup> ) flexible -	
	without cable end	
Tightening torque	Control circuit 1.2 N.m screw clamp terminals	
	Power circuit 35 N.m screw clamp terminals	
	Alarm circuit 0.45 N.m screw clamp terminals	
Height	5.4 in (136.8 mm)	
Width	5.9 in (150 mm)	
Depth	5.02 in (127.6 mm)	
Net Weight	5.11 lb(US) (2.32 kg)	

## Environment

Standards	IEC 60255-8 IEC 60947-4-1 IEC 60255-17 VDE 0660 EN 60947-4-1	
Product Certifications	UL CSA UKCA	
Protective treatment	тн	
IP degree of protection	IP20 conforming to IEC 60529	
Ambient air temperature for operation	-4131 °F (-2055 °C) IEC 60255-8	
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)	
Operating altitude	<= 6561.68 ft (2000 m) without derating	
Fire resistance	1562 °F (850 °C) IEC 60695-2-1	
Mechanical robustness	Shocks13 Gn for 11 ms IEC 60068-2-7 Vibrations 5300 Hz2 GN IEC 60068-2-6	
Dielectric strength	6 kV 50 Hz IEC 255-5	
Electromagnetic compatibility	Resistance to electrostatic discharge 6 kV in indirect mode IEC 61000-4-2 Resistance to electrostatic discharge 8 kV in air IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test 10 V/m IEC 61000-4-3 Fast transients immunity test 2 kV IEC 61000-4-4	

## Ordering and shipping details

Category	US10I1222334	
Discount Schedule	0112	
GTIN	3389118057562	
Returnability	No	
Country of origin	FR	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.09 in (18.0 cm)
Package 1 Width	7.9 in (20.0 cm)
Package 1 Length	7.7 in (19.5 cm)
Package 1 Weight	4.356 lb(US) (1.976 kg)

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov