# **Product datasheet**

Specification





# Thermal overload relay,TeSys Deca,16-24A,1NO+1NC,class 10A,spring terminal

LRD223

#### Main

Range	TeSys TeSys Deca	
Product name	TeSys LRD TeSys Deca	
Product or component type	Differential thermal overload relay	
Device short name	LRD	
relay application	Motor protection	
Product compatibility	LC1D25 LC1D32 LC1D38	
Network type	AC DC	
Thermal overload class	Class 10A conforming to IEC 60947-4-1	
Thermal protection adjustment range	1624 A	
[Ui] rated insulation voltage	Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL Power circuit: 690 V conforming to IEC 60947-4-1	

## Complementary

Network frequency	0400 Hz
Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor
Tripping threshold	1.14 +/- 0.06 Ir conforming to IEC 60947-4-1
Auxiliary contact composition	1 NO + 1 NC
[Ith] conventional free air thermal current	5 A for signalling circuit
Permissible current	1.5 A at 240 V AC-15 for signalling circuit 0.1 A at 250 V DC-13 for signalling circuit
[Ue] rated operational voltage	690 V AC 0400 Hz for power circuit conforming to IEC 60947-4-1
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit
[Uimp] rated impulse withstand voltage	6 kV
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0
Control type	Red push-button: stop Blue push-button: reset
Temperature compensation	-2060 °C

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Connections - terminals	Control circuit: spring terminals 1 cable(s) 12.5 mm² solid without cable end Control circuit: spring terminals 1 cable(s) 12.5 mm² flexible without cable end Power circuit: spring terminals 1 cable(s) 1.54 mm² flexible without cable end Power circuit: spring terminals 1 cable(s) 1.54 mm² flexible with cable end
Height	93 mm
Width	45 mm
Depth	72 mm
Net weight	0.14 kg

## **Environment**

Climatic withstand	conforming to IACS E10	
IP degree of protection	IP20 conforming to IEC 60529  -2060 °C without derating conforming to IEC 60947-4-1	
Ambient air temperature for operation		
Ambient air temperature for storage	-6070 °C	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations: 6 Gn conforming to IEC 60068-2-6 Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7	
Dielectric strength	1.89 kV at 50 Hz conforming to IEC 60947-1	
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495	
Product certifications	IEC UL CSA CCC EAC BV RINA DNV-GL LROS (Lloyds register of shipping) ATEX INERIS UKCA	

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	8.000 cm
Package 1 Length	10.000 cm
Package 1 Weight	196.300 g
Unit Type of Package 2	S02
Number of Units in Package 2	23
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.758 kg

Unit Type of Package 3	P06
Number of Units in Package 3	368
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	84.130 kg

## **Contractual warranty**

Warranty 18 months

# Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Sustainable Packaging Transparency RoHS/REACh

#### Resource performance



Sustainable Packaging

### Well-being performance

V

Reach Free Of Svhc



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information