# **Product data sheet**

Specifications





# TeSys Deca thermal overload relays - 17...24 A - class 20

LRD22L

Product availability: Stock - Normally stocked in distribution facility

Price\*: 62.00 USD

#### Main

| Range                               | TeSys<br>TeSys Deca  |
|-------------------------------------|--|
| Product Name                        | TeSys LRD<br>TeSys Deca  |
| Product Or Component Type           | Differential thermal overload relay  |
| Device Short Name                   | LRD  |
| Relay Application                   | Motor protection   |
| Product Compatibility               | LC1D38<br>LC1D25<br>LC1D32   |
| Network Type                        | AC<br>DC   |
| Thermal Overload Class              | Class 20 IEC 60947-4-1   |
| Thermal Protection Adjustment Range | 1724 A   |
| [Ui] Rated Insulation Voltage       | Power circuit 600 V CSA<br>Power circuit 600 V UL<br>Power circuit 690 V IEC 60947-4-1 |

## Complementary

| Network Frequency                              | 0400 Hz  |
|--|--|
| Mounting Support                               | Plate, with specific accessories Rail, with specific accessories Under contactor |
| Tripping Threshold                             | 1.14 +/- 0.06 Ir IEC 60947-4-1   |
| Auxiliary Contact Composition                  | 1 NO + 1 NC  |
| [Ith] Conventional Free Air<br>Thermal Current | 5 A signalling circuit   |
| Permissible Current                            | 3 A 120 V AC-15 signalling circuit<br>0.22 A 125 V DC-13 signalling circuit      |
| [Ue] Rated Operational Voltage                 | 690 V AC 0400 Hz power circuit IEC 60947-4-1                                     |
| Associated Fuse Rating                         | 4 A gG for signalling circuit 4 A BS for signalling circuit                      |
| [Uimp] Rated Impulse Withstand<br>Voltage      | 6 kV   |
| Phase Failure Sensitivity                      | Tripping current 130 % of Ir on two phase, the last one at 0                     |
| Control Type                                   | Red push-button stop<br>Blue push-button reset                                   |
| Temperature Compensation                       | -4140 °F (-2060 °C)  |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Connections - Terminals | Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) flexible without cable end Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) flexible with cable end Control circuit screw clamp terminals 2 0.000.00 in² (12.5 mm²) solid without cable end Power circuit screw clamp terminals 1 0.000.02 in² (1.510 mm²) flexible without cable end Power circuit screw clamp terminals 1 0.000.01 in² (16 mm²) flexible with cable end Power circuit screw clamp terminals 1 0.000.02 in² (1.510 mm²) solid without cable end |
|-------------------------|---|
| Tightening Torque       | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals   |
|                         | 2.60 in (66 mm)   |
| Width                   | 1.77 in (45 mm)   |
| Depth                   | 2.99 in (76 mm)   |
| Net Weight              | 0.32 lb(US) (0.144 kg)  |

## **Environment**

| Climatic Withstand                    | IACS E10   |
|---------------------------------------|--|
| Ip Degree Of Protection               | IP20 conforming to IEC 60529   |
| Ambient Air Temperature For Operation | -4140 °F (-2060 °C) without derating IEC 60947-4-1   |
| Ambient Air Temperature For Storage   | -76158 °F (-6070 °C)   |
| Mechanical Robustness                 | Shocks15 Gn for 11 ms IEC 60068-2-7<br>Vibrations3 GN IEC 60068-2-6  |
| Dielectric Strength                   | 1.89 kV 50 Hz IEC 60947-1  |
| Standards                             | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>UL 60947-5-1<br>CSA C22.2 No 60947-4-1<br>CSA C22.2 No 60947-5-1<br>EN 50495 |
| Product Certifications                | IEC UL CSA EAC ABS ATEX INERIS UKCA  |

# Ordering and shipping details

| Category          | US10I1222347  |
|-------------------|---------------|
| Discount Schedule | 0112          |
| Gtin              | 3606480609626 |
| Returnability     | Yes           |
| Country Of Origin | TH            |

## **Packing Units**

| Unit Type Of Package 1       | PCE              |
|------------------------------|------------------|
| Number Of Units In Package 1 | 1                |
| Package 1 Height             | 3.27 in (8.3 cm) |
| Package 1 Width              | 2.83 in (7.2 cm) |

| Package 1 Length             | 1.77 in (4.5 cm)          |
|------------------------------|---------------------------|
| Package 1 Weight             | 6.35 oz (180.0 g)         |
| Unit Type Of Package 2       | S02                       |
| Number Of Units In Package 2 | 24                        |
| Package 2 Height             | 5.91 in (15.0 cm)         |
| Package 2 Width              | 11.81 in (30.0 cm)        |
| Package 2 Length             | 15.75 in (40.0 cm)        |
| Package 2 Weight             | 10.35 lb(US) (4.693 kg)   |
| Unit Type Of Package 3       | P12                       |
| Number Of Units In Package 3 | 768                       |
| Package 3 Height             | 31.50 in (80.0 cm)        |
| Package 3 Width              | 29.53 in (75.0 cm)        |
| Package 3 Length             | 47.24 in (120.0 cm)       |
| Package 3 Weight             | 245.51 lb(US) (111.36 kg) |

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

|          | Toxic Heavy Metal Free     |     |
|----------|----------------------------|-----|
|          | Mercury Free               |     |
| <b>②</b> | Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant   |
|                           | EU RoHS Declaration   |
| China Rohs Regulation     | China RoHS declaration  |
|                           | Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |

Jun 6, 2024