## Product data sheet

Specifications





# TeSys Deca thermal overload relays , 95...120A , class 10A

LRD4367

Product availability: Stock - Normally stocked in distribution facility

#### Price\*: 362.00 USD

#### Main

Range	TeSys	
Product Name	TeSys LRD TeSys Deca	
Product Or Component Type	Differential thermal overload relay	
Device Short Name	LRD	
Relay Application	Motor protection	
Product Compatibility	LC1D150 LC1D115	
Network Type	AC DC	
Thermal Overload Class	Class 10A IEC 60947-4-1	
Thermal Protection Adjustment Range	95120 A	
[Ui] Rated Insulation Voltage	Power circuit 1000 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL	

#### Complementary

Network Frequency	0400 Hz	
Mounting Support	Plate, with specific accessories Rail, with specific accessories Under contactor	
Tripping Threshold	1.14 +/- 0.06 lr IEC 60947-4-1	
Auxiliary Contact Composition	1 NO + 1 NC	
[Ith] Conventional Free Air Thermal Current	5 A signalling circuit	
Permissible Current	0.06 A 440 V DC-13 signalling circuit 0.12 A 600 V AC-15 signalling circuit	
[Ue] Rated Operational Voltage	1000 V AC 0400 Hz power circuit IEC 60947-4-1	
Associated Fuse Rating	4 A gG for signalling circuit 4 A BS for signalling circuit	
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947-1	
Phase Failure Sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0	
Control Type	Red push-button stop Blue push-button reset	
Temperature Compensation	-4140 °F (-2060 °C)	

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Connections - Terminals	Power circuit screw clamp terminals 1 0.010.05 in <sup>2</sup> (435 mm <sup>2</sup> ) flexible with cable end	
	Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible without cable end	
	Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible with cable end	
	Control circuit screw clamp terminals 2 0.000.00 in <sup>2</sup> (12.5 mm <sup>2</sup> ) solid without cable end	
	Power circuit screw clamp terminals 1 0.010.08 in <sup>2</sup> (450 mm <sup>2</sup> ) flexible without cable end	
	Power circuit screw clamp terminals 1 0.010.08 in <sup>2</sup> (450 mm <sup>2</sup> ) solid without cable end	
Tightening Torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 79.66 lbf.in (9 N.m) screw clamp terminals	
Depth	5.20 in (132 mm)	
Net Weight	1.98 lb(US) (0.9 kg)	

### Environment

Climatic Withstand	IACS E10	
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Ambient Air Temperature For Operation	-4140 °F (-2060 °C) without derating IEC 60947-4-1	
Ambient Air Temperature For Storage	-76158 °F (-6070 °C)	
Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations6 Gn IEC 60068-2-6 Shocks15 Gn for 11 ms IEC 60068-2-7	
Dielectric Strength	2.2 kV 50 Hz IEC 60947-1	
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495	
Product Certifications	IEC UL CSA CCC EAC ATEX INERIS	

## Ordering and shipping details

Category	US10I1222347	
Discount Schedule	0112	
Gtin	3389110523348	
Returnability	Yes	
Country Of Origin	FR	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.98 in (15.2 cm)
Package 1 Width	5.43 in (13.8 cm)

4.02 in (10.2 cm)	
29.42 oz (834.0 g)	
S03	
10	
11.81 in (30.0 cm)	
11.81 in (30.0 cm)	
15.75 in (40.0 cm)	
19.49 lb(US) (8.84 kg)	
P06	
80	
30.31 in (77.0 cm)	
31.50 in (80.0 cm)	
23.62 in (60.0 cm)	
174.65 lb(US) (79.22 kg)	

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov