



Motor controller, TeSys T, Motor Management, Profibus DP, 6 logic inputs, 3 relay logic outputs, 1.35 to 27A, 24VDC

LTMR27PBD

Main

Range	TeSys	
Product name	TeSys T	
Device short name	LTMR	
product or component type Motor controller		
Device application	Equipment monitoring and control	
measurement current	1.3527 A	
[Us] rated supply voltage	24 V DC	
Current consumption	56127 mA	
Supply voltage limits	20.426.24 V DC	
Communication port protocol	ation port protocol Profibus DP	
Bus type	Profibus DP polarised 2-wire RS485 interface, addressing 1125, transmission rate 9.6 kbit/s12 Mbit/s, SUB-D 9 with 2 shielded twisted pairs, type A Profibus DP polarised 2-wire RS485 interface, addressing 1125, transmission rate 9.6 kbit/s12 Mbit/s, terminal block with 2 shielded twisted pairs, type A	

Complementary

<u>.</u>		
[Ui] rated insulation voltage	690 V conforming to EN/IEC 60947-1 690 V conforming to CSA C22.2 No 14 690 V conforming to UL 508	
[Uimp] rated impulse withstand voltage	6 kV current or voltage measurement circuit conforming to EN/IEC 60947-4-1 0.8 kV communication circuit conforming to EN/IEC 60947-4-1 0.8 kV supply, inputs and outputs conforming to EN/IEC 60947-4-1	
Short-circuit withstand	100 kA conforming to EN/IEC 60947-4-1	
Associated fuse rating	4 A gG for output 0.5 A gG for control circuit	
Protection type	Overload Thermal protection Power factor variation Overload (long time) Phase failure Load fluctuation Phase unbalance Locked rotor Earth-leakage protection Thermal overload protection Reverse polarity protection	

Starting current and time
Fault recording Remaining operating time before overload tripping
Motor control command recording
Running hours counter/operating time
Trip context information
Trip history information
Phase fault and earth fault trip counters
Event recording Waiting time after overload tripping
6
7 mA
Logic input: < 5 V and <= 15 mA for 5 ms
Logic input: < 15 V and 215 mA for 15 ms
2 Hz
5 A at 250 V AC for logic output
5 A at 30 V DC for logic output
480 VA (AC-15), le = 2 A, 500000 cycles (output)
30 W (DC-13), le = 1.25 A, 500000 cycles (output)
1800 cyc/h
1 NO + 1 NC fault signal 3 NO
Average current lavg
Temperature
Imbalance current Phase current I1, I2, I3 RMS
Earth-fault current
515 % earth fault current internal measurement
1 % voltage (100830 V)
3 % power factor
5 % earth fault current external measurement +/- 30 min/year internal clock
0,02 temperature
1 % current
5 % active and reactive power
III
5.08 mm
Control circuit: connector 1 cable(s) 0.252.5 mm² (AWG 24AWG 14) flexible with
cable end Control circuit: connector 1 cable(s) 0.22.5 mm² (AWG 24AWG 14) flexible
without cable end
Control circuit: connector 1 cable(s) 0.252.5 mm² (AWG 24AWG 14) flexible
without cable end
Control circuit: connector 1 cable(s) 0.22.5 mm² (AWG 24AWG 14) solid without
cable end
Control circuit: connector 2 cable(s) 0.21 mm² (AWG 24AWG 14) flexible with cable end
Control circuit: connector 2 cable(s) 0.21.5 mm² (AWG 24AWG 14) flexible
without cable end Control circuit: connector 2 cable(s) 0.51.5 mm² (AWG 24AWG 14) flexible
without cable end Control circuit: connector 2 cable(s) 0.21 mm² (AWG 24AWG 14) solid without
Control of Care Control Contro
cable end
**

Electromagnetic compatibility	Electrostatic discharge, 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, 3, 10 V/m, conforming to EN/IEC 61000-4-3
	Fast transients immunity test (other circuits), level 3, 2 kV, conforming to EN/IEC 61000-4-4
	Fast transients immunity test (on supply and relay outputs), level 4, 4 kV, conforming
	to EN/IEC 61000-4-4 Voltage dips and interruptions immunity test, 70 %, 500 ms, conforming to EN/IEC
	61000-4-11
	Conducted RF disturbances, 10 V, conforming to EN/IEC 61000-4-6
	Temperature sensor: surges (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5 Temperature sensor: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5
	Control circuit: surges (serial mode), 1 kV, conforming to EN/IEC 61000-4-5
	Control circuit: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5
	Communication: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
	Relay outputs and supply: surges (serial mode), 2 kV, conforming to EN/IEC 61000-4-5
	Relay outputs and supply: surges (common mode), 4 kV, conforming to EN/IEC
	61000-4-5
Width	91 mm
Height	61 mm
Depth	122.5 mm
net weight	0.53 kg
Web services	Web server
Compatibility code	LTMR
Environment	
Standards	UL 508
	IACS E10
	EN 60947-4-1 IEC 60947-4-1
	CSA C22.2 No 14
Product certifications	C-Tick
	CCC
	ABS
	NOM
	LROS (Lloyds register of shipping)
	EAC RINA
	ATEX
	GL
	KERI
	DNV UL
	CSA
	RMRoS
	BV
Protective treatment	12 x 24 hour cycles conforming to EN/IEC 60068-2-30
	48 h conforming to EN/IEC 60070-2-11
	TH conforming to EN/IEC 60068
Fire resistance	650 °C conforming to EN/IEC 60695-2-12 960 °C conforming to UL 94
Ambient air temperature for operation	-2060 °C
ambient air temperature for storage	-4080 °C
Operating altitude	<= 2000 m without derating
Mechanical robustness	Vibrations mounted on symmetrical rail: 1 Gn, 5300 Hz conforming to EN/IEC
	60068-2-6
	Vibrations plate mounted: 4 Gn, 5300 Hz conforming to EN/IEC 60068-2-6 Shocks half sine wave acceleration: 15 Gn for 11 ms conforming to EN/IEC 60068-2-27

Packing Units

IP degree of protection

IP20

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	10.0 cm
Package 1 Length	13.6 cm
Package 1 Weight	514.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.485 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Halogen Free Plastic Parts Product	
⊘	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information