# Product data sheet

Specifications





# Standard control unit, TeSys Ultra, 3A to 12A, class 10, 24VDC

LUCA12BL

Product availability: Stock - Normally stocked in distribution facility

Price\*: 120.00 USD

#### Main

| IVIAIII                              |  |
|--------------------------------------|--|
| Range                                | TeSys  |
| Range Of Product                     | TeSys Ultra  |
| Product Name                         | TeSys Ultra  |
| Device Short Name                    | LUCA   |
| Product Or Component Type            | Standard control unit  |
| Device Application                   | Motor control Motor protection   |
| Product Specific Application         | Basic protection requirements for motor starters: overload and short-circuit   |
| Main Function Available              | Earth fault protection Protection against overload and short-circuit Protection against phase failure and phase imbalance Manual reset   |
| Product Compatibility                | Power base LUB12 Power base LUB38 Power base LUB120 Power base LUB320 Power base LUB320 Power base LUB380 Reversing contactor breaker LU2B12BL Reversing contactor breaker LU2B32BL Reversing contactor breaker LU2B38BL |
| [Ue] Rated Operational Voltage       | 690 V AC   |
| Network Frequency                    | 4060 Hz  |
| Load Type                            | 3-phase motor self-cooled  |
| Utilisation Category                 | AC-43<br>AC-44<br>AC-41  |
| Motor Power Kw                       | 5.5 kW 400440 V AC 50/60 Hz<br>5.5 kW 500 V AC 50/60 Hz<br>9 kW 690 V AC 50/60 Hz  |
| Rated Motor Current Adjustment Range | 312 A  |
| Thermal Overload Class               | Class 10 4060 Hz -13158 °F (-2570 °C) IEC 60947-6-2<br>Class 10 4060 Hz -13158 °F (-2570 °C) UL 508  |
| Tripping Threshold                   | 14.2 x lr +/- 20 %   |
| Phase Failure Sensitivity            | Yes  |
| [Uc] Control Circuit Voltage         | 24 V DC  |

## Complementary

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Control Circuit Voltage Limits           | 2027 V DC 24 V in operation<br>14.5 V DC 24 V drop-out   |
|--|--|
| Typical Current Consumption              | 130 mA 24 V DC I maximum while closing with LUB12 220 mA 24 V DC I maximum while closing with LUB32 220 mA 24 V DC I maximum while closing with LUB38 60 mA 24 V DC I rms sealed with LUB12 80 mA 24 V DC I rms sealed with LUB32 80 mA 24 V DC I rms sealed with LUB38                        |
| Heat Dissipation                         | 2 W control circuit with LUB12<br>3 W control circuit with LUB32<br>3 W control circuit with LUB38   |
| Operating Time                           | 35 ms opening with LUB12 control circuit 35 ms opening with LUB32 control circuit 35 ms opening with LUB38 control circuit 70 ms closing with LUB12 control circuit 70 ms closing with LUB32 control circuit 70 ms closing with LUB32 control circuit 70 ms closing with LUB38 control circuit |
| Standards                                | EN 60947-6-2<br>IEC 60947-6-2<br>UL 60947-4-1, with phase barrier<br>CSA C22.2 No 60947-4-1, with phase barrier  |
| Product Certifications                   | CE UL CSA CCC EAC ASEFA ATEX Marine  |
| [Ui] Rated Insulation Voltage            | 690 V IEC 60947-6-2<br>600 V UL 60947-4-1<br>600 V CSA C22.2 No 60947-4-1  |
| [Uimp] Rated Impulse Withstand Voltage   | 6 kV IEC 60947-6-2   |
| Safe Separation Of Circuit               | 400 V SELV between the control and auxiliary circuits IEC 60947-1 400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1   |
| Fixing Mode                              | Plug-in (front face)   |
| Width                                    | 1.77 in (45 mm)  |
| Height                                   | 2.60 in (66 mm)  |
| Depth                                    | 2.36 in (60 mm)  |
| Net Weight                               | 0.30 lb(US) (0.135 kg)   |
| Compatibility Code                       | LUCA   |
| Environment                              |  |
| Ip Degree Of Protection                  | IP20 front panel and wired terminals IEC 60947-1 IP20 other faces IEC 60947-1 IP40 front panel outside connection zone IEC 60947-1   |
| Protective Treatment                     | TH IEC 60068   |
| Ambient Air Temperature For<br>Operation | -13158 °F (-2570 °C)   |
| Ambient Air Temperature For Storage      | -40185 °F (-4085 °C)   |
| Operating Altitude                       | 6561.68 ft (2000 m)  |
| Fire Resistance                          | 1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12   |
| Shock Resistance                         | 10 gn power poles open IEC 60068-2-27<br>15 gn power poles closed IEC 60068-2-27   |
|  |  |

2 gn 5...300 Hz power poles open IEC 60068-2-6 4 gn 5...300 Hz power poles closed IEC 60068-2-6

Vibration Resistance

| Resistance To Electrostatic Discharge | 8 kV 3 in open air IEC 61000-4-2<br>8 kV 4 on contact IEC 61000-4-2                          |
|---------------------------------------|--|
| Resistance To Radiated Fields         | 9.14 V/m (10 V/m) 3 IEC 61000-4-3  |
| Resistance To Fast Transients         | 2 kV 3 serial link IEC 61000-4-4<br>4 kV 4 all circuits except for serial link IEC 61000-4-4 |
| Immunity To Radioelectric Fields      | 10 V IEC 61000-4-6   |
| Immunity To Microbreaks               | 3 ms   |
| Immunity To Voltage Dips              | 70 % / 500 ms IEC 61000-4-11   |

## Ordering and shipping details

| Category          | US10I1122397  |  |
|-------------------|---------------|--|
| Discount Schedule | 0111          |  |
| Gtin              | 3389110363845 |  |
| Returnability     | Yes           |  |
| Country Of Origin | FR            |  |

## **Packing Units**

| Unit Type Of Package 1       | PCE                    |
|------------------------------|------------------------|
| Number Of Units In Package 1 | 1                      |
| Package 1 Height             | 2.13 in (5.4 cm)       |
| Package 1 Width              | 3.15 in (8.0 cm)       |
| Package 1 Length             | 4.02 in (10.2 cm)      |
| Package 1 Weight             | 4.27 oz (121.0 g)      |
| Unit Type Of Package 2       | S02                    |
| Number Of Units In Package 2 | 23                     |
| Package 2 Height             | 5.91 in (15.0 cm)      |
| Package 2 Width              | 11.81 in (30.0 cm)     |
| Package 2 Length             | 15.75 in (40.0 cm)     |
| Package 2 Weight             | 6.81 lb(US) (3.088 kg) |

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

| <b>Ø</b> | Mercury Free                       |
|----------|------------------------------------|
| <b>Ø</b> | Rohs Exemption Information Yes     |
| <b>Ø</b> | Pvc Free                           |
| <b>②</b> | Halogen Free Plastic Parts Product |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant with Exemptions  |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.                         |
| Environmental Disclosure | Product Environmental Profile  |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile      | End of Life Information  |