



advanced control unit LUCC class 10 - 3...12 A - 24 V AC

LUCC12B

Main

Main		
Range	TeSys	
Range of product	TeSys Ultra	
Product name	TeSys Ultra	
Device short name	LUCC	
Product or component type	pe Advanced control unit	
Device application	Motor control Motor protection	
Product specific application	Basic protection and advanced functions, communication	
main function available	Manual reset Protection against overload and short-circuit Protection against phase failure and phase imbalance Earth fault protection	
Product compatibility	Power base LUB12 Power base LUB32 Power base LUB38 Power base LUB120 Power base LUB320 Power base LUB380 Reversing contactor breaker LU2B12B Reversing contactor breaker LU2B32B	
[Ue] rated operational voltage	690 V AC	
Network frequency	4060 Hz	
Load type	Single-phase motor	
Utilisation category	AC-41 AC-43 AC-44	
Motor power kW	2.2 kW at 400440 V AC 50/60 Hz for 1 phase motors	
rated motor current adjustment range	312 A	
Thermal overload class	Class 10 - frequency limit: 4060 Hz - temperature compensation: -2555 °C conforming to IEC 60947-6-2 Class 10 - frequency limit: 4060 Hz - temperature compensation: -2555 °C conforming to UL 508	
Tripping threshold	14.2 x lr +/- 20 %	
[Uc] control circuit voltage	24 V AC	

Complementary

Control circuit voltage limits 20...26.5 V for AC circuit 24 V in operation

14.5 V for AC circuit 24 V drop-out

Typical current consumption	140 mA at 24 V AC I maximum while closing with LUB12 220 mA at 24 V AC I maximum while closing with LUB32 220 mA at 24 V AC I maximum while closing with LUB38 70 mA at 24 V AC I rms sealed with LUB12 90 mA at 24 V AC I rms sealed with LUB32 90 mA at 24 V AC I rms sealed with LUB38	
Heat dissipation	2 W for control circuit with LUB12 3 W for control circuit with LUB32 3 W for control circuit with LUB38	
Operating time	35 ms opening with LUB12 for control circuit 35 ms opening with LUB32 for control circuit 35 ms opening with LUB38 for control circuit 70 ms closing with LUB12 for control circuit 70 ms closing with LUB32 for control circuit 70 ms closing with LUB38 for control circuit	
Reset	Manual reset	
Standards	EN 60947-6-2 IEC 60947-6-2 UL 60947-4-1, with phase barrier CSA C22.2 No 60947-4-1, with phase barrier	
Product certifications	CE UL CSA CCC EAC ASEFA ATEX Marine	
[Ui] rated insulation voltage	690 V conforming to IEC 60947-6-2 600 V conforming to UL 60947-4-1 600 V conforming to CSA C22.2 No 60947-4-1	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-6-2	
Safe separation of circuit	400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1 400 V SELV between the control or auxiliary circuit and the main circuit conforming to IEC 60947-1	
Fixing mode	Plug-in (front face)	
Width	45 mm	
Height	66 mm	
Depth	60 mm	
Compatibility code	LUCC	
Environment		
IP degree of protection	IP20 front panel and wired terminals conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1 IP40 front panel outside connection zone conforming to IEC 60947-1	
Protective treatment	TH conforming to IEC 60068	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Operating altitude	2000 m	
Fire resistance	960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12	
Shock resistance	10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27	

Vibration resistance

2 gn, 5...300 Hz, power poles open conforming to IEC 60068-2-6 4 gn, 5...300 Hz, power poles closed conforming to IEC 60068-2-6

Resistance to electrostatic discharge	8 kV level 3 in open air conforming to IEC 61000-4-2 8 kV level 4 on contact conforming to IEC 61000-4-2	
Non-dissipating shock wave	1 kV serial mode conforming to IEC 60947-6-2 2 kV common mode conforming to IEC 60947-6-2	
Resistance to radiated fields	10 V/m 3 conforming to IEC 61000-4-3	
Resistance to fast transients	2 kV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4	
Immunity to radioelectric fields	10 V conforming to IEC 61000-4-6	
Immunity to microbreaks	3 ms	
Immunity to voltage dips	70 % / 500 ms conforming to IEC 61000-4-11	

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	8.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	131.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	23
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.439 kg

Contractual warranty

Warranty 12 months

Sustainability Screen Premium*

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free
	Rohs Exemption Information Yes
⊘	Pvc Free
	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

5 Aug 2024