Product datasheet

Specification





Advanced control unit, TeSys Ultra, 1P, 4.5 to 18A, protection & diagnostic, class 10, 24VDC coil

LUCC18BL

Main

Mani	
Range	TeSys
Range of product	TeSys Ultra
Product name	TeSys Ultra
Device short name	LUCC
Product or component type	Advanced control unit
Device application	Motor control Motor protection
Product specific application	Basic protection and advanced functions, communication
main function available	Manual reset Earth fault protection Protection against phase failure and phase imbalance Protection against overload and short-circuit
Product compatibility	Power base LUB32 Power base LUB38 Power base LUB320 Power base LUB380 Reversing contactor breaker LU2B32BL Reversing contactor breaker LU2B38BL
[Ue] rated operational voltage	690 V AC
Network frequency	4060 Hz
Load type	Single-phase motor
Utilisation category	AC-44 AC-43 AC-41
Motor power kW	4 kW at 400440 V AC 50/60 Hz for 1 phase motors
rated motor current adjustment range	4.518 A
Thermal overload class	Class 10 - frequency limit: 4060 Hz - temperature compensation: -2555 °C conforming to IEC 60947-6-2 Class 10 - frequency limit: 4060 Hz - temperature compensation: -2555 °C conforming to UL 508
Tripping threshold	14.2 x lr +/- 20 %
[Uc] control circuit voltage	24 V DC

Complementary

2027 V for DC circuit 24 V in operation 14.5 V for DC circuit 24 V drop-out	
220 mA at 24 V DC I maximum while closing with LUB32	
80 mA at 24 V DC I rms sealed with LUB32	
	14.5 V for DC circuit 24 V drop-out 220 mA at 24 V DC I maximum while closing with LUB32 220 mA at 24 V DC I maximum while closing with LUB38

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

5 Aug 2024 Life Is On Schneider 1

Heat dissipation	3 W for control circuit with LUR22	
πεαι αισσιματίστι	3 W for control circuit with LUB32 3 W for control circuit with LUB38	
	3 VV TOT CONTROL CITCUIT WITH LODGE	
Operating time	35 ms opening with LUB32 for control circuit	
	35 ms opening with LUB38 for control circuit	
	70 ms closing with LUB32 for control circuit	
	70 ms closing with LUB38 for control circuit	
Reset	Manual reset	
Standards	EN 60947-6-2	
	IEC 60947-6-2	
	UL 60947-4-1, with phase barrier	
	CSA C22.2 No 60947-4-1, with phase barrier	
Product certifications	CE	
	UL	
	CSA	
	CCC	
	EAC	
	ASEFA	
	ATEX	
	Marine	
	wante	
[Ui] rated insulation voltage	690 V conforming to IEC 60947-6-2	
	600 V conforming to UL 60947-4-1	
	600 V conforming to CSA C22.2 No 60947-4-1	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-6-2	
Safe separation of circuit	400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1	
	400 V SELV between the control or auxiliary circuit and the main circuit conforming to	
	IEC 60947-1	
Fixing mode	Plug-in (front face)	
Width	45 mm	
Height	66 mm	
Depth	60 mm	
Compatibility code	LUCC	
Environment		
IP degree of protection	IP20 front panel and wired terminals conforming to IEC 60947-1	
3 ,	IP20 other faces conforming to IEC 60947-1	
	ID40 front panel outside connection zone conforming to IEC 60047.1	

IP degree of protection	IP20 front panel and wired terminals conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1 IP40 front panel outside connection zone conforming to IEC 60947-1	
Protective treatment	TH conforming to IEC 60068	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Operating altitude	2000 m	
Fire resistance	960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12	
Shock resistance	10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27	
Vibration resistance	2 gn, 5300 Hz, power poles open conforming to IEC 60068-2-6 4 gn, 5300 Hz, power poles closed conforming to IEC 60068-2-6	
Resistance to electrostatic discharge	8 kV level 3 in open air conforming to IEC 61000-4-2 8 kV level 4 on contact conforming to IEC 61000-4-2	
Resistance to radiated fields	10 V/m 3 conforming to IEC 61000-4-3	
Resistance to fast transients	2 kV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4	
Immunity to radioelectric fields	10 V conforming to IEC 61000-4-6	
Immunity to microbreaks	3 ms	

Immunity to voltage dips 70 % / 500 ms conforming to IEC 61000-4-11

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	8.100 cm
Package 1 Length	8.700 cm
Package 1 Weight	123.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	23
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.124 kg

Contractual warranty

Warranty 18 months

Sustainability Screen Premium*

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free
	Rohs Exemption Information Yes
⊘	Pvc Free
	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

5 Aug 2024