Product data sheet

Specifications





Advanced control unit, TeSys Ultra, 8A to 32A, 1P motors, protection & diagnostic, class 10, coil 110-240VAC/DC

LUCC32FU

Product availability: Stock - Normally stocked in distribution facility

Price*: 150.00 USD

Main

Range	TeSys	
Range Of Product	TeSys Ultra	
Product Name	TeSys Ultra	
Device Short Name	LUCC	
Product Or Component Type	Advanced control unit	
Device Application	Motor control Motor protection	
Product Specific Application	Basic protection and advanced functions, communication	
Main Function Available	Protection against overload and short-circuit Protection against phase failure and phase imbalance Manual reset Earth fault protection	
Product Compatibility	Power base LUB32 Power base LUB38 Power base LUB320 Power base LUB380 Reversing contactor breaker LU2B32FU Reversing contactor breaker LU2B38FU	
[Ue] Rated Operational Voltage	690 V AC	
Network Frequency	4060 Hz	
Load Type	Single-phase motor	
Utilisation Category	AC-44 AC-43 AC-41	
Motor Power Kw	7.5 kW 400440 V AC 50/60 Hz 1 phase	
Rated Motor Current Adjustment Range	832 A	
Thermal Overload Class	Class 10 4060 Hz -13131 °F (-2555 °C) IEC 60947-6-2 Class 10 4060 Hz -13131 °F (-2555 °C) UL 508	
Tripping Threshold	14.2 x lr +/- 20 %	
[Uc] Control Circuit Voltage	110240 V AC 110220 V DC	

Complementary

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Control Circuit Voltage Limits	88264 V AC 110240 V in operation
	88242 V DC 110220 V in operation
	55 V AC 110240 V drop-out 55 V DC 110220 V drop-out
	33 V DC 110220 V drop-out
Typical Current Consumption	280 mA 110240 V AC I maximum while closing with LUB32
	280 mA 110240 V AC I maximum while closing with LUB38
	280 mA 110220 V DC I maximum while closing with LUB32 280 mA 110220 V DC I maximum while closing with LUB38
	25 mA 110240 V AC I rms sealed with LUB32
	25 mA 110240 V AC I rms sealed with LUB38
	25 mA 110220 V DC I rms sealed with LUB32
	25 mA 110220 V DC I rms sealed with LUB38
Heat Dissipation	3 W control circuit with LUB32
·	3 W control circuit with LUB38
Operating Time	35 ms opening with LUB32 control circuit
	35 ms opening with LUB38 control circuit
	50 ms closing with LUB32 control circuit
	50 ms closing with LUB38 control circuit
Reset	Manual reset
	EN 60947-6-2
	IEC 60947-6-2
	UL 60947-4-1, with phase barrier
	CSA C22.2 No 60947-4-1, with phase barrier
Product Certifications	CE
	UL
	CSA
	CCC EAC
	ASEFA
	ATEX
	Marine
[Ui] Rated Insulation Voltage	690 V IEC 60947-6-2
[e.]a.eaea.a.e ve.a.ge	600 V UL 60947-4-1
	600 V CSA C22.2 No 60947-4-1
[Uimp] Rated Impulse Withstand Voltage	6 kV IEC 60947-6-2
Safe Separation Of Circuit	400 V SELV between the control and auxiliary circuits IEC 60947-1
	400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1
Fixing Mode	Plug-in (front face)
Width	1.77 in (45 mm)
Height	2.60 in (66 mm)
Depth	2.36 in (60 mm)
Compatibility Code	LUCC
Environment	
Ip Degree Of Protection	IP20 front panel and wired terminals IEC 60947-1
. · ·	IP20 other faces IEC 60947-1 IP40 front panel outside connection zone IEC 60947-1
Protective Treatment	TH IEC 60068
Ambient Air Temperature For	
Operation	-13158 °F (-2570 °C)
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)
Operating Altitude	6561.68 ft (2000 m)
Fire Resistance	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12
	(000 0) 120 00000 2 12
Shock Resistance	10 gn power poles open IEC 60068-2-27
	15 gn power poles closed IEC 60068-2-27

Vibration Resistance	2 gn 5300 Hz power poles open IEC 60068-2-6 4 gn 5300 Hz power poles closed IEC 60068-2-6
Resistance To Electrostatic Discharge	8 kV 3 in open air IEC 61000-4-2 8 kV 4 on contact IEC 61000-4-2
Non-Dissipating Shock Wave	1 kV serial mode IEC 60947-6-2 2 kV common mode IEC 60947-6-2
Resistance To Radiated Fields	9.14 V/m (10 V/m) 3 IEC 61000-4-3
Resistance To Fast Transients	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
Immunity To Radioelectric Fields	10 V IEC 61000-4-6
Immunity To Microbreaks	3 ms
Immunity To Voltage Dips	70 % / 500 ms IEC 61000-4-11

Ordering and shipping details

Category	US10I1122397
Discount Schedule	0144
Discount Schedule	0111
Gtin	3389110364781
Returnability	Yes
Country Of Origin	FR

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.97 in (5.0 cm)
Package 1 Width	3.19 in (8.1 cm)
Package 1 Length	3.43 in (8.7 cm)
Package 1 Weight	4.48 oz (127.0 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	23
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	7.27 lb(US) (3.298 kg)

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free
Ø	Rohs Exemption Information Yes
Ø	Pvc Free
Ø	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information