# **Product data sheet**

Specification





Advanced control unit, TeSys Ultra, 8A to 32A, 3P motors, protection & diagnostic, class 20, coil 110-240VAC/DC

LUCD32FU

Product availability: Stock - Normally stocked in distribution facility

Price\*: 150.00 USD

#### Main

Range	TeSys
Range of Product	TeSys Ultra
Product name	TeSys Ultra
Device short name	LUCD
Product or Component Type	Advanced control unit
Device Application	Motor control Motor protection
Product Specific Application	Basic protection and advanced functions, communication
main function available	Protection against overload and short-circuit Manual reset Protection against phase failure and phase imbalance Earth fault protection
Product compatibility	Power base LUB32 Power base LUB38 Power base LUB320 Power base LUB380 Reversing contactor breaker LU2B32FU Reversing contactor breaker LU2B38FU
[Ue] rated operational voltage	690 V AC
Network frequency	4060 Hz
Load type	3-phase motor self-cooled
Utilisation category	AC-44 AC-41 AC-43
Motor power kW	15 kW 400440 V AC 50/60 Hz 15 kW 500 V AC 50/60 Hz 18.5 kW 690 V AC 50/60 Hz
rated motor current adjustment range	832 A
Thermal overload class	Class 20 4060 Hz -13158 °F (-2570 °C) IEC 60947-6-2 Class 20 4060 Hz -13158 °F (-2570 °C) UL 508
Tripping threshold	14.2 x lr +/- 20 %
Phase failure sensitivity	Yes
[Uc] control circuit voltage	110240 V AC 110220 V DC

### **Complementary**

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Control circuit voltage limits	88264 V AC 110240 V in operation 88242 V DC 110220 V in operation
	55 V AC 110240 V drop-out
	55 V DC 110220 V drop-out
Typical current consumption	280 mA 110240 V AC I maximum while closing with LUB32
. Jprod. current concumpation	280 mA 110240 V AC I maximum while closing with LUB38
	280 mA 110220 V DC I maximum while closing with LUB32
	280 mA 110220 V DC I maximum while closing with LUB38
	25 mA 110240 V AC I rms sealed with LUB32
	25 mA 110240 V AC I rms sealed with LUB38
	25 mA 110220 V DC I rms sealed with LUB32
	25 mA 110220 V DC I rms sealed with LUB38
Heat dissipation	3 W control circuit with LUB32 3 W control circuit with LUB38
Operating time	25 are against with LLIP22 control size of
Operating time	35 ms opening with LUB32 control circuit 35 ms opening with LUB38 control circuit
	50 ms closing with LUB32 control circuit
	50 ms closing with LUB38 control circuit
Reset	Manual reset
 Standards	EN 60947-6-2
	IEC 60947-6-2
	UL 60947-4-1, with phase barrier
	CSA C22.2 No 60947-4-1, with phase barrier
Product Certifications	CE
	UL
	CSA
	CCC
	EAC
	ASEFA
	ATEX
	Marine
[Ui] rated insulation voltage	690 V IEC 60947-6-2
	600 V UL 60947-4-1
	600 V CSA C22.2 No 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-6-2
Safe separation of circuit	400 V SELV between the control and auxiliary circuits IEC 60947-1 400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1
Fixing mode	Plug-in (front face)
Width	1.8 in (45 mm)
Height	2.6 in (66 mm)
Depth	2.4 in (60 mm)
Compatibility code	LUCD
Environment	
IP degree of protection	IP20 front panel and wired terminals IEC 60947-1
·	IP20 other faces IEC 60947-1 IP40 front panel outside connection zone IEC 60947-1
Protective treatment	TH IEC 60068
Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)
Operating altitude	6561.68 ft (2000 m)
Fire resistance	1760 °F (960 °C) parts supporting live components IEC 60695-2-12
	1202 °F (650 °C) IEC 60695-2-12
Shock resistance	10 gn power poles open IEC 60068-2-27
	15 gn power poles closed IEC 60068-2-27

Vibration resistance	2 gn 5300 Hz power poles open IEC 60068-2-6 4 gn 5300 Hz power poles closed IEC 60068-2-6
Resistance to electrostatic discharge	8 kV 3 in open air IEC 61000-4-2 8 kV 4 on contact IEC 61000-4-2
Non-dissipating shock wave	1 kV serial mode IEC 60947-6-2 2 kV common mode IEC 60947-6-2
Resistance to radiated fields	9.1 V/m (10 V/m) 3 IEC 61000-4-3
Resistance to fast transients	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
Immunity to radioelectric fields	10 V IEC 61000-4-6
Immunity to microbreaks	3 ms
Immunity to voltage dips	70 % / 500 ms IEC 61000-4-11

## Ordering and shipping details

Category	US10I1122397
<u> </u>	
Discount Schedule	0111
GTIN	3389110365078
Returnability	Yes
Country of origin	FR

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.02 in (10.2 cm)
Package 1 Width	2.2 in (5.5 cm)
Package 1 Length	3.1 in (8.0 cm)
Package 1 Weight	4.5 oz (127.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	23
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	7.134 lb(US) (3.236 kg)

### **Contractual warranty**

Warranty 18 months

### Sustainability Green Premium\*

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Mercury Free
	Rohs Exemption Information Yes
<b>⊘</b>	Pvc Free
	Halogen Free Plastic Parts Product

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information

Aug 9, 2024