

Communication gateway, TeSys Ultra, 24VDC +/- 10%, 1Profibus DP SUB-D9, 1 RJ45 Modbus

LUFP7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1,490.00 USD

Main

| Range | TeSys | |
|---------------------------|-----------------------------------------|--|
| Device short name | LUF | |
| Product or Component Type | Communication gateway | |
| Product Compatibility | ATV31 ATS48 TeSys U starter-controllers | |

Complementary

| Bus type | Profibus DP Modbus |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector type | Female SUB-D 9 field bus RJ45 Modbus RJ45 to a PC |
| Maximum number of connections | <= 8 Modbus slaves |
| [Us] rated supply voltage | 24 V DC +/- 10 % |
| Current consumption | 100 mA typical 280 mA maximum |
| Local signalling | LED front panel |
| Services | Command Profibus DP 122 configurable words Configuration and adjustment Fipio by gateway mini messaging facility Monitoring Profibus DP 122 configurable words |
| Net Weight | 0.540 lb(US) (0.245 kg) |

Environment

| Electromagnetic compatibility | Electromagnetic emission IEC 50081-2 Electromagnetic immunity IEC 61000-6-2 |
|------------------------------------------|--------------------------------------------------------------------------------|
| Pollution degree | 2 IEC 60664 |
| Ambient air temperature for installation | 41122 °F (550 °C) |
| IP Degree of Protection | IP20 |

Ordering and shipping details

| Category | US10I1122398 |
|-------------------|---------------|
| Discount Schedule | 0111 |
| GTIN | 3389110109368 |
| Returnability | No |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin SE

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|--------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.772 in (17.200 cm) |
| Package 1 Width | 5.394 in (13.700 cm) |
| Package 1 Length | 2.283 in (5.800 cm) |
| Package 1 Weight | 7.760 oz (220.000 g) |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 36 |
| Package 2 Height | 11.811 in (30.000 cm) |
| Package 2 Width | 15.748 in (40.000 cm) |
| Package 2 Length | 23.622 in (60.000 cm) |
| Package 2 Weight | 19.156 lb(US) (8.689 kg) |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Toxic Heavy Metal Free | |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Mercury Free | |
| Rohs Exemption Information | Yes |
| | |
| Eu Rohs Directive | Compliant |
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| | Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| California Proposition 65 | WARNING: Cancer - www.P65Warnings.ca.gov |