# Product data sheet

Specifications





## TeSys Deca - contactor coil -LX1D6 - 24 V AC 60 Hz for 80 & 95 A contactor

LX1D6B6

! Discontinued on: Mar 13, 2024

(!) Discontinued

Product availability: Stock - Normally stocked in distribution facility

Price\*: 117.72 USD

#### Main

Range	TeSys	
Product or Component Type	Contactor coil	
Device short name	LX1D6	
Control circuit type	AC 60 Hz	
[Uc] control circuit voltage	24 V AC 60 Hz	
Average resistance	1.05 Ohm 68 °F (20 °C)	
Inductance of closed circuit	0.06 H	
Product Compatibility	LC1D40 LC1D50 LC1D65D95	
Mechanical durability	4 Mcycles	
Maximum operating rate	3600 cyc/h 140 °F (60 °C)	

### Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <131 °F (55 °C)) Operational: 0.81.1 Uc at 50 Hz (at <131 °F (55 °C)) Operational: 0.851.1 Uc at 60 Hz (at <131 °F (55 °C))
Inrush power in VA	220 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	22 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	610 W 50/60 Hz

#### **Environment**

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Net Weight	0.62 lb(US) (0.28 kg)

### Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
GTIN	3389110208450	
Returnability	No	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin US

## **Packing Units**

PCE
1
3.465 in (8.800 cm)
4.961 in (12.600 cm)
2.126 in (5.400 cm)
11.287 oz (320.000 g)
S02
16
5.906 in (15.000 cm)
11.811 in (30.000 cm)
15.748 in (40.000 cm)
11.861 lb(US) (5.380 kg)
P06
256
29.528 in (75.000 cm)
31.496 in (80.000 cm)
23.622 in (60.000 cm)
207.411 lb(US) (94.080 kg)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Reach Free Of Svhc	
<b>②</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov