



Contactor coil, TeSys Deca, LX1D6, 480 V AC 60Hz for 80 and 95A contactor

LX1D6T6

Product availability: Stock - Normally stocked in distribution

Price*: 52.32 USD

Main

Range	TeSys	
Product or Component Type	Contactor coil	
Device short name	LX1D6	
Control circuit type	AC 60 Hz	
[Uc] control circuit voltage	480 V AC 60 Hz	
Average resistance	480 Ohm 68.0000000000 °F (20 °C)	
Inductance of closed circuit	23 H	
Product Compatibility	LC1D80 LC1D95	
Mechanical durability	10 Mcycles	
Maximum operating rate	3600 cyc/h 140 °F (60 °C)	

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <131 °F (55 °C)) Operational: 0.81.1 Uc at 50 Hz (at <131 °F (55 °C)) Operational: 0.851.1 Uc at 60 Hz (at <131 °F (55 °C))	
Inrush power in VA	220 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C))	
Hold-in power consumption in VA	A 22 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))	
Heat dissipation	dissipation 610 W 50/60 Hz	

Environment

Ambient Air Temperature for Operation	23140 °F (-560 °C)	
Net Weight	0.62 lb(US) (0.28 kg)	

Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
GTIN	3389110208832	
Returnability	Yes	
Country of origin	CZ	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.362 in (6.000 cm)	
Package 1 Width	3.504 in (8.900 cm)	
Package 1 Length	5.039 in (12.800 cm)	
Package 1 Weight	10.9 oz (308 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	16	
Package 2 Height	5.906 in (15.000 cm)	
Package 2 Width	11.811 in (30.000 cm)	
Package 2 Length	ength 15.748 in (40.000 cm)	
Package 2 Weight	age 2 Weight 11.528 lb(US) (5.229 kg)	

Contractual warranty

Warranty 18 months

Oct 14, 2024



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Reach Free Of Svhc	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov