Specifications



TeSys F - contactor coil - LX1FG - 220 V AC 60Hz

LX1FG184

() Discontinued on: 8 Oct 2021

() Discontinued

Main

Range	TeSys
product or component type	Contactor coil
Device short name	LX1FG
Range compatibility	TeSys TeSys F LC1F contactor
Product compatibility	LC1F225 LC1F185
Control circuit type	AC at 60 Hz
[Uc] control circuit voltage	220 V AC 60 Hz
Inductance of closed circuit	1.8 H
Average resistance	11.1 Ohm at 20 °C
Operating time	2035 ms closing 715 ms opening
Mechanical durability	10 Mcycles
Maximum operating rate	2400 cyc/h 55 °C

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.350.55 Uc 50/60 Hz (at 55 °C) Operational: 0.851.1 Uc 50/60 Hz (at 55 °C)
Inrush power in VA	970 VA 60 Hz cos phi 0.3 (at 20 °C)
Hold-in power consumption in VA	66 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	1824 W at 60 Hz

Environment

Ambient air temperature for operation	-555 °C	
net weight	0.55 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	8 cm

Package 1 Length	15.8 cm
Package 1 Weight	530 g

Contractual warranty

Warranty

18 months

Sustainability

Green Premium[™] label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu f	Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Chiı	na Rohs Regulation	China RoHS declaration