



TeSys F - contactor coil - LX1FH - 440V AC 40...400 Hz

LX1FH4402

! To be discontinued on: 31-Dec-2028

! To be discontinued

Main

Range	TeSys	
product or component type	Contactor coil	
Device short name	LX1FH	
Range compatibility	TeSys TeSys F LC1F contactor	
Product compatibility	LC1F265 LC1F330	
Control circuit type	AC at 40400 Hz	
[Uc] control circuit voltage	trol circuit voltage 440 V AC 40400 Hz	
Average resistance	265 Ohm inrush at 20 °C 6731 Ohm holding at 20 °C	
Operating time	100170 ms opening 4065 ms closing	
Mechanical durability	pility 10 Mcycles	
Maximum operating rate	2400 cyc/h 55 °C	

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.350.55 Uc 40400 Hz (at 55 °C) Operational: 0.851.1 Uc 40400 Hz (at 55 °C)
Inrush power in VA	650 VA 40400 Hz cos phi 0.9 (at 20 °C)
Hold-in power consumption in VA	10 VA 40400 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	8 W at 40400 Hz

Environment

ambient air temperature for operation	-555 °C
net weight	0.75 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	10.0 cm
Package 1 Length	18.5 cm

Package 1 Weight	830.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	10.52 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
9	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information