



TeSys F - contactor coil - LX1FK - 200.208 V AC 40...400 Hz

LX1FK200

! To be discontinued on: 31 Dec 2028

(!) To be discontinued

Main

Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1FK	
Range compatibility	TeSys TeSys F LC1F contactor	
Product compatibility	LC1F500	
Control circuit type	AC at 40400 Hz	
[Uc] control circuit voltage	200208 V AC 40400 Hz	
Inductance of closed circuit	3.75 H	
Average resistance	29 Ohm inrush at 20 °C 735 Ohm holding at 20 °C	
Operating time	100170 ms opening 4075 ms closing	
Mechanical durability	rability 10 Mcycles	
Maximum operating rate	2400 cyc/h 55 °C	

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational: 0.851.1 Uc 40400 Hz (at 55 °C) Drop-out: 0.30.5 Uc 40400 Hz (at 55 °C)
Inrush power in VA	1100 VA 40400 Hz cos phi 0.9 (at 20 °C)
Hold-in power consumption in VA	18 VA 40400 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	18 W at 40400 Hz

Environment

Ambient air temperature for operation	-555 °C
Net weight	1.15 kg

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	10.400 cm	
Package 1 Width	13.500 cm	

Package 1 Length	20.500 cm
Package 1 Weight	1.228 kg
Unit Type of Package 2	S02
Number of Units in Package 2	3
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.944 kg
Unit Type of Package 3	P06
Number of Units in Package 3	48
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	71.104 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information