



# TeSys F - contactor coil - LX1FK - 415...440V AC 40...400 Hz

LX1FK415

! To be discontinued on: 31 Dec 2028

(!) To be discontinued

#### Main

Range	TeSys	
product or component type	Contactor coil	
Device short name	LX1FK	
Range compatibility	TeSys TeSys F LC1F contactor	
Product compatibility	LC1F500	
Control circuit type	AC at 40400 Hz	
[Uc] control circuit voltage	415 V AC 40400 Hz	
Inductance of closed circuit	18.4 H	
Average resistance	143 Ohm inrush at 20 °C 3730 Ohm holding at 20 °C	
Operating time	100170 ms opening 4075 ms closing	
Mechanical durability	10 Mcycles	
Maximum operating rate	2400 cyc/h 55 °C	

## Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Operational: 0.851.1 Uc 40400 Hz (at 55 °C) Drop-out: 0.30.5 Uc 40400 Hz (at 55 °C)	
Inrush power in VA	1100 VA 40400 Hz cos phi 0.9 (at 20 °C)	
Hold-in power consumption in VA	18 VA 40400 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	18 W at 40400 Hz	

#### **Environment**

Ambient air temperature for operation	-555 °C	
net weight	1.15 kg	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.6 cm
Package 1 Width	11.2 cm

Package 1 Length	22.6 cm
Package 1 Weight	1.193 kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.717 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>Ø</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information