Product data sheet

Specifications





Contactor coil, TeSys Deca, LXD1, 110V AC 50/60Hz for 9...38A contactor

LXD1F7

Product availability: Stock - Normally stocked in distribution

Price*: 33.00 USD

Main

Range	TeSys	
Product or Component Type	Contactor coil	
Device short name	LXD1	
Control circuit type	AC 50/60 Hz	
[Uc] control circuit voltage	110 V AC 50/60 Hz	
Average resistance	124.1 Ohm 68.0000000000 °F (20 °C)	
Inductance of closed circuit	4.6 H	
Product Compatibility	LC1DT20DT40 LC1D09D38 CAD	
Mechanical durability	15 Mcycles	
Maximum operating rate	3600 cyc/h 140.0000000000 °F (60 °C)	

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <140.0000000000 °F (60 °C)) Operational: 0.81.1 Uc at 50 Hz (at <140.000000000 °F (60 °C)) Operational: 0.851.1 Uc at 60 Hz (at <140.0000000000 °F (60 °C))
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 68.0000000000 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68.0000000000 °F (20 °C))
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 68.0000000000 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68.0000000000 °F (20 °C))
Heat dissipation	23 W 50/60 Hz

Environment

Ambient Air Temperature for Operation	23.0000000000140.0000000000 °F (-560 °C)
Net Weight	0.15 lb(US) (0.07 kg)

Ordering and shipping details

Category	US10l1222341	
Discount Schedule	0112	
GTIN	3389110467734	
Returnability	No	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.575 in (4.000 cm)
Package 1 Width	2.480 in (6.300 cm)
Package 1 Length	1.772 in (4.500 cm)
Package 1 Weight	2.469 oz (70.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	100
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	16.380 lb(US) (7.430 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
②	Toxic Heavy Metal Free
⊘	Mercury Free
⊘	Rohs Exemption Information Yes
②	Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov