# Product data sheet





## TeSys Deca - contactor coil -LXD1 - 12 V AC 50/60 Hz for 9... 38 A contactor

LXD1J7

! Discontinued on: Dec 31, 2023

(!) Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Range	TeSys	
Product or Component Type	Contactor coil	
Device short name	LXD1	
Control circuit type	AC 50/60 Hz	
[Uc] control circuit voltage	12 V AC 50/60 Hz	
Average resistance	1.33 Ohm 68 °F (20 °C)	
Inductance of closed circuit	0.05 H	
Product Compatibility	LC1DT20DT40 LC1D09D38 CAD	
Mechanical durability	15 Mcycles	
Maximum operating rate	3600 cyc/h 140 °F (60 °C)	

## Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <140 °F (60 °C)) Operational: 0.81.1 Uc at 50 Hz (at <140 °F (60 °C)) Operational: 0.851.1 Uc at 60 Hz (at <140 °F (60 °C))
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	23 W 50/60 Hz

## **Environment**

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Net Weight	0.15 lb(US) (0.07 kg)

## Ordering and shipping details

Category	US10l1222341
Discount Schedule	0112
GTIN	3389110467741
Returnability	No

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Country of origin FR

## **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.378 in (3.500 cm)
Package 1 Width	1.772 in (4.500 cm)
Package 1 Length	2.756 in (7.000 cm)
Package 1 Weight	2.646 oz (75.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	100
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	17.538 lb(US) (7.955 kg)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

<b>⊘</b>	Reach Free Of Svhc
<b>⊘</b>	Toxic Heavy Metal Free
<b>⊘</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>⊘</b>	Pvc Free

### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov