Product datasheet

Specifications





TeSys D - contactor coil - LXD1 - 220 V AC 50/60 Hz for 9... 38 A contactor

LXD1M7

Main

| Range | TeSys | |
|------------------------------|---------------------------------|--|
| product or component type | Contactor coil | |
| Device short name | LXD1 | |
| Control circuit type | AC at 50/60 Hz | |
| [Uc] control circuit voltage | 220 V AC 50/60 Hz | |
| Average resistance | 515.4 Ohm at 20 °C | |
| Inductance of closed circuit | 18 H | |
| Product compatibility | CAD LC1D09D38 LC1DT20DT40 | |
| Mechanical durability | 15 Mcycles | |
| Maximum operating rate | 3600 cyc/h 60 °C | |

Complementary

| Coil technology | Without built-in suppressor module | |
|---------------------------------|--|--|
| Control circuit voltage limits | Drop-out: 0.30.6 Uc at 50/60 Hz (at <60 °C) Operational: 0.81.1 Uc at 50 Hz (at <60 °C) Operational: 0.851.1 Uc at 60 Hz (at <60 °C) | |
| Inrush power in VA | 70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C) | |
| Hold-in power consumption in VA | 7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C) | |
| Heat dissipation | 23 W at 50/60 Hz | |

Environment

| Ambient air temperature for operation | -560 °C | |
|---------------------------------------|---------|--|
| net weight | 0.07 kg | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.500 cm |
| Package 1 Width | 6.300 cm |
| Package 1 Length | 4.000 cm |
| Package 1 Weight | 67.000 g |

| Unit Type of Package 2 | S02 |
|------------------------------|-----------|
| Number of Units in Package 2 | 100 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 7.134 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| | Mercury Free | |
|----------|----------------------------|-----|
| ⊘ | Rohs Exemption Information | Yes |
| | Pvc Free | |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |