

Contactor coil, TeSys Deca, LXD3, 220V AC 50/60Hz for 40…65A contactor

LXD3M7

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 52.32 USD

Main

Range	TeSys	
Product or Component Type	Contactor coil	
Device short name	LXD3	
Control circuit type	AC 50/60 Hz	
[Uc] control circuit voltage	220 V AC 50/60 Hz	
Average resistance	182 Ohm 68.0000000000 °F (20 °C)	
Inductance of closed circuit	10 H	
Product Compatibility	ct Compatibility LC1D40AD65A LC1DT80A LC1DT60A	
Mechanical durability	6 Mcycles	
Maximum operating rate	3600 cyc/h 140.000000000 °F (60 °C)	

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <140.0000000000 °F (60 °C)) Operational: 0.81.1 Uc at 50 Hz (at <140.0000000000 °F (60 °C)) Operational: 0.851.1 Uc at 60 Hz (at <140.0000000000 °F (60 °C))
Inrush power in VA	160 VA 60 Hz cos phi 0.75 (at 68.0000000000 °F (20 °C)) 160 VA 50 Hz cos phi 0.75 (at 68.0000000000 °F (20 °C))
Hold-in power consumption in VA	15 VA 60 Hz cos phi 0.3 (at 68.0000000000 °F (20 °C)) 15 VA 50 Hz cos phi 0.3 (at 68.0000000000 °F (20 °C))
Heat dissipation	45 W 50/60 Hz

Environment

Ambient Air Temperature for Operation	23.0000000000140.0000000000 °F (-560 °C)
Net Weight	0.15 lb(US) (0.07 kg)

Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
GTIN	3389119410410	
Returnability	Yes	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin FR

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.3 in (5.8 cm)	
Package 1 Width	2.3 in (5.8 cm)	
Package 1 Length	3.9 in (9.8 cm)	
Package 1 Weight	4.0 oz (113.0 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	30	
Package 2 Height	5.9 in (15 cm)	
Package 2 Width	11.8 in (30 cm)	
Package 2 Length	ength 15.7 in (40 cm)	
Package 2 Weight	8.455 lb(US) (3.835 kg)	

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

②	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes
_		
Rea	ch Regulation	REACh Declaration
Eu F	Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
		EU RoHS Declaration
Chir	na Rohs Regulation	China RoHS declaration
		Pro-active China RoHS declaration (out of China RoHS legal scope)
Calif	fornia Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov