Product data sheet

Specifications





motion servo drive, Lexium 28, single and three phase, 200 to 240V, 100W

LXM28AU01M3X

Product availability: Stock - Normally stocked in distribution

Price*: 595.00 USD

Main

Range of Product	Lexium 28	
Device short name	LXM28A	
Product or Component Type	Motion servo drive	
Format of the drive	Compact housing	
Line current	1.2 A 239.2 % 220 V, single phase 1.2 A 212.7 % 220 V, three phase	

Complementary

Phase	Three phase Single phase	
[Us] rated supply voltage	200240 V - 1015 %)three phase 200240 V - 2015 %)single phase	
Supply voltage limits	200255 V three phase 170255 V single phase	
Supply frequency	50/60 Hz - 55 %	
Network Frequency	47.563 Hz	
EMC filter	Without EMC filter	
Continuous output current	nt 0.9 A 16 kHz	
Output current 3s peak	2.7 A 220 V	
Continuous power 100 W 220 V		
Nominal power 0.1 kW 220 V 16 kHz		
switching frequency	16 kHz	
Overvoltage category	III	
Maximum leakage current	1.3 mA	
Output voltage	<= power supply voltage	
Electrical isolation	Dn Between power and control	
Type of cable	Shielded motor cable 32.0000000000131.0000000000 °F (055 °C)) copper	
Electrical connection	Spring terminal 0.821 mm², AWG 18 L1-L2) Spring terminal 0.821 mm², AWG 18 R, S, T) Spring terminal 0.821 mm², AWG 18 U, V, W, PE) Spring terminal 0.821 mm², AWG 18 PA/+, PBe)	
Discrete input number	8 programmable CN1) 1 pulse train input (PTI) CN1) 2 fast capture CN1) 1 safety function STO CN9)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

·		
Discrete input voltage	te input voltage 24 V DC logic	
Discrete input logic	Positive or negative CN1)	
Discrete output number	5 logic output CN1)1224 V DC 1 pulse train output (PTO) CN1)	
Discrete output voltage	1224 V DC	
Discrete output logic	Positive or negative CN1)	
Analogue input number	2	
Absolute accuracy error	0.1 %	
Analogue input type	V_REF voltage analog input - 1010 V 10 kOhm 14 bits T_REF voltage analog input	
Control signal type	Servo motor encoder feedback CN2	
Protection type	Against reverse polarity inputs signal Against short-circuits outputs signal Overcurrent motor Overvoltage motor Undervoltage motor Overheating motor Overload motor Overspeed motor	
Safety function	STO (safe torque off), Integrated	
Safety level	SIL 2 IEC 61800-5-2 2007 SIL 2 IEC 61508-1 2010 PL d/category 3 ISO 13849-1 2008 SIL 2 ISO 13849-1 2009/AC SIL 2 IEC 60204-1 2006 SIL 2 IEC 60204-1 2009/A1 SIL 2 IEC 60204-1 2010/AC SIL 2 IEC 62061 2012	
Communication interface	CANopen, Integrated CANmotion, Integrated	
Communication interface Connector type		
	CANmotion, Integrated	
Connector type	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion	
Connector type Method of access	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion	
Connector type Method of access Transmission rate	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion	
Connector type Method of access Transmission rate Number of addresses	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion	
Connector type Method of access Transmission rate Number of addresses Physical interface	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED Signalling function	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CULus	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED Signalling function Marking	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CULus CE	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED Signalling function Marking Type of cooling	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CULus CE Natural convection	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED Signalling function Marking Type of cooling Operating position	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CULus CE Natural convection Vertical	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED Signalling function Marking Type of cooling Operating position Product compatibility	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CULus CE Natural convection Vertical Servo motor BCH2 1.6 in (40 mm), 2 100 W	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED Signalling function Marking Type of cooling Operating position Product compatibility Width	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CULus CE Natural convection Vertical Servo motor BCH2 1.6 in (40 mm), 2 100 W 2.2 in (55 mm)	
Connector type Method of access Transmission rate Number of addresses Physical interface Status LED Signalling function Marking Type of cooling Operating position Product compatibility Width Height	CANmotion, Integrated RJ45 CN4)CANopen, CANmotion Slave 250 kbit/s 328.08820.2 ft (100250 m) CANopen, CANmotion 500 kbit/s 13.1328.08 ft (4100 m) CANopen, CANmotion 1 Mbit/s 13.1 ft (4 m) CANopen, CANmotion 1127 CANopen, CANmotion RS485 Modbus Serial line slave 1 LED (Red) charge 1 LED (Green) RUN 1 LED (Red) error Servo status and fault codes five 7-segment display units CSA CULus CE Natural convection Vertical Servo motor BCH2 1.6 in (40 mm), 2 100 W 2.2 in (55 mm) 5.9 in (150 mm)	

Environment

Electromagnetic compatibility	Conducted emission - test level: level 3 category C3 conforming to IEC 61800-3	
Standards	IEC 61800-5-1	
Product Certifications	CE CSA cULus	
IP degree of protection	IP20	
Vibration resistance	3M4 3 mm 9200 Hz)IEC 60721-3-3	
Shock resistance	10 gn, type I IEC 60721-3-3	
Relative humidity	595 % without condensation	
Ambient Air Temperature for Operation	32.0000000000131.0000000000 °F (055 °C)	
Ambient Air Temperature for Storage	-13.0000000000149.0000000000 °F (-2565 °C)	
Operating altitude	<= 3280.84 ft (1000 m) without derating > 3280.846561.68 ft (> 10002000 m) 1 % per 100 m	

Ordering and shipping details

Category	US1PC5118262	
Discount Schedule	PC51	
GTIN	3606480711763	
Returnability	Yes	
Country of origin	CN	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.0 in (7.5 cm)	
Package 1 Width	9.06 in (23 cm)	
Package 1 Length	9.3 in (23.7 cm)	
Package 1 Weight	2.78 lb(US) (1.26 kg)	
Unit Type of Package 2	\$03	
Number of Units in Package 2	5	
Package 2 Height	11.8 in (30 cm)	
Package 2 Width	11.8 in (29.9 cm)	
Package 2 Length	15.7 in (39.8 cm)	
Package 2 Weight	15.19 lb(US) (6.89 kg)	
Unit Type of Package 3	PAL	
Number of Units in Package 3	40	
Package 3 Height	23.6 in (60 cm)	
Package 3 Width	23.6 in (60 cm)	
Package 3 Length	31.5 in (80 cm)	
Package 3 Weight	121.52 lb(US) (55.12 kg)	

Sustainability Green Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
②	Mercury Free	
②	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Product data sheet

LXM28AU01M3X

Dimensions Drawings

Dimensions

Dimensions of Drive



Jul 19, 2024

LXM28AU01M3X

Mounting and Clearance

Mounting Clearance

Mounting Distances and Air Circulation

mm in.

