Product datasheet





Motion servo drive, Lexium 32, single phase supply voltage 115/230 V, 0.3/0.5 kW

LXM32AU90M2

EAN Code: 3606480076749

Main

-		
Range of product	Lexium 32	
Device short name	LXM32A	
product or component type	Motion servo drive	
Format of the drive	Book	
Network number of phases	Single phase	
[Us] rated supply voltage	100120 V - 1510 % 200240 V - 1510 %	
Supply voltage limits	85132 V 170264 V	
Supply frequency	50/60 Hz - 55 %	
Network frequency	47.563 Hz	
EMC filter	Integrated	
Continuous output current	3 A at 8 kHz	
Output current 3s peak	6 A at 115 V for 5 s 9 A at 230 V for 5 s	
maximum continuous power	us power 400 W at 115 V 900 W at 230 V	
Nominal power	0.3 kW at 115 V 8 kHz 0.5 kW at 230 V 8 kHz	
Line current	5.2 A 90 % at 115 V, with external line choke of 2 mH 6.3 A 107 % at 230 V, with external line choke of 2 mH 5.4 A 159 % at 115 V, without line choke 4.5 A 166 % at 230 V, without line choke	

Complementary

•		
switching frequency	8 kHz	
Overvoltage category	III	
Maximum leakage current	30 mA	
Output voltage	<= power supply voltage	
Electrical isolation	Between power and control	
Type of cable	Single-strand IEC cable (temperature: 50 °C) copper 90 °C XLPE/EPR	
Electrical connection	Terminal, clamping capacity: 3 mm², AWG 12 (CN8) Terminal, clamping capacity: 5 mm², AWG 10 (CN1) Terminal, clamping capacity: 5 mm², AWG 10 (CN10)	
Tightening torque	CN8: 0.5 N.m CN1: 0.7 N.m CN10: 0.7 N.m	

4 Jul 2024 Life Is On Schneider

Discrete input number	1 capture discrete input(s) 2 safety discrete input(s) 4 logic discrete input(s)	
Discrete input type	Capture (CAP terminals) Logic (DI terminals) Safety (compliment of STO_A, compliment of STO_B terminals)	
Sampling duration	DI: 0.25 ms discrete	
Discrete input voltage	24 V DC for capture 24 V DC for logic 24 V DC for safety	
Discrete input logic	Positive (compliment of STO_A, compliment of STO_B) at State 0: < 5 V at State 1: > 15 V conforming to EN/IEC 61131-2 type 1 Positive (DI) at State 0: > 19 V at State 1: < 9 V conforming to EN/IEC 61131-2 type 1 Positive or negative (DI) at State 0: < 5 V at State 1: > 15 V conforming to EN/IEC 61131-2 type 1	
Response time	<= 5 ms compliment of STO_A, compliment of STO_B	
Discrete output number	2	
Discrete output type	Logic output(s) (DO)24 V DC	
Discrete output voltage	<= 30 V DC	
Discrete output logic	Positive or negative (DO) conforming to EN/IEC 61131-2	
Contact bounce time	<= 1 ms for compliment of STO_A, compliment of STO_B 2 μs for CAP 0.25 μs1.5 ms for DI	
Braking current	50 mA	
Response time on output	250 μs (DO) for discrete output(s)	
Control signal type	Servo motor encoder feedback	
Protection type	Against reverse polarity: inputs signal Against short-circuits: outputs signal	
Safety function	STO (safe torque off), integrated	
Safety level	SIL 3 conforming to EN/IEC 61508 PL = e conforming to ISO 13849-1	
Communication interface	CANmotion, integrated CANopen, integrated Modbus, integrated	
Connector type	RJ45 (labelled CN4 or CN5) for CANmotion RJ45 (labelled CN4 or CN5) for CANopen RJ45 (labelled CN7) for Modbus	
Method of access	Slave	
commissioning port	2-wire RS485 multidrop for Modbus	
Transmission rate	1 Mbps for bus length of 4 m for CANopen, CANmotion 125 kbps for bus length of 500 m for CANopen, CANmotion 250 kbps for bus length of 250 m for CANopen, CANmotion 50 kbps for bus length of 1000 m for CANopen, CANmotion 500 kbps for bus length of 100 m for CANopen, CANmotion 9600, 19200, 38400 bps for bus length of 40 m for Modbus	
Number of addresses 1127 for CANopen, CANmotion 1247 for Modbus		

Communication service	1 receive SDO for CANmotion 1 transmit SDO for CANmotion 2 PDOs conforming to DSP 402 for CANmotion 2 SDOs receive for CANopen 2 SDOs send for CANopen 4 configurable mapping PDOs for CANopen CANopen device profile drives and motion control for CANopen, CANmotion Display of faults on integrated display terminal for Modbus Emergency for CANopen, CANmotion Event-triggered, time-triggered, remotely requested,sync (cyclic), sync(acyclic) for CANopen Node guarding, heartbeat for CANopen Position control mode for CANmotion Position control, speed profile, torque profile and homing mode for CANopen Sync for CANmotion	
Status LED	1 LED (red) servo drive voltage 1 LED error 1 LED RUN	
Signalling function	Display of faults 7 segments	
marking	CE	
Operating position	Vertical +/- 10 degree	
Product compatibility	Servo motor BMH (70 mm, 1 motor stacks) Servo motor BSH (70 mm, 1 motor stacks) Servo motor BSH (55 mm, 3 motor stacks) Servo motor BSH (55 mm, 1 motor stacks) Servo motor BSH (55 mm, 2 motor stacks)	
Width	48 mm	
Height	270 mm	
Depth	237 mm	
net weight	1.7 kg	

Environment

Electromagnetic compatibility	Conducted EMC, class A group 1 conforming to EN 55011 Conducted EMC, class A group 2 conforming to EN 55011 Conducted EMC, environment 2 category C3 conforming to EN/IEC 61800-3 Conducted EMC, category C2 conforming to EN/IEC 61800-3 Conducted EMC, environments 1 and 2 conforming to EN/IEC 61800-3 Electrostatic discharge immunity test, level 3 conforming to EN/IEC 61000-4-2 Susceptibility to electromagnetic fields, level 3 conforming to EN/IEC 61000-4-3 1.2/50 µs shock waves immunity test, level 3 conforming to EN/IEC 61000-4-5 Electrical fast transient/burst immunity test, level 4 conforming to EN/IEC 61000-4-4 Radiated EMC, class A group 2 conforming to EN 55011 Radiated EMC, category C3 conforming to EN/IEC 61800-3	
Standards	EN/IEC 61800-3 EN/IEC 61800-5-1	
Product certifications	UL CSA TÜV	
IP degree of protection	IP20 conforming to EN/IEC 60529 IP20 conforming to EN/IEC 61800-5-1	
Vibration resistance	1 gn (f= 13150 Hz) conforming to EN/IEC 60068-2-6 1.5 mm peak to peak (f= 313 Hz) conforming to EN/IEC 60068-2-6	
Shock resistance	15 gn for 11 ms conforming to EN/IEC 60028-2-27	
Pollution degree	2 conforming to EN/IEC 61800-5-1	
Environmental characteristic	Classes 3C1 conforming to IEC 60721-3-3	
Relative humidity	Class 3K3 (5 to 85 %) without condensation conforming to IEC 60721-3-3	
Ambient air temperature for operation	050 °C conforming to UL	
Ambient air temperature for storage	-2570 °C	

4 Jul 2024 Life Is On Schneider 3

Type of cooling	Natural convection	
Operating altitude	<= 1000 m without derating > 10003000 m with conditions	

Packing Units

PCE
1
8.5 cm
27.5 cm
33 cm
2.112 kg
S03
3
30 cm
30 cm
40 cm
7.246 kg
P06
24
80 cm
80 cm
60 cm
64.892 kg

Contractual warranty

Warranty 18 months

4 Jul 2024



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards

Circularity Profile	End of Life Information		
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
Environmental Disclosure	Product Environmental Profile		
China Rohs Regulation	China RoHS declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
Reach Regulation	REACh Declaration		


Product datasheet

LXM32AU90M2

Dimensions Drawings

Lexium 32 Servo Drive


Dimensions



Mounting and Clearance

Lexium 32 Motion Control Servo Drives

Mounting Recommendations



LXM32•U45M2, •U90M2 and LXM32•U60N4 servo drives are cooled by natural convection. LXM32•D18M2, •D30M2, LXM32 •D12N4, •D18N4, •D30N4 and •D72N4servo drives have an integrated fan.

When installing the servo drive in the enclosure, follow the instructions below with regard to the temperature and protection index:

- Provide sufficient cooling of the servo drive
- Do not mount the servo drive near heat sources
- . Do not mount the servo drive on flammable materials
- Do not heat the servo drive cooling air by currents of hot air from other equipment and components, for example from an external braking resistor
- Mount the servo drive vertically (± 10%)
- If the servo drive is used above its thermal limits, control stops due to overtemperature

NOTE: For cables that are connected via the underside of the servo drive, a free space ≥ 200 mm/7.87 in. is required under the unit to comply with the bending radius of the connection cables.

Ambient temperature	Mounting distances	Instructions to be followed
0°C+ 50°C	d ≥ 0 mm	-
+ 50°C+ 60°C	d ≥ 0 mm	Reduce the output current by 2.2% per °C above 50°C

NOTE: Do not use insulated enclosures, as they have a poor level of conductivity.


Recommendations for Mounting in an Enclosure

To ensure good air circulation in the servo drive:

- Fit ventilation grilles on the enclosure.
- Ensure that ventilation is adequate, otherwise install a forced ventilation unit with a filter.

Product datasheet

LXM32AU90M2



- (1) Natural convection
- (2) Forced ventilation
 - Any apertures and/or fans must provide a flow rate at least equal to that of the servo drive fans (refer to characteristics).
 - Use special filters with IP 54 protection.

Mounting in Metal Enclosure (IP 54 Degree of Protection)

The servo drive must be mounted in a dust and damp proof enclosure in certain environmental conditions, such as dust, corrosive gases, high humidity with risk of condensation and dripping water, splashing liquid, etc. In these cases, Lexium 32 servo drives can be installed in an enclosure where the internal temperature must not exceed 60°C.