Product data sheet

Specifications

Multi9 - shunt trip release - MX - 48 V AC - 48 V DC

M9A26477

Product availability: Stock - Normally stocked in distribution facility

Price*: 165.00 USD

Main

range of product	Multi9
Product or Component Type	Shunt trip release
Device short name	MX
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 Multi9 C60 C60BP Multi 9 Multi9 C60 C60BPR Multi 9 Multi9 C60 C60SP Multi 9 Multi9 GFP GFP Multi 9 Multi9 C60H-DC C60H-DC
local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Comb busbar and distribution block compatibility	Top YES
Height	3.2 in (82.5 mm)
Width	0.7 in (18 mm)
Depth	2.7 in (68 mm)
Net Weight	0.13 lb(US) (0.06 kg)
Connections - terminals	Clamp terminal bottom) - 1 0.004 in² (2.5 mm²) AWG 14) - rigid Clamp terminal bottom) - 2 0.002 in² (1.5 mm²) AWG 16) - rigid
Wire stripping length	0.4 in (9 mm) for bottom connection
Tightening torque	8.9 lbf.in (1 N.m) bottom

Environment

Standards	EN/IEC 60947-1
Product Certifications	UR UL PCT
Pollution degree	3
Tropicalisation	2 EN/IEC 60947-1
Relative humidity	95 % 131.0000000000 °F (55 °C)
Ambient Air Temperature for Operation	-13.0000000000…122.0000000000 °F (-25…50 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Storage	-40.0000000000...185.0000000000 °F (-40...85 °C)

Ordering and shipping details

Category	US10DE200948
Discount Schedule	0DE2
GTIN	3606480639029
Returnability	Yes
Country of origin	BE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.1 in (2.9 cm)
Package 1 Width	3.1 in (8 cm)
Package 1 Length	3.7 in (9.4 cm)
Package 1 Weight	2.5 oz (70 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	3.4 in (8.7 cm)
Package 2 Width	3.9 in (10 cm)
Package 2 Length	10.4 in (26.5 cm)
Package 2 Weight	22.05 oz (625 g)
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	13.475 lb(US) (6.112 kg)

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations