

Product data sheet

Specifications



Multi9 - shunt trip release with OC contact - MX + OF - 12/24 V AC - 12/24 V DC

M9A26948

Product availability: Stock - Normally stocked in distribution facility

Price*: 140.00 USD

Main

range of product	Multi9
Product or Component Type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
Line Rated Current	6 A at <= 240 V, AC
[Uc] control circuit voltage	12...24 V AC 50/60 Hz 12...24 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 Multi9 C60 C60BP Multi 9 Multi9 C60 C60BPR Multi 9 Multi9 C60 C60SP Multi 9 Multi9 GFP GFP Multi 9 Multi9 C60H-DC C60H-DC
local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Height	3.2 in (82.5 mm)
Width	0.7 in (18 mm)
Depth	2.7 in (68 mm)
Net Weight	0.143 lb(US) (0.065 kg)
Connections - terminals	Clamp terminal bottom) - 1 0.004 in² (2.5 mm²) AWG 14) - rigid Clamp terminal bottom) - 2 0.002 in² (1.5 mm²) AWG 16) - rigid
Wire stripping length	0.4 in (9 mm) for bottom connection
Tightening torque	8.9 lbf.in (1 N.m) bottom

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Product Certifications	CCC PCT UL UR
Pollution degree	3

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Operation	-13...122 °F (-25...50 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	US10DE200948
Discount Schedule	0DE2
GTIN	3606480639098
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.2 in (3 cm)
Package 1 Width	3.1 in (8 cm)
Package 1 Length	3.7 in (9.4 cm)
Package 1 Weight	2.6 oz (75 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	3.4 in (8.6 cm)
Package 2 Width	3.9 in (10 cm)
Package 2 Length	10.4 in (26.5 cm)
Package 2 Weight	23.3 oz (660 g)
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	14.158 lb(US) (6.422 kg)

Sustainability



Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations